

Modular Session Types for Objects

Simon J. Gay
University of Glasgow

Nils Gesbert
Grenoble INP – Ensimag

António Ravara
Universidade Nova de Lisboa

Vasco T. Vasconcelos
Universidade de Lisboa

May 27, 2011

Abstract

Session types allow communication protocols to be specified type-theoretically so that protocol implementations can be verified by static type checking. We extend previous work on session types for distributed object-oriented languages in three ways. (1) We attach a session type to a class definition, to specify the possible sequences of method calls. (2) We allow a session type (protocol) implementation to be *modularized*, i.e. partitioned into separately-callable methods. (3) We treat session-typed communication channels as objects, integrating their session types with the session types of classes. The result is an elegant unification of communication channels and their session types, distributed object-oriented programming, and a form of typestate supporting non-uniform objects, i.e. objects that dynamically change the set of available methods. We define syntax, operational semantics, a sound type system, and a sound and complete type checking algorithm for a small distributed class-based object-oriented language with structural subtyping. Static typing guarantees that both sequences of messages on channels, and sequences of method calls on objects, conform to type-theoretic specifications, thus ensuring type-safety. The language includes expected features of session types, such as delegation, and expected features of object-oriented programming, such as encapsulation of local state. The main ideas presented herein have been implemented as a prototype, extending Java 1.4.

1 Introduction

Session types [60, 37] allow communication protocols to be specified type-theoretically, so that protocol implementations can be verified by static type checking. The underlying assumption is that we have a concurrent or distributed system with bi-directional point-to-point communication channels. A session type describes the protocol that should be followed on a particular channel; that is to say, it defines the permitted sequences, types and directions of messages. For example, the session type $S = ![\text{Int}] . ?[\text{Bool}] . \text{end}$ specifies that an integer must be sent and then a boolean must be received, and there is no further communication. More generally, branching and repetition can also be specified. A session type can be regarded as a finite-state automaton whose transitions are annotated with types and directions, and whose language defines the protocol.

Session types were originally formulated for languages closely based on process calculus. Since then, the idea has been applied to functional languages [32, 49, 62, 54, 33], component-based object systems [61], object-oriented languages [[25]; [24, 22, 23]; [39, 13]], operating system services [26] and more general service-oriented systems [14]. Session types have also been generalized from two-party to multi-party systems [8, 36], although in the present paper we will only consider the two-party case.

We are interested in combining session-typed channels and object-oriented programming. The references above can be divided into two groups. The approach of Dezani-Ciancaglini et al. is for a class to define sessions *instead of* methods. Invoking a session on an object creates a channel which is used for communication between two blocks of code: the body of the session, and a *co-body* defined by the invoker of the session. A session is therefore a generalization of a method, in which there can be an extended dialogue between caller and callee instead of a single exchange of parameters and result. The structure of this dialogue is defined by a session type.

The SJ (Session Java) language developed by Hu is a less radical extension of the object-oriented paradigm. Channels, described by session types, are essentially the same as those in the original work based on process calculus. Program code is located in methods, as usual, and can create channels, communicate on them, and pass them as messages. SJ has a well-developed implementation and has been applied to a range of situations, and more recently has been extended to support event-driven programming. However, SJ has one notable restriction: a channel cannot be stored in a field. This means that a channel, once created, must be either completely used, or else delegated, within the same method. It is not possible for a session to be split into methods that can be called separately.

In previous work [30] we proposed a new approach to combining session-typed communication channels and distributed object-oriented programming. Our approach extends earlier work and allows increased programming flexibility. We adopted the principle that it should be possible to store a channel in a field of an object and allow the object’s methods to use the field like any other; we then followed the consequences of this idea. For example, consider a field containing a channel of type S above, and suppose that method m sends the integer and method n receives the boolean. Because the session type of the channel requires the send to occur first, it follows that m must be called before n . We therefore need to work with *non-uniform objects*, in which the availability of methods depends on the state of the object: method n is not available until after method m has been called. In order to develop a static type system for object-oriented programming with session-typed channels, we use a form of typestate [59] that we have previously presented under the name of *dynamic interfaces* [63]. In this type system, the availability of a class’s methods (i.e., the possible sequences of method calls) is specified in a style that itself resembles a form of session type, giving a pleasing commonality of notation at both the channel and class levels.

The result of this combination of ideas is a language that allows a very natural integration of programming with session-based channels and with non-uniform objects. In particular, the implementation of a session can be *modularized* by dividing it into separate methods that can be called in turn. This is not possible in SJ [39], the most closely related approach to combining sessions and objects. We believe that we have achieved a smooth and elegant combination of three important high-level abstractions: the object-oriented abstraction for structuring computation and data, the typestate abstraction for structuring state-dependent method availability, and the session abstraction for structuring communication.

In the present paper we formalize a core *distributed class-based object-oriented* language with a static type system that combines session-typed channels and a form of typestate. The formal language differs from that introduced in our previous work [30] by using structural rather than nominal types. This allows several simplifications of the type system. We have also simplified the semantics, and revised and extended the presentation. We prove that static typing guarantees two runtime safety properties: first, that the sequence of method calls on every non-uniform object follows the specification of its class’s session type; second, as a consequence (because channel operations are implemented as method calls), that the sequence of messages on every channel follows the specification of its session type. This paper includes full statements and proofs of type safety, in contrast to the abbreviated presentation in our conference paper. We also formalize a type checking algorithm and prove its correctness, again with a revised and expanded presentation in comparison with the conference paper.

There is a substantial literature of related work, which we discuss in detail in Section 9. Very briefly, the contributions of our paper are the following.

- In contrast to other work on session types for object-oriented languages, we do not require a channel to be created and completely used (or delegated) within a single method. Several methods can operate on the same channel, thus allowing effective encapsulation of channels in objects, while retaining the usual object-oriented development practice. This is made possible by our integration of channels and non-uniform objects. This contribution was the main motivation for our work.
- In contrast to other typestate systems, we use a global specification of method availability, inspired by session types, as part of a class definition. This replaces pre- and post-condition annotations on method definitions, except in the particular case of recursive methods.

```

// Style 1: method signatures with their definitions
class File {
  session Init
  where Init = {open: ⟨OK: Open, ERROR: Init⟩}
             Open = {hasNext: ⟨TRUE: Read, FALSE: Close⟩, close: Init}
             Read = {read: Open, close: Init}
             Close = {close: Init}
  {OK, ERROR} open(String filename) {...}
  {TRUE, FALSE} hasNext() {...}
  String read() {...}
  Null close() {...}
}

// Style 2: method signatures in the session type
class File {
  session Init
  where Init = { {OK, ERROR} open(String): ⟨OK: Open, ERROR: Init⟩}
             Open = { {TRUE, FALSE} hasNext(): ⟨TRUE: Read, FALSE: Close⟩,
                     Null close(): Init }
             Read = {String read(): Open, Null close(): Init}
             Close = {Null close(): Init}
  open(filename) {...}
  hasNext() {...}
  read() {...}
  close() {...}
}

```

Figure 1: A class describing a file in some API, defined in two styles

- When an object’s typestate depends on the *result* (in an enumerated type) of a method call, meaning that the result must be case-analyzed before using the object further, we do not force the case-analysis to be done immediately by using a combined “switch-call” primitive. Instead, the method result can be stored in a field and the case-analysis can happen at any subsequent point. Although this feature significantly increases the complexity of the formal system and could be omitted for simplicity, it supports a natural programming style and gives more options to future programming language designers.
- Our structural definition of subtyping provides a flexible treatment of relationships between typestates, without requiring a large inheritance hierarchy to be defined.

The remainder of the paper is structured as follows. In Section 2 we illustrate the concept of dynamic interfaces by means of a sequential example. In Section 3 we formalize a core sequential language and in Section 4 we describe some extensions. In Section 5 we extend the sequential example to a distributed setting and in Section 6 we extend the formal language to a core distributed language. In Section 7 we state and prove the key properties of the type system. In Section 8 we present a type checking algorithm and prove its soundness and completeness, and describe a prototype implementation of a programming language based on the ideas of the paper. Section 9 contains a more extensive discussion of related work; Section 10 outlines future work and concludes.

2 A Sequential Example

A file is a natural example of an object for which the availability of its operations depends on its state. The file must first be opened, then it can be read repeatedly, and finally it must be closed. Before reading from the file, a test must be carried out in order to determine whether or not any data is present. The file can be closed at any time.

There is a variety of terminology for objects of this kind. [57] refer to them as *non-uniform*. We have previously used the term *dynamic interface* [63] to indicate that the interface, i.e. the set of available operations, changes with time. The term *typestate* [59] is also well established.

Figure 1 defines the class `File`, which we imagine to be part of an API for using a file system. The definition does not include method bodies, as these would typically be implemented natively




Figure 2: Diagrammatic representation of the session type of class `File` in Figure 1

by the file system. What it does contain is method signatures and, crucially, a session type definition which specifies the availability of methods. We will refer to a skeleton class definition of this kind as an *interface*, using the term informally to mean that method definitions are omitted.

The figure shows the same definition written in two styles. Style 1 writes method signatures as part of the method definitions, as is normal in many programming languages, and writes only method names in the session type. Style 2 writes the method signatures in the session type and not as part of the method definitions. Style 2 is closer to the formal language that we will define in Section 3, while Style 1 is sometimes less verbose. The detailed explanation of this example, below, refers to Style 1.

Line 3 declares the initial session type `Init` for the class. This and other session types are defined on lines 4–7. We will explain them in detail; they are abstract states of objects, indicating which methods are available in a given state and which is the state after calling a method. In a session type, the constructor `{...}`, which we call *branch*, indicates that certain methods are available. In this example, `Init` declares the availability of one method (`open`), states `Open` and `Read` allow for two methods each, and state `Close` for a single method (`close`). For technical convenience, the presence of data is tested by calling the method `hasNext`, in the style of a Java iterator, rather than by calling an `endOfFile` method. If desired, method `hasNext` could also be included in state `Read`.

The constructor `< ... >`, which we call *variant*, indicates that a method returns a value from an enumeration, and that the subsequent state (session type) depends on the result. For example, from state `Init` the only available method is `open`, and it returns a value from an enumeration comprising the constants (or labels) `OK` and `ERROR`. If the result is `OK` then the next state is `Open`; if the result is `ERROR` then the state remains `Init`. It is also possible for a session type to be the empty set of methods, meaning that no methods are available; this feature is not used in the present example, but would indicate the end of an object’s useful life.

The session type can be regarded as a finite state automaton whose transitions correspond to method calls and results. This is illustrated in Figure 2.

Lines 8–11 define the signatures of four methods. We have already explained that their definitions are omitted; however, we will soon see an example of a full class definition including method definitions.

Our language does not include constructor methods as a special category, but the method `open` must be called first and can therefore be regarded as doing initialisation that might be included in a constructor. Notice that `open` has the filename as a parameter. Unlike a typical file system API, creating an object of class `File` does not associate it with a particular file; instead this happens when `open` is called.

```

class FileReader {
  session {init: {read: Final}}
  where Final = {toString: Final}

  file; text;

  Null init() {
    file = new File();
    text = ""; // Evaluates to null
  }
  Null read(String filename) {
    switch (file.open(filename)) {
      case ERROR:
        null;
      case OK:
        while (f.hasNext())
          text = text + file.read();
        file.close(); // Returns null
    }
  }
  String toString() { text; }
}

```

Figure 3: A client that reads from a File

The reader might expect a declaration **void** `close()` rather than **Null** `close()`; for simplicity, we do not address procedures in this paper, instead working with the type **Null** inhabited by a single value, **null**. Methods `open` and `hasNext` return a constant from an enumeration: **OK** or **ERROR** for method `open`, and **TRUE** or **FALSE** for method `hasNext`. Enumerations are simply sets of labels, and do not need to be declared with names.

Figure 3 defines (using Style 1) the class `FileReader`, which uses an object of class `File`. `FileReader` has a session type of its own, defined on lines 2–3. It specifies that methods must be called in the sequence `init`, `read`, `toString`, `toString`, `...`. Line 5 defines the fields of `FileReader`. The formal language does not require a type declaration for fields, since fields always start with type **Null**, and are initialised to value **null**. Lines 7–10 define the method `init`, which has initialisation behaviour typical of a constructor. Lines 12–19 illustrate the **switch** construct. In this particular case the **switch** is on the result of a method call. One of the distinctive features of our language is that it is possible, instead, to store the result of the method call in a field and later **switch** on the field; we will explain this in detail later. This contrasts with, for example, *Sing#* [26], in which the call/**switch** idiom is the only possibility. The **while** loop (lines 16–17) is similar in the sense that the result of `file.hasNext()` must be tested in order to find out whether the loop can continue, calling `file.read()`, or must terminate. Line 21 defines the method `toString` which simply accesses a field.

Clearly, correctness of this code requires that the sequence of method calls on field `file` within class `FileReader` matches the available methods in the session type of class `File`, and that the appropriate **switch** or **while** loops are performed when prescribed by session types of the form $\langle \dots \rangle$ in class `File`. Our static type system, defined in Section 3, enables this consistency to be checked at compile-time. In order to check statically that an object with a dynamic interface such as `file` is used correctly, our type system treats the reference linearly so that aliases to it cannot be created. This restriction is not a problem for a simple example such as this one, but there is a considerable literature devoted to more flexible approaches to unique ownership. We discuss this issue further in Sections 9 and 10.

In order to support *separate compilation* we require only the interface of a class, including the session type and the signature of each method. The exact information required by our type system is in Figure 4; here it is very convenient to use Style 2, with the method signatures in the session types, and drop the method definitions completely. Our formal language uses session types of this form, meaning that an interface is simply a session type. For example, in order to typecheck classes that are clients of `FileReader`, we only need its interface, as defined in Figure 4. Similarly, to typecheck class `FileReader`, which is a client of `File`, it suffices to use the interface for

```

class File {
  session Init
  where Init = {{OK,ERROR} open(String f): ⟨OK: Open, ERROR: {}⟩}
         Open = {{TRUE,FALSE} hasNext(): ⟨TRUE: Read, FALSE: Close⟩,
                Null close(): {}}
         Read = {String read(): Open, Null close(): {}}
         Close = {Null close(): {}}
}

class FileReader {
  session {Null init(): {Null read(String filename): Final}}
  where Final = {String toString(): Final}
}

class FileReadToEnd {
  session Init
  where Init = {{OK,ERROR} open(String f): ⟨OK: Open, ERROR: {}⟩}
         Open = {{TRUE,FALSE} hasNext(): ⟨TRUE: Read, FALSE: Close⟩}
         Read = {String read(): Open}
         Close = {Null close(): {}}
}

```

Figure 4: Interfaces for classes File, FileReader and FileReadToEnd

class File in the same figure, thus effectively supporting typing clients of classes containing *native methods*.

Figure 4 also defines the interface for a class FileReadToEnd. This class has the same method definitions as File, but the close method is not available until all of the data has been read. According to the subtyping relation defined in Section 3.3, state Init of File is a subtype of state Init of FileReadToEnd, which we express as $\text{File.Init} <: \text{FileReadToEnd.Init}$. Subtyping guarantees safe substitution: an object of type File.Init can be used whenever an object of type $\text{FileReadToEnd.Init}$ is expected, by forgetting that close is available in more states. As it happens, FileReader reads all of the data from its File object and could use a FileReadToEnd instead.

3 A Core Sequential Language

We now present the formal syntax, operational semantics, and type system of a core sequential language. As usual, the formal language makes a number of simplifications with respect to the more practical syntax used in the examples in Section 2.

- All objects are non-uniform, with session types, and are treated strictly linearly by the type system. A practical language would also need standard objects, treated non-linearly. Adding them to the type system, orthogonally to linear objects, is straightforward but complicates and obscures the typing rules.
- Every method has exactly one parameter. This does not affect expressivity, as multiple parameters can be passed within an object, and a dummy parameter can be added if necessary: we consider a method call of the form $f.m()$ as an abbreviation for $f.m(\text{null})$. It is easy to generalize the definitions to allow arbitrary numbers of parameters, but again at the expense of complicating the typing rules.
- Field access and assignment are defined in terms of a swap operation $f \leftrightarrow e$ which puts the value of e into the field f and evaluates to the former content of f . This operation is formally convenient because, due to strict linearity, extracting the value of a field also requires updating its value to null. The normal assignment operation $f = e$ is an abbreviation for $f \leftrightarrow e; \text{null}$ (where the sequence operator explicitly discards the former content of f) and field access as the standalone expression f is an abbreviation for $f \leftrightarrow \text{null}$.
- The formal system only uses Style 2, with method signatures appearing in session types and only there. This simplifies the treatment of subtyping and, when we consider a distributed

Class dec	$D ::= \text{class } C \{S; \vec{f}; \vec{M}\}$
Label sets	$E ::= \{l, \dots, l\}$
Types	$T ::= \text{Null} \mid S \mid E \mid \text{linkthis}$
Method dec	$M ::= m(x) \{e\}$
Values	$v ::= \text{null} \mid l$
Paths	$r ::= \text{this}$
Expressions	$e ::= v \mid f.m(e) \mid x \mid e; e \mid \text{switch } (e) \{l : e_l\}_{l \in E} \mid f \leftrightarrow e \mid \text{new } C()$
Class session types	$S ::= \{T'_i m_i(T_i) : S_i\}_{i \in I} \mid \langle l : S_l \rangle_{l \in E} \mid X \mid \mu X. S$

Figure 5: Top level syntax

Types	$T ::= \dots \mid \text{link } f \mid C[F]$
Field types	$F ::= \{T_i f_i\}_{i \in I} \mid \langle l : F_l \rangle_{l \in E}$
Values	$v ::= \dots \mid o$
Paths	$r ::= o \mid r.f$
Expressions	$e ::= \dots \mid \text{return } e$
Object records	$R ::= C[\{f_i = v_i\}_{i \in I}]$
Heaps	$h ::= \varepsilon \mid h, \{o = R\}$
States	$s ::= (h * r; e)$
Contexts	$\mathcal{E} ::= [_] \mid \mathcal{E}; e \mid \text{switch } (\mathcal{E}) \{l : e_l\}_{l \in E} \mid \text{return } \mathcal{E} \mid f \leftrightarrow \mathcal{E} \mid f.m(\mathcal{E})$

The productions for types, values and expressions extend those in Figure 5. Session types may never contain types of the form $\text{link } f$, even in the extended syntax.

Figure 6: Extended syntax, used only in the type system and semantics

language, of channels. It also supports a form of overloading, allowing a method to have different signatures at different points in the same session type.

- When a method is followed by a variant session type, the return type of the method is the special type linkthis rather than the set of labels from the variant.

Our prototype implementation, described briefly at the end of Section 8, does not make these simplifications and its syntax is closer to that of Section 2.

3.1 Syntax

We separate the syntax into the top-level language (Figure 5) and the extensions required by the type system and operational semantics (Figure 6). Identifiers C , m , f and l are taken from disjoint countable sets representing names of classes, methods, fields and labels respectively. The vector arrow indicates a sequence of zero or more elements of the syntactic class it is above. Similarly, constructs indexed by a set denote a finite sequence. We use E to specifically denote finite sets of labels l , whereas I is any finite indexing set.

Field names always refer to fields of the current object; there is no qualified field specification $o.f$. In other words, all fields are private. Method call is only available on a field, not an arbitrary expression. This is because calling a method changes the session type of the object on which the method is called, and in order for the type system to record this change, the object must be in a specified location (field).

A program consists of a sequence of class declarations D . In the core language, types in a top-level program only occur in the *session* part of a class declaration: no type is declared for fields because they can vary at run-time and are always initially null, and method declarations are also typeless, as explained earlier.

A session type S corresponds to a view of an object from outside. It shows which methods can be called, and their signatures, but the fields are not visible. We refer to $\{T'_i m_i(T_i) : S_i\}_{i \in I}$ as a *branch* type and to $\langle l : S_l \rangle_{l \in E}$ as a *variant* type. Session type **end** abbreviates the empty branch type $\{\}$. The core language does not include named session types, or the **session** and **where** clauses

from the examples; we just work with recursive session type expressions of the form $\mu X.S$, which are required to be *contractive*, i.e. containing no subexpression of the form $\mu X_1 \cdots \mu X_n.X_1$. The μ operator is a binder, giving rise, in the standard way, to notions of bound and free variables and alpha-equivalence. A type is *closed* if it includes no free variables. We denote by $T\{U/X\}$ the capture-avoiding substitution of U for X in T .

Value types which can occur either as parameter or return type for a method are: **Null** which has the single value **null**, a session type S which is the type of an object, or an enumerated type E which is an arbitrary finite set of labels l . Additionally, the specific return type **linkthis** is used for method occurrences after which the resulting session type is a variant, and means that the method result will be the tag of the variant (hence *linked* to *this* variantly-typed object). The set of possible labels appears in the variant construct of the session type, so it is not necessary to specify it in the return type of the method. However, in the example code, the set of labels is written instead of **linkthis**, so that the method signature shows the return type in the usual way.

The type system, which we will describe later, enforces the following restrictions on session types: the immediate components of a variant type are always branch types, and the session type in a class declaration is always a branch. This is because a variant type is used only to represent the effect of method calls and the dependency between a method result and the subsequent session type, so it only makes sense immediately within a branch type.

Figure 6 defines additional syntax that is needed for the formal system but is not used in top-level programs. This includes some expressions that arise from the operational semantics, some extra forms of type that are used in the proof of type preservation in order to type expressions arising from the operational semantics, and syntax for the heap.

The first addition is the type **link** f . When a field f is given a variant type, the corresponding tag, which in our language is a separate value, has type **link** f . It is not possible for these tags to be returned from a method or passed as parameters, hence they cannot appear in the declarations and are not part of the syntax of programs. There is also an alternative form of object type, $C[F]$, which has a field typing instead of a session type. It represents the view of an object from within its own class and is used when typing method definitions. A field typing F can either be a record type associating one type to each field of the object or a variant field typing $\langle l : F_l \rangle_{l \in E}$, indexed by the values of an enumerated set E , similar to a variant session type.

The other additions are used to define the operational semantics. A heap h maps object identifiers o , taken from yet another countable set of names, to object records R . We write $\text{dom}(h)$ for the set of object identifiers in h . The identifiers are values, which may occur in expressions. The operation $h, \{o = R\}$ represents adding a record for identifier o to the heap h and we consider it to be associative and commutative, that is, h is essentially an unordered set of bindings. It is only defined if $o \notin \text{dom}(h)$. Paths r represent locations in the heap. A path consists of a top-level object identifier followed by an arbitrary number of field specifications. We use the following notation to interpret paths relative to a given heap.

Definition 3.1 (Heap locations)

- If $R = C[\{f_i = v_i\}_{i \in I}]$, we define $R.f_i = v_i$ (for all i) and $R.\text{class} = C$. For any value v and any $j \in I$, we also define $R\{f_j \mapsto v\} = C[\{f_i = v'_i\}_{i \in I}]$ where $v'_i = v_i$ for $i \neq j$ and $v'_j = v$.
- If $h = (h', \{o = R\})$, we define $h(o) = R$, and for any field f of R , $h\{o.f \mapsto v\} = (h', \{o = R\{f \mapsto v\}\})$.
- If $r = r'.f$ and $h(r').f = o$, then we also define $h(r) = h(o)$ and $h\{r.f' \mapsto v\} = h\{o.f' \mapsto v\}$.
- In any other case, these operations are not defined. Note in particular that $h(r)$ is not defined if r is a path that exists in h but does not point to an object identifier.

There is a new form of expression, **return** e , which is used to represent an ongoing method call.

Finally, a state consists of a heap and an expression, and the operational semantics will be defined as a reduction relation on states; \mathcal{E} are evaluation contexts in the style of Wright and Felleisen [64], used in the definition of reduction.

The semantic and typing rules we will present next are implicitly parameterized by the set of declarations D which constitute the program. It is assumed that the whole set is available at any

$$\begin{array}{c}
\text{(R-SEQ)} \quad (h * r; v; e) \longrightarrow (h * r; e) \\
\\
\text{(R-RETURN)} \quad (h * r.f; \text{return } v) \longrightarrow (h * r; v) \quad \text{(R-CALL)} \quad \frac{m(x) \{e\} \in h(r.f).\text{class}}{(h * r; f.m(v)) \longrightarrow (h * r.f; \text{return } e\{v/x\})} \\
\\
\text{(R-SWITCH)} \quad \frac{l_0 \in E}{(h * r; \text{switch } (l_0) \{l : e_l\}_{l \in E}) \longrightarrow (h * r; e_{l_0})} \\
\\
\text{(R-SWAP)} \quad \frac{h(r).f = v}{(h * r; f \leftrightarrow v') \longrightarrow (h\{r.f \mapsto v'\} * r; v)} \\
\\
\text{(R-NEW)} \quad \frac{o \notin \text{dom}(h) \quad C.\text{fields} = \vec{f}}{(h * r; \text{new } C()) \longrightarrow (h, \{o = C[\vec{f} = \vec{\text{null}}]\} * r; o)} \quad \text{(R-CONTEXT)} \quad \frac{(h * r; e) \longrightarrow (h' * r'; e')}{(h * r; \mathcal{E}[e]) \longrightarrow (h' * r'; \mathcal{E}[e'])}
\end{array}$$

Figure 7: Reduction rules for states

point¹ and that any class is declared only once. We do not require the sets of method or field names to be disjoint from one class to another. We will use the following notation: if $\text{class } C \{S; \vec{f}; \vec{M}\}$ is one of the declarations, $C.\text{session}$ means S and $C.\text{fields}$ means \vec{f} , and if $m(x) \{e\} \in \vec{M}$ then $C.m$ is e .

3.2 Operational Semantics

Figure 7 defines an operational semantics on states $(h * r; e)$ consisting of a heap, a path in the heap indicating the *current object*, and an expression. All rules have the implicit premise that the expressions appearing in them must be defined. For example, $f \leftrightarrow v$ only reduces if $h(r)$ is an object record containing a field named f . An example of reduction, together with typing, is presented in Figure 12 and discussed at the end of the present section.

The current object path r is used to resolve field references appearing in the expression e . Except in the case of R-CONTEXT, e is always a part of a partially reduced method body, and r shows the location in the heap of the object on which the method was called. The current object path behaves like a call stack: as shown in R-CALL, when a method call on a field f (relative to the current object located at r) is entered, the object in $r.f$ becomes the current object; this is indicated by changing the path to $r.f$. Additionally, the method body, with the actual parameter substituted for the formal parameter, is wrapped in a **return** expression and replaces the method call. When the body has reduced to a value, this value is unwrapped by R-RETURN which also pops the field specification f from the path, recovering the previous current object r . R-NEW creates a new object in the heap, with **null** fields. R-SWAP updates the value of a field and reduces to its former value.

R-SWITCH is standard. R-SEQ discards the result of the first part of a sequential composition. R-CONTEXT is the usual rule for reduction in contexts.

To complete the definition of the semantics we need to define the initial state. The idea is to designate a particular method m of a particular class C as the *main* method, which is called in order to begin execution. The most convenient way to express this is to have an initial heap that contains an object of class C , which is also chosen as the current object, and an initial expression e which is the body of m . The initial state is therefore

$$(\text{top} = C[C.\text{fields} = \vec{\text{null}}] * \text{top}; e).$$

Strictly speaking, method m must have a parameter x ; we take x to be of type **Null** and assume that it does not occur in e .

Alternatively, if we want the initial expression to be a call of m , then remembering that a method call must be on a field we have to introduce another object, of a dummy class D , with a field containing the object of class C on which m is called:

$$(\text{top} = D[f = c], c = C[C.\text{fields} = \vec{\text{null}}] * \text{top}; f.m(\text{null})).$$

¹This is assumed for simplicity, but it is easy to check that when typing a toplevel program, the body of a method or class is never used outside that particular method or class — hence respecting encapsulation and allowing separate checking and compilation. The only information needed is a session declaration for every class being instantiated. Conversely, the semantic rules do not need any type information and, in particular, completely ignore session declarations.

$$\begin{array}{c}
\text{(S-RECORD)} \frac{\forall i \in I, T_i <: T'_i}{\{T_i f_i\}_{i \in I} <: \{T'_i f_i\}_{i \in I}} \quad \text{(S-VARIANT)} \frac{E \subseteq E' \quad \forall l \in E, F_l <: F'_l}{\langle l : F_l \rangle_{l \in E} <: \langle l : F'_l \rangle_{l \in E'}} \\
\text{(S-FIELD)} \frac{F <: F'}{C[F] <: C[F']}
\end{array}$$

Figure 8: Subtyping rules for fields

3.3 Subtyping

Two kinds of types in the top-level core language are subject to subtyping: enumerated types and session types. The internal language also has field typings; subtyping on them is derived from subtyping on top-level types by the rules in Figure 8.

Subtyping for enumerated types is simply set inclusion: $E <: E'$ if and only if $E \subseteq E'$. We refer to subtyping for session types as the *sub-session* relation. Because session types can be recursive, the sub-session relation is defined coinductively, by defining necessary conditions it must satisfy and taking the largest relation satisfying them. The definition involves checking compatibility between different method signatures, which itself is dependent on the whole subtyping relation. We proceed as follows: given a candidate sub-session relation \mathcal{R} , we define an \mathcal{R} -compatibility relation between types and between method signatures which uses \mathcal{R} as a sub-session relation. We then use \mathcal{R} -compatibility in the structural conditions that \mathcal{R} must satisfy in order to effectively be a sub-session relation.

Let \mathcal{S} denote the set of contractive, closed session types. We deal with recursive types using the following unfold operator:

Definition 3.2 (Unfolding) *The operator unfold is defined inductively on \mathcal{S} by $\text{unfold}(\mu X.S) = \text{unfold}(S\{\mu X.S\}/X\}$ and $\text{unfold}(S) = S$ if S is not of the form $\mu X.S$. Since the types in \mathcal{S} are contractive, this definition is well-founded.*

We now define the two compatibility relations we need.

Definition 3.3 (\mathcal{R} -Compatibility (Types)) *Let \mathcal{R} be a binary relation on \mathcal{S} . We say that type T is \mathcal{R} -compatible with type T' if one of the following conditions is true.*

1. $T = T'$
2. T and T' are enumerated types and $T \subseteq T'$
3. $T, T' \in \mathcal{S}$ and $(T, T') \in \mathcal{R}$.

Definition 3.4 (\mathcal{R} -Compatibility (Signatures)) *Let \mathcal{R} be a binary relation on \mathcal{S} . Let $\sigma = U \ m(T) : S$ and $\sigma' = U' \ m(T') : S'$ be components of branch types, both for the same method name m , i.e. method signatures with subsequent session types. We say that σ is \mathcal{R} -compatible with σ' if T' is \mathcal{R} -compatible with T and either:*

1. U is \mathcal{R} -compatible with U' and $(S, S') \in \mathcal{R}$, or
2. U is an enumerated type E , $U' = \text{linkthis}$ and $(\langle l : S \rangle_{l \in E}, S') \in \mathcal{R}$.

The compatibility relation on method signatures is, as expected, covariant in the return type and the subsequent session type and contravariant in the parameter type, but with one addition: if a method has an enumerated return type E and subsequent session type S , then it can always be used as if it had a return type of `linkthis` and were followed by the uniform variant session type $\langle l : S \rangle_{l \in E}$. Indeed, both signatures mean that the method can return any label in E and will always leave the object in state S . However, subtyping is in one direction only because usage of labels with a link type is more restricted; for example, they cannot be discarded.

We can now state the necessary conditions for a sub-session relation.

Definition 3.5 (Sub-session) *Let \mathcal{R} be a binary relation on \mathcal{S} . We say that \mathcal{R} is a sub-session relation if $(S, S') \in \mathcal{R}$ implies:*

1. If $\text{unfold}(S) = \{U_i \ m_i(T_i) : S_i\}_{i \in I}$ then $\text{unfold}(S')$ is of the form $\{U'_j \ m_j(T'_j) : S'_j\}_{j \in J}$ with $J \subseteq I$, and for all $j \in J$, $U_j \ m_j(T_j) : S_j$ is \mathcal{R} -compatible with $U'_j \ m_j(T'_j) : S'_j$.

2. If $\text{unfold}(S) = \langle l : S_l \rangle_{l \in E}$ then $\text{unfold}(S')$ is of the form $\langle l : S'_l \rangle_{l \in E'}$ with $E \subseteq E'$ and for all $l \in E$, $(S_l, S'_l) \in \mathcal{R}$.

For the sake of simplicity we will now, when we refer to this definition later on, make the unfolding step implicit by assuming, without loss of generality, that neither S nor S' is of the form $\mu X.S''$.

Lemma 3.6 *The union of several sub-session relations is a sub-session relation.*

Proof. Let $\mathcal{R} = \bigcup_{i \in I} \mathcal{R}_i$, where the \mathcal{R}_i are sub-session relations. Let $(S, S') \in \mathcal{R}$. Then there is j in I such that $(S, S') \in \mathcal{R}_j$. This implies that (S, S') satisfies the conditions in Definition 3.5 with respect to \mathcal{R}_j . Just notice that, because $\mathcal{R}_j \subseteq \mathcal{R}$, the conditions are satisfied with respect to \mathcal{R} as well — in particular, \mathcal{R}_j -compatibility implies \mathcal{R} -compatibility. Indeed, the conditions for \mathcal{R} only differ from those for \mathcal{R}_j by requiring particular pairs of session types to be in \mathcal{R} rather than in \mathcal{R}_j , so they are looser.

We now define the subtyping relation $<:$ on session types to be the largest sub-session relation, i.e. the union of all sub-session relations. The subtyping relation on general top-level types is just $<:-$ -compatibility.

Subtyping on session types means that either both are branches or both are variants. In the former case, the supertype must allow fewer methods and their signatures must be compatible; in the latter case, the supertype must allow more labels and the common cases must be in the subtyping relation. Like the definition of subtyping for channel session types [31], the type that allows a choice to be made (the branch type here, the \oplus type in [31]) has contravariant subtyping in the set of choices.

The following lemma shows that the necessary conditions of Definition 3.5 are also sufficient in the case of $<:-$.

Lemma 3.7 1. Let $S = \{U_i m_i(T_i) : S_i\}_{i \in I}$ and $S' = \{U'_j m_j(T'_j) : S'_j\}_{j \in J}$ with $J \subseteq I$. If for all $j \in J$, $U_j m_j(T_j) : S_j$ is $<:-$ -compatible with $U'_j m_j(T'_j) : S'_j$, then $S <: S'$.

2. Let $S = \langle l : S_l \rangle_{l \in E}$ and $S' = \langle l : S'_l \rangle_{l \in E'}$ with $E \subseteq E'$. If for all l in E we have $S_l <: S'_l$, then $S <: S'$.

Proof. The relation $<: \cup \{(S, S')\}$ is a sub-session relation.

Finally, we prove that this subtyping relation provides a preorder on types.

Proposition 3.8 *The subtyping relation is reflexive and transitive.*

Proof. First note that session types can only be related by subtyping to other session types; the same applies to enumerated types and, in the internal system, field typings. Since the relation for enumerated types is just set inclusion, we already know the result for it. We now prove the properties for session types; the fact that they hold for field typings is then a straightforward consequence.

For reflexivity, just notice that the diagonal relation $\{(S, S) \mid S \in \mathcal{S}\}$ is a sub-session relation, hence included in $<:-$.

For transitivity, what we need to prove is that the relation $\mathcal{R} = \{(S, S') \mid \exists S'', S <: S'' \wedge S'' <: S'\}$ is a sub-session relation. Let $(S, S') \in \mathcal{R}$ and let S'' be as given by the definition of \mathcal{R} .

In case (1) where we have $S = \{U_i m_i(T_i) : S_i\}_{i \in I}$, we know that:

- $S'' = \{U''_j m_j(T''_j) : S''_j\}_{j \in J}$ with $J \subseteq I$, and for all $j \in J$, $\sigma_j = U_i m_i(T_i) : S_j$ is $<:-$ -compatible with $\sigma''_j = U''_j m_j(T''_j) : S''_j$.
- Therefore, S' is of the form $\{U'_k m_k(T'_k) : S'_k\}_{k \in K}$ with $K \subseteq J$, and for all $k \in K$, σ''_k is $<:-$ -compatible with $\sigma'_k = U'_k m_k(T'_k) : S'_k$.

Straightforwardly $K \subseteq I$. For every k in K , we have to prove that σ_k is \mathcal{R} -compatible with σ'_k . We deduce it from the two $<:-$ -compatibilities we know by looking into the definition of compatibility point by point:

- We have $T''_k <: T_k$ and $T'_k <: T''_k$. Either these types are all session types, and then $(T'_k, T_k) \in \mathcal{R}$ by definition of \mathcal{R} , or none of them is and we have $T'_k <: T_k$ by transitivity of subtyping on base types. In both cases, T'_k is \mathcal{R} -compatible with T_k .

- We also have either:

- $U_k <: U_k'', U_k'' <: U_k', S_k <: S_k''$ and $S_k'' <: S_k'$. In this case, the former two conditions imply, similarly to the above, that U_k is \mathcal{R} -compatible with U_k' . The latter two imply $(S_k, S_k') \in \mathcal{R}$.
- Or U_k is an enumerated type E , $U_k'' = U_k' = \text{linkthis}$, $\langle l : S_k \rangle_{l \in E} <: S_k''$ and $S_k'' <: S_k'$. Then we have $(\langle l : S_k \rangle_{l \in E}, S_k') \in \mathcal{R}$, which is all we need.
- Or, finally, U_k is an enumerated type E , U_k'' is an enumerated type E'' such that $E \subseteq E''$, $S_k <: S_k''$ and $\langle l : S_k'' \rangle_{l \in E''} <: S_k'$. Then from $S_k <: S_k''$ and $E \subseteq E''$ we deduce, using case (2) of Lemma 3.7, $\langle l : S_k \rangle_{l \in E} <: \langle l : S_k'' \rangle_{l \in E''}$. We thus have, again, $(\langle l : S_k \rangle_{l \in E}, S_k') \in \mathcal{R}$ which is the required condition.

In case (2) where we have $S = \langle l : S_l \rangle_{l \in E}$, we obtain $S'' = \langle l : S_l'' \rangle_{l \in E''}$ and $S' = \langle l : S_l' \rangle_{l \in E'}$, with $E \subseteq E'' \subseteq E'$ and for any l in E , $S_l <: S_l''$ and $S_l'' <: S_l'$, which imply by definition of \mathcal{R} that (S_l, S_l') is in \mathcal{R} .

Definition 3.9 (Type equivalence) *We define equivalence of session types S and S' as $S <: S'$ and $S' <: S$. This corresponds precisely to S and S' having the same infinite unfoldings (up to the ordering of cases in branches and variants). Henceforth types are understood up to type equivalence, so that, for example, in any mathematical context, types $\mu X.S$ and $S\{\mu X.S/X\}$ can be used interchangeably, effectively adopting the equi-recursive approach [53, Chapter 21].*

3.4 Type System

We introduce a static type system whose purpose is to ensure that typable programs satisfy a number of safety properties. As usual, we make use of a type preservation theorem, which states that reduction of a typable expression produces another typable expression. Therefore the type system is formulated not only for top-level expressions but for the states (i.e. (heap, expression) pairs) on which the reduction relation is defined.

An important feature of the type system is that the method definitions within a particular class are not checked independently, but are analyzed in the order specified by the session type of the class. In Figure 9, rule T-CLASS (last rule) uses a consistency relation between field typings and session types, defined in Section 3.4.2. This relation in turn uses the typing judgement for expressions, which is defined by the other rules in Figure 9.

In the following sections we describe the type system in several stages.

3.4.1 Typing expressions

The typing judgement for expressions is $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$. In such a judgement, Γ is a type environment that maps object identifiers and parameter names to types, and r is the path to the current object in Γ . The expression e and its type T appear in the central part of the judgement. The Γ' and r' on the right hand side show the change, if any, that e causes in the type environment and current object path. There are several reasons for Γ' to differ from Γ ; the most important is that if e contains a method call on object o then the difference between Γ and Γ' shows that the session type of o changes. Any difference between r and r' means that e contains **return**; in that case, r and r' represent the call stack during and after a method call.

When typing an expression as part of a top-level program, the typing judgement has the particular form $\text{this} : C[F], V * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], V' * \text{this}$. Here the only object reference in the type environment is **this**, symbolically representing the object in which e occurs as part of a method body. The rest of the environment, V , has the form $x : U$ where U is the type of the parameter of the method (hence a top-level type). The initial type of **this** is the internal type $C[F]$, where F is a field typing; the final type is $C[F']$, as e may change the types of the fields (for example, by calling methods on them). The final parameter typing V' is either the same as V , if the parameter has a non-linear type, or empty, if the parameter has a linear type and is consumed by e . The path to the current object is **this** on both the left hand side and the right hand side of the judgement; that is the only possibility, because **this** is the only object reference in the environment; also, because e is a top-level expression, it does not contain **return**, which is the only expression that can change the current object path.

$$\begin{array}{c}
\text{(T-NULL)} \quad \Gamma * r \triangleright \text{null} : \text{Null} \triangleleft \Gamma * r \qquad \text{(T-LABEL)} \quad \Gamma * r \triangleright l : \{l\} \triangleleft \Gamma * r \\
\text{(T-NEW)} \quad \Gamma * r \triangleright \text{new } C() : C.\text{session} \triangleleft \Gamma * r \qquad \text{(T-LINVAR)} \quad \Gamma, x : S * r \triangleright x : S \triangleleft \Gamma * r \\
\text{(T-VAR)} \quad \frac{T \text{ is not an object type}}{\Gamma, x : T * r \triangleright x : T \triangleleft \Gamma, x : T * r} \\
\text{(T-SWAP)} \quad \frac{\Gamma * r \triangleright e : T \triangleleft \Gamma' * r' \quad \Gamma'(r'.f) = T' \quad T \neq \text{linkthis} \quad T' \text{ is not a variant}}{\Gamma * r \triangleright f \leftrightarrow e : T' \triangleleft \Gamma'\{r'.f \mapsto T\} * r'} \\
\text{(T-CALL)} \quad \frac{\Gamma * r \triangleright e : T_j' \triangleleft \Gamma' * r' \quad \Gamma'(r'.f) = \{T_i \ m_i(T_i') : S_i\}_{i \in I} \quad j \in I \quad T = \text{link } f \text{ if } T_j = \text{linkthis}, T = T_j \text{ otherwise}}{\Gamma * r \triangleright f.m_j(e) : T \triangleleft \Gamma'\{r'.f \mapsto S_j\} * r'} \\
\text{(T-SEQ)} \quad \frac{\Gamma * r \triangleright e : T \triangleleft \Gamma' * r' \quad \Gamma' * r' \triangleright e' : T' \triangleleft \Gamma'' * r' \quad T \neq \text{link } _ \text{ or linkthis}}{\Gamma * r \triangleright e; e' : T' \triangleleft \Gamma'' * r'} \\
\text{(T-SWITCH)} \quad \frac{\Gamma * r \triangleright e : E' \triangleleft \Gamma' * r' \quad E' \subseteq E \quad \forall l \in E', \Gamma' * r' \triangleright e_l : T \triangleleft \Gamma'' * r'}{\Gamma * r \triangleright \text{switch } (e) \{l : e_l\}_{l \in E} : T \triangleleft \Gamma'' * r'} \\
\text{(T-SWITCHLINK)} \quad \frac{\Gamma * r \triangleright e : \text{link } f \triangleleft \Gamma' * r' \quad \Gamma'(r'.f) = \langle l : S_l \rangle_{l \in E'} \quad E' \subseteq E \quad \forall l \in E', \Gamma'\{r'.f \mapsto S_l\} * r' \triangleright e_l : T \triangleleft \Gamma'' * r'}{\Gamma * r \triangleright \text{switch } (e) \{l : e_l\}_{l \in E} : T \triangleleft \Gamma'' * r'} \\
\text{(T-VARF)} \quad \frac{\Gamma * r \triangleright e : E \triangleleft \Gamma' * r' \quad \Gamma'(r') = C[F'] \quad F' \text{ is a record}}{\Gamma * r \triangleright e : \text{linkthis} \triangleleft \Gamma'\{r' \mapsto C[\langle l : F' \rangle_{l \in E}]\} * r'} \\
\text{(T-SUB)} \quad \frac{\Gamma * r \triangleright e : T \triangleleft \Gamma' * r' \quad T <: T'}{\Gamma * r \triangleright e : T' \triangleleft \Gamma' * r'} \qquad \text{(T-SUBENV)} \quad \frac{\Gamma * r \triangleright e : T \triangleleft \Gamma' * r' \quad \Gamma' <: \Gamma''}{\Gamma * r \triangleright e : T \triangleleft \Gamma'' * r'} \\
\text{(T-CLASS)} \quad \frac{\overrightarrow{\text{Null}} \vec{f} \vdash C : S}{\vdash \text{class } C \{S; \vec{f}; \vec{M}\}}
\end{array}$$

Figure 9: Typing rules for the top level language

We define notation for interpreting paths relative to type environments, analogously to Definition 3.1 for heaps.

Definition 3.10 (Locations in environments)

- If $\Gamma = \Gamma', o : T$ then we define $\Gamma(o) = T$ and $\Gamma\{o \mapsto T'\} = \Gamma', o : T'$
- Inductively, if $r = r'.f$, and if $\Gamma(r') = C[F]$ where F is a record field typing containing f , then $\Gamma(r)$ is defined as $F(f)$ and $\Gamma\{r \mapsto T'\}$ as $\Gamma\{r' \mapsto C[F\{f \mapsto T'\}]\}$.
- In any other case, these operations are not defined. In particular, if $\Gamma(r')$ is defined but is a session type, then $\Gamma(r'.f)$ is not defined for any f .

A pair $\Gamma * r$ only makes sense if $\Gamma(r)$ is defined and is of the form $C[F]$.

We extend subtyping to a relation on type environments, as follows.

Definition 3.11 (Environment subtyping) $\Gamma <: \Gamma'$ if for every $\alpha \in \text{dom}(\Gamma')$, where α is either a parameter or an object identifier, we have $\alpha \in \text{dom}(\Gamma)$ and $\Gamma(\alpha) <: \Gamma'(\alpha)$.

Essentially $\Gamma <: \Gamma'$ if Γ is more precise (contains more information) than Γ' : it contains types for everything in Γ' (and possibly more) and those types are more specific.

3.4.2 Consistency between field typings and session types

There are two possible forms for the type of an object. One is a session type S , which describes the view of the object from outside, i.e. from the perspective of code in other classes. The session type specifies which methods may be called, but does not reveal information about the fields. The other form, $C[F]$, contains a field typing F , and describes the internal view of the object, i.e. from the perspective of code in its own methods. Consider a sequence of method calls in a particular class. There are two senses in which it may be considered correct or incorrect. (1) In the sense that it is allowed, or not allowed, by the session type of the class. (2) In the sense that the field typings before and after each method call follow each other in a connected way. In order to type

a class definition, these two senses of correctness must be consistent according to the following coinductive definition.

Definition 3.12 *Let C be a class and let \mathcal{R} be a relation between field typings F and session types S . We say that \mathcal{R} is a C -consistency relation if $(F, S) \in \mathcal{R}$ implies:*

1. *If $S = \{T_i \text{ } m_i(T'_i) : S_i\}_{i \in I}$, then F is not a variant and for all i in I , there is a definition $m_i(x_i) \{e_i\}$ in the declaration of class C such that we have $\text{this} : C[F], x_i : T'_i * \text{this} \triangleright e_i : T_i \triangleleft \text{this} : C[F_i] * \text{this}$ with F_i such that $(F_i, S_i) \in \mathcal{R}$.*
2. *If $S = \langle l : S_l \rangle_{l \in E}$, then $F = \langle l : F_l \rangle_{l \in E'}$ with $E' \subseteq E$ and for all l in E' we have $(F_l, S_l) \in \mathcal{R}$.*

The definition implies that a method with return type `linkthis` must be followed by a variant session type, for the following reason. Suppose that in clause (1), some T_i is `linkthis`. The only way for e_i to have type `linkthis` is by using rule T-VARF, which implies that F_i must be a variant field typing. The condition $(F_i, S_i) \in \mathcal{R}$ implies, by clause (1), that S_i is a variant.

Lemma 3.13 *The union of several C -consistency relations is a C -consistency relation.*

Proof. Similar to (but simpler than) the proof of Lemma 3.6. For any class C , we define the relation $F \vdash C : S$ between field typings F and session types S to be the largest C -consistency relation, i.e. the union of all C -consistency relations.

The relation $F \vdash C : S$ represents the fact that an object of class C with internal (private) field typing F can be safely viewed from outside as having type S . The second point accounts for correspondence between variant types. The main point is the first: if the object's fields have type F and its session type allows a certain method to be called, then it means that the method body is typable with an initial field typing of F and the declared type for the parameter. Furthermore, the type of the expression must match the declared return type and the final type of the fields must be compatible with the subsequent session type. The parameter may or may not be consumed by the method, but T-SUBENV at the end of Figure 9 allows discarding it silently in any case, hence its absence from the final environment.

The rule T-CLASS, last rule in Figure 9, checks that the initial session type of a class is consistent with the initial Null field typing. It refers to the above definition of consistency, which itself refers to typing judgements built using the other rules in the figure.

3.4.3 Typing rules for top-level expressions

The typing rules for top-level expressions (the syntax in Figure 5) are in Figure 9. T-NUL and T-LABEL type constants. A label is given a singleton enumerated type, which is the smallest type it can have, but subsumption can be used to increase its type. T-NEW types a new object, giving it the initial session type from the class declaration. T-LINVAR and T-VAR are used to access a method's parameter, removing it from the environment if it has an object type (which is linear). For simplicity, this is the only way to use a parameter. In particular, we do not allow calling methods directly on parameters: to call a method on a parameter, it must first be assigned to a field. T-SWAP types the combined read-write field access operation, exchanging the types of the field and expression. There are two restrictions on its use. T is not allowed to be `linkthis`, because that would mean creating a variant field typing and hiding the tag instead of returning it from a method. This implies that $\Gamma'(r')$ is not a variant, because the only rule that could produce one is T-VARF, which would also give $T = \text{linkthis}$; hence $\Gamma'(r'.f)$ is defined. Also, T' is not allowed to be a variant, because in that case removing the contents of f would invalidate the link type that points to it.

T-CALL checks that field f has a session type that allows method m_j to be called. The type of the parameter is checked as usual, and the final type environment is updated to contain the new session type of the object in f . If the return type of the method is `linkthis`, it means that the value returned is a label describing the state of this object; since the object is in f , it is changed into `link f`. Because the return type appears in the session type and is therefore expressed in the top-level syntax, it cannot already be of the form `link f`.

T-SEQ accounts for the effects of the first expression on the environment and checks that a label is not discarded, which would leave the associated variant unusable.

$$\begin{array}{c}
\text{(T-REF)} \frac{r \neq o.\bar{f}}{\Gamma, o : T * r \triangleright o : T \triangleleft \Gamma * r} \quad \text{(T-VARS)} \frac{\Gamma * r \triangleright e : E \triangleleft \Gamma' * r' \quad \Gamma'(r'.f) = S \quad S \text{ is a branch}}{\Gamma * r \triangleright e : \text{link } f \triangleleft \Gamma' \{r'.f \mapsto \langle l : S \rangle_{l \in E}\} * r'} \\
\text{(T-RETURN)} \frac{\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'.f \quad \Gamma'(r'.f) = C[F] \quad F \vdash C : S \quad T \neq \text{link } _ \quad T' = \text{link } f \text{ if } T = \text{linkthis}, T' = T \text{ otherwise}}{\Gamma * r \triangleright \text{return } e : T' \triangleleft \Gamma' \{r'.f \mapsto S\} * r'}
\end{array}$$

Figure 10: Typing rules for expressions in the internal language

T-SWITCH types a **switch** whose expression e does not have a link type. All relevant branches are required to have the same type and final environment, and the whole **switch** expression inherits them. A typical example is if the branches just contain different labels: in that case they are given singleton types by T-LABEL and then T-SUB is used to give all of them the same enumerated type. If the type E' of the parameter expression is strictly smaller than the set E of case labels in the **switch** expression, branches corresponding to the extra cases are ignored.

T-SWITCHLINK is the only rule for deconstructing variants. It types a **switch**, similarly to the previous one, but the type of e must be a link to a field f with a variant session type. The relevant branches are then typed with initial environments containing the different case types for f according to the value of the label. As before, they must all have the same type and final environment, and if the **switch** expression defines extra branches for labels which do not appear in the variant type of f , they are ignored.

T-VARF constructs a variant field typing for the current object. Here E is typically, but not necessarily, a singleton type, and e is typically a literal label. The field typing before applying the rule must be a record as nested variants are not permitted, and the rule transforms it into a variant with identical cases for all labels in E . It can then be extended to a variant with arbitrary other cases using rule T-SUBENV. This rule is used for methods leading to variant session types, which, as Definition 3.12 implies, must finish with a variant field typing. As a simple example, consider the following expression, which could end a method body in some class D :

`switch (e) {TRUE : $f \leftrightarrow \text{new } C()$; OK, FALSE : $f \leftrightarrow \text{null}$; ERROR}`

If S is the declared session type of class C , we have, using rules T-SWAP, T-LABEL and T-SEQ, the following judgements (T is just the initial type of f):

`this : $D[T \ f] * \text{this} \triangleright f \leftrightarrow \text{new } C()$; OK : $\{\text{OK}\} \triangleleft \text{this} : D[S \ f] * \text{this}$`

and

`this : $D[T \ f] * \text{this} \triangleright f \leftrightarrow \text{null}$; ERROR : $\{\text{ERROR}\} \triangleleft \text{this} : D[\text{Null } f] * \text{this}$.`

Then T-VARF can be applied to both these judgements, giving both expressions the same type `linkthis`, and giving at the same time to `this`, in the final environment, the variant types $D[\langle \text{OK} : \{S \ f\} \rangle]$ and $D[\langle \text{ERROR} : \{\text{Null } f\} \rangle]$ respectively. These two types are both subtypes of the combined variant $D[\langle \text{OK} : \{S \ f\}, \text{ERROR} : \{\text{Null } f\} \rangle]$ and T-SUBENV can thus be applied to both judgements to increase the final type of `this` to this common supertype. It is then possible to use T-SWITCH to type the whole expression. Note that the final type of the expression is always `linkthis`: as T-VARF is the only rule for constructing variants, this is the only possible return type for a method leading to a variant.

T-SUB is a standard subsumption rule, and T-SUBENV allows subsumption in the final environment. The main use of the latter rule, as illustrated above, is to enable the branches of a **switch** to be given the same final environments.

3.4.4 Typing rules for internal expressions, heaps and states

The type system described so far is all we need to type check class declarations and hence programs, which are sequences of class declarations. In order to describe the runtime consequences of well-typedness, we now introduce an extended set of typing rules for expressions that occur only at runtime (Figure 10) and for program states including heaps (Figure 11).

Runtime expressions may contain object identifiers, typed by T-REF. In this rule, the current object path r must not be within o , meaning that the current object or any object containing

$$\begin{array}{c}
\text{(T-EMPTY)} \vdash \varepsilon : \emptyset \quad \text{(T-HADD)} \frac{\vdash h : \Gamma \quad \Gamma, o : C[\{\text{Null } f_i\}_{1 \leq i \leq n}] * o \triangleright f_1 \leftrightarrow v_1; \dots; f_n \leftrightarrow v_n : \text{Null} \triangleleft \Gamma' * o}{\vdash h, \{o = C[\{f_i = v_i\}_{1 \leq i \leq n}]\} : \Gamma'} \\
\text{(T-HIDE)} \frac{\vdash h : \Gamma, o : C[F] \quad F \vdash C : S}{\vdash h : \Gamma, o : S} \quad \text{(T-STATE)} \frac{\vdash h : \Gamma \quad \Gamma * r \triangleright e : T \triangleleft \Gamma' * r'}{\Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r'}
\end{array}$$

Figure 11: Typing rules for states

it cannot be used within an expression. This is part of the linear control of objects: somewhere there must be a reference to the object at r , in order for a method to have been called on that object, which is what gives rise to the evaluation of an expression whose current object path is r . So obtaining another reference to the object at r , within the active expression, would violate linearity.

Another new rule is T-VARS, which constructs a variant session type for a field of the current object. At the top level, the only expression capable of constructing a variant session type is a method call, but once the method call has reduced into something else this rule is necessary for type preservation.

The last additional rule for expressions is T-RETURN, which types a **return** expression representing an ongoing method call. The subexpression e represents an intermediate state in a method of object $r'.f$. As such, it is typed with final current object $r'.f$ and a final environment where the type of $r'.f$ is of the form $C[F]$, representing an inside view of the object, where the fields are visible. This rule then steps out of the object, hides its fields and changes its type into the outside view of a session type, which must be consistent with the internal type ($F \vdash C : S$). The particular case where T is **linkthis** is the same as in T-CALL. T is not allowed to already be of the form **link** f' since it would break encapsulation (f' would refer to a field of $r'.f$ which is not known outside of the object).

An important point is that the only expression that changes the current object is **return**. Several rules besides T-RETURN can inherit in the conclusion a change of current object from a subexpression in a premise, but they do not add further changes. Thus the final current object path is always a prefix of the initial one, and the number of field specifications removed is equal to the number of **returns** contained in the expression. Also note that the second part of a sequence and the branches of a **switch** are not reduction contexts; therefore, they should not contain **return** and are not allowed by the rules to change the current object.

As we saw in Section 3.2, a runtime state consists of a heap, a current object path, and a runtime expression. Figure 11 describes how these parts are related by typing: a typing judgement for the expression gives one for the state provided the current object is the same and the initial environment reflects the content of the heap; this last constraint is represented by the judgement $\vdash h : \Gamma$. Such a judgement is constructed starting from the axiom T-EMPTY which types an empty heap and adding objects into the heap one by one with rule T-HADD, converting their types into sessions using T-HIDE as needed. As T-HADD is the only rule that adds to Γ , we have the property that $\vdash h : \Gamma$ implies that every identifier in Γ also appears in h .

T-HADD essentially says that adding a new object with given field values to the heap affects the environment in the same way as an expression that starts from an empty object and puts the values into the fields one by one. The most important feature of this rule is that whenever a v_i is an object identifier, the typing derivation for the expression has to use T-REF, which implies both that the initial environment contains v_i and that the final one, which represents the type of the extended heap, does not. This means that a type environment corresponding to a heap never contains entries for object identifiers that appear in fields of other objects, and it also implies that a heap with multiple references to the same object is not typable. The numbering of the fields in the rightmost premise is arbitrary, meaning it must not be interpreted as requiring the sequence of swaps to be done in any particular order; all possible orders are valid instances of the premise. This is important if the type of the object being added is to contain links and variants: suppose that field f contains an object o and field g a label l ; it must be possible to attribute a variant type to f and the type **link** f to g , but this can only be done as a result of typing the sequence of swaps if $f \leftrightarrow o$ occurs before $g \leftrightarrow l$.

$$\begin{array}{ll}
o : C[C'[\{m_i : S_i\}_{i \in I}] f, T g] * o & \triangleright \quad g \leftrightarrow f.m_j(); \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E} \\
& \downarrow \quad (\text{R-CALL}) \\
o : C[C'[F] f, T g] * o.f & \triangleright \quad g \leftrightarrow \text{return } e; \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E} \\
& \downarrow * \\
o : C[C'[F_{l_0}] f, T g] * o.f & \triangleright \quad g \leftrightarrow \text{return } l_0; \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E} \\
& \downarrow \quad (\text{R-RETURN}) \\
o : C[C'[S_{l_0}] f, T g] * o & \triangleright \quad g \leftrightarrow l_0; \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E} \\
& \downarrow \quad (\text{R-SWAP, R-SEQ}) \\
o : C[C'[\langle l : S_l \rangle_{l \in E}] f, (\text{link } f) g] * o & \triangleright \quad \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E} \\
& \downarrow \quad (\text{R-SWAP}) \\
o : C[C'[S_{l_0}] f, \text{Null } g] * o & \triangleright \quad \text{switch } (l_0) \{l : e_l\}_{l \in E} \\
& \downarrow \quad (\text{R-SWITCH}) \\
o : C[C'[S_{l_0}] f, \text{Null } g] * o & \triangleright \quad e_{l_0}
\end{array}$$

Figure 12: Example of the interplay between method call, switch and link types. The heap and the rightmost typing environment are omitted.

3.5 Example of reduction and typing

Figure 12 illustrates the operational semantics and the way in which the environment used to type an expression changes as the expression reduces (see Theorem 3.18 on page 19).

The initial expression is

$$g = f.m_j(); \text{switch } (g) \{l : e_l\}_{l \in E}$$

where for simplicity we have ignored the parameter of m_j . This expression is an abbreviation for

$$g \leftrightarrow f.m_j(); \text{null}; \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E}$$

which we simplify to

$$g \leftrightarrow f.m_j(); \text{switch } (g \leftrightarrow \text{null}) \{l : e_l\}_{l \in E}$$

The initial typing environment is

$$o : C[C'[\{m_i : S_i\}_{i \in I}] f, T g]$$

with o as the current object, where $S_j = \langle l : S_l \rangle_{l \in E}$. The body of method m_j is e with the typing

$$\text{this} : C'[F] * \text{this} \triangleright e : \text{linkthis} \triangleleft \text{this} : C'[\langle l : F_l \rangle_{l \in E}] * \text{this}$$

and we assume that m_j returns $l_0 \in E$. According to Definition 3.12 and the typing of the declaration of class C' we have $F_{l_0} \vdash C' : S_{l_0}$ and $F \vdash C' : \{m_i : S_i\}_{i \in I}$.

The figure shows the environment in which each expression is typed; the environment changes as reduction proceeds, for several reasons explained below. The typing of an expression is $\Gamma \triangleright e : T \triangleleft \Gamma'$ but we only show Γ because Γ' does not change and T is not the interesting part of this example. We also omit the heap, showing the typing of expressions instead of states. Calling $f.m_j()$ changes the type of field f to $C'[F]$ because we are now inside the object; the current object path changes from o to $o.f$. As e reduces to l_0 the type of f may change, finally becoming $C'[F_{l_0}]$ so that it has the component of the variant field typing $\langle l : F_l \rangle_{l \in E}$ corresponding to l_0 . The reduction by R-RETURN changes the type of f to $C'[S_{l_0}]$ because we are now outside the object again, but the type is still the component of a variant typing corresponding to l_0 . At this point f is popped from the current object path. The swap changes the type of f again, to $C'[\langle l : S_l \rangle_{l \in E}]$, which is $C'[S_j]$, the type we were expecting after the method call. At this point the information about which component of the variant typing we have is stored in $o.g$, the field the label was swapped into: the type of the expression $f.m_j()$ is $\text{link } f$, which appears as the type of $o.g$ after the swap is executed. When extracting the value of g in order to switch on it, the type $\text{link } f$ disappears from the environment and becomes the type of the subexpression $g \leftrightarrow \text{null}$, at the same time resolving the variant type of f according to the particular enumerated value l_0 .

3.6 Typing the initial state

Recall the discussion of the initial state for execution of a program, from the end of Section 3.2. The initial state is $(\text{top} = C[C.\text{fields} = \vec{\text{null}}] * \text{top}; e)$ where class C has a designated *main* method m with body e . In order to type this initial state, we require that m is immediately available in $C.\text{session}$, and assume that the program is typable, i.e. that rule T-CLASS is applicable to every class definition. If $C.\text{fields} = \vec{f}$ then the hypothesis of T-CLASS is $\vec{\text{Null}} \vec{f} \vdash C : C.\text{session}$; this is what the type checking algorithm defined in Section 8 checks. The definition of $F \vdash C : S$ gives $\text{this} : C[\vec{\text{Null}} \vec{f}], x : \text{Null} * \text{this} \triangleright e : T \triangleleft \text{this} : C[F] * \text{this}$ for some field typing F . The type T is irrelevant. Lemma 7.10 (Substitution), to be proved later, gives $\text{top} : C[\vec{\text{Null}} \vec{f}] * \text{top} \triangleright e : T \triangleleft \text{top} : C[F] * \text{top}$, as we assumed that $e\{\vec{\text{null}}/\vec{x}\} = e$. Straightforward use of T-EMPTY and T-HADD gives $\vdash \text{top} = C[C.\text{fields} = \vec{\text{null}}] : \text{top} : C[\vec{\text{Null}} \vec{f}]$ and then T-STATE gives a typing for the initial state.

3.7 Properties of the type system

The main results in this sequential setting are standard: type preservation under reduction (also known as Subject Reduction) and absence of stuck states for well-typed programs. Furthermore, the system also enjoys of a conformance property: all executions of well-typed programs follow what is specified by the classes' session types.

3.7.1 Soundness of subtyping

In this section we prove that the subtyping relation is sound with respect to the type system, in the sense that it preserves not only typing judgements but also consistency between field typings and session typings, reflecting the safe substitution property.

Lemma 3.14 *If $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$ and $\Gamma'' <: \Gamma$, then $\Gamma'' * r \triangleright e : T \triangleleft \Gamma' * r'$.*

Proof. Straightforward induction on the derivation.

Proposition 3.15 (soundness of subtyping for fields) *If $F \vdash C : S$ and $F' <: F$ then $F' \vdash C : S$.*

Proof. Straightforward using Lemma 3.14.

Before proving the case where subtyping is on the right, we first remark that, similarly to sub-session, the necessary conditions in the definition of C -consistency (Definition 3.12) become sufficient once we consider the largest relation:

Lemma 3.16 *Let C be a class and F a field typing for that class.*

1. *Suppose F is not a variant, and suppose there is a set of method definitions $\{m_i(x_i) \{e_i\}\}_{i \in I}$ in the declaration of class C such that, for all i , we have $\text{this} : C[F], x_i : T'_i * \text{this} \triangleright e_i : T_i \triangleleft \text{this} : C[F_i] * \text{this}$ with $F_i \vdash C : S_i$. Then $F \vdash C : \{T_i \ m_i(T'_i) : S_i\}_{i \in I}$ holds.*
2. *Suppose $F = \langle l : F_l \rangle_{l \in E'}$ and let $(S_l)_{l \in E}$ be a family of session types such that $E' \subseteq E$ and $F_l \vdash C : S_l$ for all $l \in E'$. Then $F \vdash C : \langle l : S_l \rangle_{l \in E}$ holds.*

Proof. Let S be either $\{T_i \ m_i(T'_i) : S_i\}_{i \in I}$ or $\langle l : S_l \rangle_{l \in E}$ depending on the case. Just notice that $(\bullet \vdash C : \bullet) \cup \{(F, S)\}$ is a C -consistency relation.

Proposition 3.17 (soundness of subtyping for sessions) *If $F \vdash C : S$ and $S <: S'$ then $F \vdash C : S'$.*

Proof. For any class C , we define the following relation:

$$\mathcal{R}_C = \{(F, S') \mid \exists S, F \vdash C : S \text{ and } S <: S'\}$$

and prove that it is a C -consistency relation (Definition 3.12). Let $(F, S') \in \mathcal{R}_C$, and let S be as given by the definition of the relation. We have two cases depending on the form of S' (branch or variant).

The first one is $S' = \{U'_j \ m_j(T'_j) : S'_j\}_{j \in J}$. Then $S <: S'$ means (Definition 3.5) that we have: $S = \{U_i \ m_i(T_i) : S_i\}_{i \in I}$ with $J \subseteq I$ and for all $j \in J$, $U_j \ m_j(T_j) : S_j$ is $<:-$ -compatible with $U'_j \ m_j(T'_j) : S'_j$. Let $j \in J$, we know from $F \vdash C : S$ that C contains a method declaration $m_j(x) \{e\}$ such that the following judgement:

$$x : T_j, \text{this} : C[F] * \text{this} \triangleright e : U_j \triangleleft \text{this} : C[F_j] * \text{this}$$

holds, with $F_j \vdash C : S_j$. $<:-$ -compatibility between the two signatures of m_j (Definition 3.4) gives us, first, $T'_j <: T_j$, which allows us to apply Lemma 3.14 to this judgement and replace T_j by T'_j in it, and second, either:

1. $U_j <: U'_j$ and $S_j <: S'_j$. The former allows us to use T-SUB to replace U_j by U'_j in the typing judgement for e , fulfilling the first condition in the definition of C -consistency. The latter, together with $F_j \vdash C : S_j$, implies $(F_j, S'_j) \in \mathcal{R}_C$, fulfilling the second one.
2. U_j is an enumerated type E , $U'_j = \text{linkthis}$ and $\langle l : S_j \rangle_{l \in E} <: S'_j$. In this case we first apply T-VARF to the judgement, yielding:

$$x : T'_j, \text{this} : C[F] * \text{this} \triangleright e : \text{linkthis} \triangleleft \text{this} : C[\langle l : F_j \rangle_{l \in E}] * \text{this}.$$

From $F_j \vdash C : S_j$ we deduce $\langle l : F_j \rangle_{l \in E} \vdash C : \langle l : S_j \rangle_{l \in E}$ using Lemma 3.16, and conclude $(\langle l : F_j \rangle_{l \in E}, S'_j) \in \mathcal{R}_C$.

In the second case, where $S' = \langle l : S'_l \rangle_{l \in E'}$, then $S = \langle l : S_l \rangle_{l \in E}$ with $E \subseteq E'$ and $\forall l \in E, S_l <: S'_l$. From $F \vdash C : S$ we know that $F = \langle l : F_l \rangle_{l \in E''}$ with $E'' \subseteq E$ and $F_l \vdash C : S_l$ for any l in E'' . Just notice that $E'' \subseteq E'$ and $(F_l, S'_l) \in \mathcal{R}_C$ for any l in E'' .

3.7.2 Type preservation

Theorem 3.18 (Subject Reduction) *Let \mathcal{D} be a set of well-typed declarations, that is, such that for every class declaration D in \mathcal{D} we have $\vdash D$.*

*If, in a context parameterised by \mathcal{D} , we have $\Gamma * r \triangleright (h * r; e) : T \triangleleft \Gamma' * r'$, and if $(h * r; e) \longrightarrow (h' * r''; e')$, then there exists Γ'' such that $\Gamma'' * r'' \triangleright (h' * r''; e') : T \triangleleft \Gamma' * r'$.*

Proof. This theorem is a particular case of Theorem 7.16 which will be proved in Section 7.

3.7.3 Type safety

Theorem 3.19 (No Stuck Expressions) *Let \mathcal{D} be a set of well-typed declarations, that is, such that for every class declaration D in \mathcal{D} we have $\vdash D$.*

*If, in a context parameterised by \mathcal{D} , we have $\Gamma * r \triangleright (h * r; e) : T \triangleleft \Gamma' * r'$, then either e is a value or there exists $(h' * r''; e')$ such that $(h * r; e) \longrightarrow (h' * r''; e')$.*

Proof. This theorem is also a consequence of Theorem 7.16, so we postpone its proof until Section 7.

3.7.4 Conformance

We show that, in well-typed programs, a sequence of method calls (interleaved with their respective return labels) of a given class is a path of its session type. In order to state this property precisely, we introduce a few definitions.

Definition 3.20 (Call trace) *A call trace is a sequence $m_1 l_1 m_2 l_2 \dots m_n l_n$ in which each m_i is a method name and each l_i may be absent or, if present, is a label.*

Definition 3.21 (LTS on session types) *Define a labelled transition relation on class session types by the following rules. α stands for m or l .*

$$\begin{array}{c} \frac{j \in I}{\{T'_i \ m_i(T_i) : S_i\}_{i \in I} \xrightarrow{m_j} S_j} \qquad \frac{l_0 \in E}{\langle l : S_l \rangle_{l \in E} \xrightarrow{l_0} S_{l_0}} \\[2ex] \frac{S \text{ is not a variant}}{S \xrightarrow{l} S} \qquad \frac{S\{\mu X.S/X\} \xrightarrow{\alpha} S'}{\mu X.S \xrightarrow{\alpha} S'} \end{array}$$

Definition 3.22 (Call trace mapping) A call trace mapping for a heap h is a function tr from $\text{dom}(h)$ to call traces.

Definition 3.23 (Validity of mappings) A call trace mapping tr for a heap h is valid if for every entry $o = C[\dots]$ in h , we have $C.\text{session} \xrightarrow{tr(o)}^*$. An element in a call trace which does not allow the corresponding session type to reduce is a type error. (Thus a call trace is valid if and only if it does not contain type errors).

Definition 3.24 If tr is a call trace mapping for a heap h then we define $tr(h, r)$ for references r such that $h(r)$ is defined, as follows:

$$\begin{aligned} tr(h, o) &= tr(o) \\ tr(h, r.f) &= tr(h(r).f) \end{aligned}$$

Definition 3.25 (Original reduction rule) If $(h * r; e) \longrightarrow (h' * r'; e')$ then the derivation of this reduction consists of a number of applications of R-CONTEXT, preceded by another rule which forms a unique leaf node in the derivation. We say that the rule at the leaf node is the original reduction rule for the reduction, or that the reduction originates from this rule.

Definition 3.26 (Extension of call traces) Suppose tr is a call trace mapping for h and $(h * r; e) \longrightarrow (h' * r'; e')$. Define a call trace mapping tr' for h' as follows:

- If the reduction originates from R-CALL with method m and field f then $tr' = tr\{h(r.f) \mapsto tr(h(r).f)m\}$.
- If the reduction originates from R-RETURN with value v , and v is a label l , then $tr' = tr\{h(r) \mapsto tr(h(r))l\}$.
- If the reduction originates from R-NEW and the fresh object is o then $tr' = tr\{o \mapsto \varepsilon\}$.
- Otherwise, $tr' = tr$.

The conformance property is the following: in a sequence of reductions starting from the initial state of a well-typed program, the call traces built using the extension mechanism defined above are valid throughout the sequence. We need a couple of lemmas to properly relate call traces and typings in the case of variant types.

Lemma 3.27 If $\vdash h : \Gamma$, then Γ does not contain `linkthis` or any variant field typing.

Proof. It suffices to show that rule T-VARF cannot be used in the derivation of $\vdash h : \Gamma$, since it is the only rule that introduces `linkthis` or variant field typings.

This rule can only be used on an expression of enumerated type, and the only place where such an expression can occur in the derivation of $\vdash h : \Gamma$ is as the right member of a swap in the second premise of T-HADD (the swap expression itself has type `Null` because of the initial environment). It corresponds to the first premise of T-SWAP. However, the third premise of T-SWAP forbids that the type of the expression be `linkthis`, hence T-VARF cannot be used there.

Lemma 3.28 (Variant consistency) If $\vdash h : \Gamma$ and $\Gamma(r) = \langle l : S_l \rangle_{l \in E}$, then:

1. r is of the form $r'.f$
2. there exists f' such that $\Gamma(r'.f') = \text{link } f$ and $h(r'.f') \in E$.

Proof. Consider how a variant session type can be introduced in the derivation of $\vdash h : \Gamma$. Because of Lemma 3.27, it cannot be a consequence of T-HIDE: indeed, $F \vdash C : S$ where S is a variant can only hold if F is a variant as well. Thus the only possibility is T-VARS, and it can only occur when typing one of the values in the right premise of T-HADD. (1) follows from the fact that T-VARS acts on a field of the current object. Then T-SUBENV can be applied but the original label T-VARS was applied to is still in the final E . (2) follows from the structure of the derivation: the label T-VARS is applied to is then swapped into a field of the same object.

Top-level syntax (add to Figure 5):

$$e ::= \dots \mid \text{while } (e) \{e\}$$

Reduction rule (add to Figure 7):

$$(\text{R-WHILE}) \quad (h * r; \text{while } (e) \{e'\}) \longrightarrow (h * r; \text{switch } (e) \{\text{True} : e'; \text{while } (e) \{e'\}, \text{False} : \text{null}\})$$

Top-level typing rules (add to Figure 9):

$$\begin{aligned}
(\text{T-WHILE}) \quad & \frac{\Gamma * r \triangleright e : \{\text{True}, \text{False}\} \triangleleft \Gamma' * r' \quad \Gamma' * r' \triangleright e' : \text{Null} \triangleleft \Gamma * r}{\Gamma * r \triangleright \text{while } (e) \{e'\} : \text{Null} \triangleleft \Gamma' * r'} \\
(\text{T-WHILELINK}) \quad & \frac{\Gamma * r \triangleright e : \text{link } f \triangleleft \Gamma' * r' \quad \Gamma'(r'.f) = \langle \text{True} : S_{\text{True}}, \text{False} : S_{\text{False}} \rangle}{\Gamma * r \triangleright \text{while } (e) \{e'\} : \text{Null} \triangleleft \Gamma' \{r'.f \mapsto S_{\text{False}}\} * r'}
\end{aligned}$$

Figure 13: Rules for **while**

Definition 3.29 (Actual session type) Let Γ and h be such that $\vdash h : \Gamma$. For any r in Γ such that $\Gamma(r)$ is a session type S , we define S' , the actual session type of r in h according to Γ , as follows:

- If S is a branch then $S' = S$.
- If S is a variant $\langle l : S_l \rangle_{l \in E}$, then $S' = S_{h(r'.f')}$, where r' and f' are as given by Lemma 3.28.

Definition 3.30 (Consistency of call traces) Let tr be a call trace mapping for a heap h and let Γ be a type environment such that $\vdash h : \Gamma$. We say that tr is consistent with Γ if for every r in Γ with actual session type S we have $\text{class}(h(r)).\text{session} \xrightarrow{tr(h,r)}^* S$.

Theorem 3.31 (Conformance) Suppose we are in a context parameterised by a set of well-typed declarations.

Let $(h_1 * r_1; e_1)$ be a program state together with a valid call trace mapping tr_1 , and suppose that $(h_1 * r_1; e_1) \longrightarrow \dots \longrightarrow (h_n * r_n; e_n)$ is a reduction sequence such that r_1 is a prefix of all r_i . Definition 3.26 gives a corresponding sequence of call traces tr_i .

If there exists Γ such that tr_1 is consistent with Γ and $\Gamma * r_1 \triangleright (h_1 * r_1; e_1) : T \triangleleft \Gamma' * r'$ then for all i , tr_i is valid.

Proof. Postponed, again, to Section 7 as it makes use of the proof of Theorem 7.16 which will be proved there.

Corollary 3.32 Given a well-typed program, starting from the initial state described at the end of Section 3.2 with the initial call trace mapping $\{\text{top} \mapsto m\}$, and given a reduction sequence from there, the call trace mappings obtained by Definition 3.26 following the reductions are valid throughout the sequence.

Proof. We just have to see that:

1. the initial call trace mapping is valid, as the main method m is required to appear in the initial session type of the main class;
2. it is also consistent with the initial typing given in Section 3.6, as the initial Γ contains no session type;
3. the initial current object path is reduced to an object identifier and, therefore, stays a prefix of the current object path throughout any reduction sequence. \square

4 Extensions to the Sequential Language

This section describes some extensions of the core language presented in the previous section.

Top-level syntax (add to Figure 5) :

$$\begin{aligned} M &::= \dots \mid \text{req } F \text{ ens } F \text{ for } T \text{ m}(T \ x) \{e\} \\ e &::= \dots \mid m(e) \end{aligned}$$

Reduction rule (add to Figure 7):

$$(\text{R-SELF CALL}) \frac{\text{req } _ \text{ ens } _ \text{ for } _ \text{ m}(_ \ x) \{e\} \in h(r).\text{class}}{(h * r; \ m(v)) \longrightarrow (h * r; \ e\{v/x\})}$$

Top-level typing rules (add or replace in Figure 9):

$$\begin{aligned} (\text{T-SELF CALL}) & \frac{\Gamma * r \triangleright_C e : T \triangleleft \Gamma' * r' \quad \Gamma'(r') = C[F] \quad \text{req } F \text{ ens } F' \text{ for } T' \text{ m}(T \ x) \{e\} \in C}{\Gamma * r \triangleright_C m(e) : T' \triangleleft \Gamma' \{r' \mapsto C[F']\} * r'} \\ (\text{T-ANNOT METH}) & \frac{\text{this} : C[F], x : T' * \text{this} \triangleright_C e : T \triangleleft \text{this} : C[F'], x : T'' * \text{this} \quad F' \neq \langle _ \rangle}{\vdash_C \text{req } F \text{ ens } F' \text{ for } T \text{ m}(T' \ x) \{e\}} \\ (\text{T-CLASS}) & \frac{\overrightarrow{\text{Null}} \vec{f} \vdash C : S \quad \forall M \in \vec{M}. (M \text{ has req/ens} \Rightarrow \vdash_C M)}{\vdash \text{class } C \{S; \vec{f}; \vec{M}\}} \end{aligned}$$

Figure 14: Rules for recursive methods and other self-calls

4.1 While Loops

The language can easily be extended to include while loops, by adding the rules in Figure 13. The reduction rule defines while recursively in terms of switch. There are two typing rules, derived from T-SWITCH and T-SWITCHLINK. The first deals with a straightforward while loop that has no interaction with session types, and the second deals with the more interesting case in which the condition of the loop is linked to the session type of an object.

4.2 Self-Calls and Recursive Methods

The rules in Figure 14 extend the language to include self-calls (method calls on this). This extension also supports recursive calls, which are necessarily self-calls. Self-calls do not check or advance the session type, and a method that is only self-called does not appear in the session type. A method that is self-called and called from outside appears in the session type, and calls from outside do check and advance the session type. The reason why it is safe to not check the session type for self-calls is that the effect of the self-call on the field typing is included in the effect of the method that calls it. All of the necessary checking of session types is done because of the original outside call that eventually leads to the self-call.

Because they are not in the session type, self-called methods must be explicitly annotated with their initial (req) and final (ens) field typings. The annotations are used to type self-calls (T-SELF CALL) and method definitions (T-ANNOT METH). The result type and parameter type are also specified as part of the method definition, again because the method is not in the session type.

If a method is in the session type then its body is checked by the first hypothesis of T-CLASS, but the annotations (if present) are ignored except when they are needed to check recursive calls. If a method has an annotation then its body is checked by the second hypothesis of T-CLASS. If both conditions apply then the body is checked twice. An implementation could optimize this.

An annotated method cannot produce a variant field typing or have a link type, because T-SWITCHLINK can only analyze a variant session type, not a variant field typing.

4.3 Shared Types and Base Types

The formal language described in this paper has a very strict linear type system. It is straightforward to add non-linear classes as an orthogonal extension: they would not have session types and their instances would be shared objects, treated in a completely standard way. Our prototype implementation, described in Section 8.4, includes them, but including them in the formalisation would only complicate the typing rules.

```

FileReadCh = &{OPEN: ?String.⊕{OK: OpenCh, ERROR: FileReadCh}, QUIT: End}      1
OpenCh = &{HASNEXT: ⊕{TRUE: CanReadCh, FALSE: MustCloseCh}, CLOSE: FileReadCh} 2
MustCloseCh = &{CLOSE: FileReadCh}                                           3
CanReadCh = &{READ: !String.OpenCh, CLOSE: FileReadCh }                     4

```

Figure 15: Remote file server version 1: channel session type (server side)

More interesting, and more challenging, is the possibility of introducing a more refined approach to aliasing and ownership, for example along the lines of the systems discussed in Section 9. We intend to investigate this in the future.

Base types such as **int** are also straightforward to add, and would be treated non-linearly.

4.4 Nominal Subtyping

The formal language uses a structural type system in which class names are only used in order to obtain their session types; method availability is determined solely by the session type, and method signatures are also in the session type. In particular, the subtyping relation is purely structural and makes no reference to class names. It is straightforward to adapt the language to include features associated with nominal subtyping, such as an explicitly declared inheritance hierarchy for classes with inheritance and overriding of method definitions. In this case, if class C is declared to inherit from class D , and both define session types (alternatively, C might inherit its session type from D), then the condition $C.\text{session} <: D.\text{session}$ would be required in order for the definition of C to be accepted.

5 A Distributed Example

We now present an example of a distributed system, illustrating the way in which our language unifies session-typed channels and more general typestate. The scenario is a file server, which clients can communicate with via a channel. The file server uses a local file, represented by a `File` object as defined in Section 2, and responds to requests such as `OPEN` and `HASNEXT` on the channel. On the client side, the remote file is represented by an object of class `RemoteFile`, whose interface is similar to `File`. In this “stub” object, methods such as `open` are implemented by communicating with the file server.

The channel between the client and the server has a session type in the standard sense, which defines a communication protocol. In our language, each endpoint of the channel is represented by an object of class `Chan`, with a class session type derived from the channel session type. This class session type also expresses the definition of the communication protocol, by specifying when the methods **send** and **receive** are available.

For the purpose of this example, we imagine that the communication protocol (channel session type) is defined by the provider of the file server, while the class session type of `RemoteFile` is defined by the implementor of a file system API. We therefore present two versions of the example: one in which the channel session type, and the class session type of `RemoteFile`, have the same structure; and one in which they have different structures.

5.1 Distributed Example Version 1

Figure 15 defines a channel session type for interaction between a file server and a client. The type of the server’s endpoint is shown, and the type `FileReadCh` is the starting point of the protocol. The type constructor `&` means that the server offers a choice, in this case between `OPEN` and `QUIT`; the client makes a choice by sending one of these labels. If `OPEN` is selected, the server receives (constructor `?`) a `String` and then (the `.` constructor means sequencing) the constructor `⊕` indicates that the server can choose either `OK` or `ERROR`. The remaining definitions are read in the same way; note that `End` means termination of the protocol. The type of the client’s endpoint is dual, meaning that receive (`?`) and send (`!`) are exchanged, as are offer (`&`) and select (`⊕`). When the server offers a choice, the client must make a choice, and *vice versa*.

```

FileRead_cl = {Null send({OPEN}): {Null send(String): {{OK, ERROR} receive():
1
                                     <OK: Open_cl,
2
                                     ERROR: FileRead_cl>}},
3
               Null send({QUIT}): {}}
4
where
5
  Open_cl = {Null send({HASNEXT}): {{TRUE, FALSE} receive():
6
                                     <TRUE: CanRead_cl, FALSE: MustClose_cl>},
7
            Null send({CLOSE}): FileRead_cl}
8
  MustClose_cl = {Null send({CLOSE}): FileRead_cl}
9
  CanRead_cl = {Null send({READ}): {String receive(): Open_cl},
10
               Null send({CLOSE}): FileRead_cl}
11

FileRead_s = {{OPEN, QUIT} receive(): <OPEN: {String receive():
1
                                     {Null send({OK}): Open_s,
2
                                     Null send({ERROR}): FileRead_s},
3
                                     QUIT: {}}}>
4

where
5
  Open_s = {{HASNEXT, CLOSE} receive():
6
            <HASNEXT: {Null send({TRUE}): CanRead_s,
7
            Null send({FALSE}): MustClose_s},
8
            CLOSE: FileRead_s}>
9
  MustClose_s = {{CLOSE} receive(): <CLOSE: FileRead_s>}
10
  CanRead_s = {{READ, CLOSE} receive(): <READ: {Null send(String): Open_s},
11
              CLOSE: FileRead_s}>
12

```

Figure 16: Remote file server version 1: client and server class session types generated from channel session type FileReadCh

```

class RemoteFile {
1
  session {connect: Init}
2
  where Init = {open: <OK: Open, ERROR: Init>}
3
            Open = {hasNext: <TRUE: Read, FALSE: Close>, close: Init }
4
            Read = {read: Open, close: Init }
5
            Close = {close: Init }
6
  }
7
  channel;
8
  Null connect(<FileReadCh> server) {
9
    channel = server.request();
10
  }
11
  {OK,ERROR} open(String name) {
12
    channel.send(OPEN);
13
    channel.send(name);
14
    switch (channel.receive()) {
15
      OK: OK;
16
      ERROR: ERROR;
17
    }
18
  }
19
  {TRUE,FALSE} hasNext () {
20
    channel.send(HAS_NEXT);
21
    switch (channel.receive()) {
22
      TRUE: TRUE;
23
      FALSE: FALSE;
24
    }
25
  }
26
  String read() {
27
    channel.send(READ);
28
    channel.receive();
29
  }
30
  Null close() {
31
    channel.send(CLOSE);
32
  }
33
}
34
35

```

Figure 17: Remote file server version 1: client side stub


```

class FileServer {
    session { Null main(<FileReadCh> port): {} }

    channel; file;

    Null main(<FileRead_c> port) {
        file = new File();
        channel = port.accept();
        fileRead();
    }
    req FileRead_s channel, Init file
    ens {} channel, Init file
    Null fileRead() {
        switch (channel.receive()) {
            OPEN:
                switch (file.open(channel.receive())) {
                    OK: open();
                    ERROR: fileRead();
                }
            QUIT: null;
        }
    }
    req Open_s channel, Open file
    ens {} channel, Init file
    Null open() {
        switch (channel.receive()) {
            HASNEXT:
                switch (file.hasNext()) {
                    TRUE: channel.send(TRUE); canRead();
                    FALSE: channel.send(FALSE); mustClose();
                }
            CLOSE: file.close(); fileRead();
        }
    }
    req MustClose_s channel, Close file
    ens {} channel, Init file
    Null mustClose() {
        switch (channel.receive()) {
            CLOSE: file.close(); fileRead();
        }
    }
    req CanRead_s channel, Read file
    ens {} channel, Init file
    Null canRead() {
        switch (channel.receive()) {
            READ: channel.send(file.read()); open();
            CLOSE: file.close(); fileRead();
        }
    }
}

```

Figure 18: Remote file server version 1: server code

The structure of the channel session type is similar to that of the class session type of `File` from Section 2, in the sense that `HASNEXT` is used to discover whether or not data can be read.

We regard each endpoint of a channel as an object with **send** and **receive** methods. For every channel session type there is a corresponding class session type that specifies the availability and signatures of **send** and **receive**. The general translation is defined in Section 6, Figure 25. For the particular case of `FileReadCh`, the client and server class session types are as defined in Figure 16 (using Style 2 since the signatures vary and there is no associated class declaration).

Selecting one option from a range (\oplus) corresponds to availability of **send** with a range of signatures, each with a parameter type representing one of the possible labels; here we are taking advantage of overloading, disambiguated by parameter type. Offering a choice ($\&$) corresponds to a **receive** in which the subsequent session depends on the label that is received. Sending and receiving data correspond straightforwardly to **send** and **receive** with appropriate signatures.

```

FileChannel = &{OPEN: ?String.⊕{OK: CanRead, ERROR: FileChannel}, QUIT: End}      1
CanRead = &{READ: ⊕{EOF: FileChannel, DATA: !String.CanRead}, CLOSE: FileChannel} 2

```

Figure 19: Remote file server version 2: channel session type (server side)

```

ClientCh = {Null send({OPEN}): {Null send(String): {{OK, ERROR} receive():      1
                                                    {OK: CanRead_cl,      2
                                                    ERROR: ClientCh}}},      3
            Null send({QUIT}): {}}      4
where CanRead_cl = {Null send({READ}): {{EOF, DATA} receive():      5
                                                    {EOF: ClientCh,      6
                                                    DATA:{String receive(): CanRead_cl}}},      7
                    Null send({CLOSE}): ClientCh}      8

ServerCh = {{OPEN, QUIT} receive(): {OPEN: {String receive():      1
                                           {Null send({OK}): CanRead_cl,      2
                                           Null send({ERROR}): ServerCh}},      3
          QUIT: {}}}      4
where CanRead_cl = {{READ, CLOSE} receive():      5
{READ: {Null send({EOF}): ServerCh,      6
        Null send({DATA}):{Null send(String): CanRead_cl}},      7
  CLOSE: ServerCh}}      8

```

Figure 20: Remote file server version 2: client and server class session types generated from channel session type FileChannel

Figure 17 defines the class `RemoteFile`, which acts as a local proxy for a remote file server. Its interface is similar to that of the class `File` from Section 2; the only difference is that `RemoteFile` has an additional method `connect`, which must be called in order to establish a connection to the file server. The types `RemoteFile.Init` and `File.Init` are equivalent (Definition 3.9): each is a subtype of the other, and they can be used interchangeably.

The methods of `RemoteFile` are implemented by communicating over a channel to a file server. The `connect` method has a parameter of type $\langle \text{FileReadCh} \rangle$. A value of this type represents an access point, analogous to a URL, on which a connection can be requested by calling the **request** method (line 11); the resulting channel endpoint has type `FileRead_cl`.

The remaining methods communicate on the channel, and thus advance the type of the field `channel`. The similarity of structure between the channel session type `FileReadCh` and the class session type `Init` is reflected in the simple definitions of the methods, which just copy information between their parameters and results and the channel. There is one point of interest in relation to the `close` method. It occurs three times in the class session type, and according to our type system, its body is type checked once for each occurrence. Each time, the initial type environment in which the body is checked has a different type for the `channel` field: `Open_cl`, `MustClose_cl` or `CanRead_cl`. Type checking is successful because all of these types allow **send**({CLOSE}).

Figure 18 defines the class `FileServer`, which accesses a local file system and uses the server endpoint of a channel of type `FileReadCh`. The session type of this class contains the single method `main`, with a parameter of type $\langle \text{FileReadCh} \rangle$. We imagine this `main` method to be the top-level entry point of a stand-alone application, with the parameter value (the access point or URL for the server) being provided when the application is launched. The server uses **accept** to listen for connection requests, and when a connection is made, it obtains a channel endpoint of type `FileRead_s`.

The remaining methods of `FileServer` are mutually recursive in a pattern that matches the structure of `FileRead_s`. The methods are self-called, and do not appear in the class session type; instead, they are annotated with pre- and post-conditions on the types of the fields `channel` and `file`. The direct correspondence between the structure of the channel session type and the class session type of `File` is again reflected in the code, for example on lines 29 and 30 where the result of calling `hasNext` on `file` directly answers the `HASNEXT` query on `channel`.

```

class RemoteFile {
    session {connect: Init}
    where Init = {open: {OK: Open, ERROR: Init}}
           Open = {hasNext: {TRUE: Read, FALSE: Close}, close: Init}
           Read = {read: Open, close: Init}
           Close = {close: Init}

    channel; state;

    Null connect(<FileChannel> c) {
        channel = c.request();
    }
    {OK,ERROR} open(String name) {
        channel.send(OPEN);
        channel.send(name);
        switch (channel.receive()) {
            OK: state = READ; OK;
            ERROR: ERROR;
        }
    }
    {TRUE,FALSE} hasNext() {
        channel.send(READ);
        switch (channel.receive()) {
            EOF: state = EOF; FALSE;
            DATA: state = DATA; TRUE;
        }
    }
    String read() {
        state = READ;
        channel.receive();
    }
    Null close() {
        switch (state) {
            EOF: null;
            READ: channel.send(CLOSE);
            DATA: channel.receive(); channel.send(CLOSE);
        }
    }
}

```

Figure 21: Remote file server version 2: client side stub

5.2 Distributed Example Version 2

This version has a different channel session type, `FileChannel`, defined in Figure 19, which does not match the class session type `FileRead`. The difference is that there is no `HASNEXT` option; instead, the `READ` option is always available. If there is no more data then `EOF` is returned in response to `READ`; alternatively, `DATA` is returned, followed by the desired data. The corresponding class session types for the client and server endpoints are defined in Figure 20.

The implementation of `RemoteFile` must now mediate between the different structures of the class session type `FileRead` and the channel session type `FileChannel`. The new definition is in Figure 21. The main point is that the definition of the `close` method must depend on the state of the channel. For example, if `close` is called immediately after a call of `hasNext` that returns `TRUE`, then the channel session type requires data to be read before `CLOSE` can be sent. We therefore introduce the field `state`, which stores a value of the enumerated type `{EOF, READ, DATA}`. This field represents the state of the channel (equivalently, the session type of the `channel` field): `EOF` corresponds to `ClientCh`, `READ` corresponds to `CanRead`, and `DATA` corresponds to the point after the `DATA` label in `CanRead`. The definition of `close` contains a **switch** on `state`, with appropriate behaviour for each possible value. It is also possible for `state` to be `null`, but this only occurs before `open` has been called, and at this point `close` is not available.

In order to type check this example we take advantage of the fact that the body of the `close` method is repeatedly checked, according to its occurrence in the class session type. The value of `state` always corresponds to the state of `channel`. This correspondence is not represented in the type system — that would require some form of dependent type — but whenever the body of `close`

```

class FileServer {
  session {main: {}}

  channel; file;

  Null main(<FileChannel> c) {
    file = new File();
    channel = c.accept();
    serverCh();
  }
  req ServerCh channel, Init file
  ens {} channel, Init file
  Null serverCh() {
    switch (channel.receive()) {
      OPEN:
        switch (file.open(channel.receive())) {
          OK: canRead();
          ERROR: serverCh();
        }
      QUIT: null;
    }
  }
  req CanRead_s channel, Open file
  ens {} channel, Init file
  Null canRead() {
    switch (channel.receive()) {
      READ:
        switch (file.hasNext()) {
          TRUE: channel.send(DATA); channel.send(file.read());
              canRead();
          FALSE: channel.send(EOF); file.close(); serverCh();
        }
      CLOSE: file.close(); serverCh();
    }
  }
}

```

Figure 22: Remote file server version 2: server code

is type checked, the *type* of `channel` is compatible with the *value* of `state`, and so typechecking succeeds. More precisely, each possible value of `state` corresponds to a different singleton type for `state` (typing rule T-LABEL), and rule T-SWITCH only checks the branches that correspond to possible values in the enumerated type of the condition. So each time the body of `close` is type checked, only *one* branch (because the type of `state` is a singleton) of the **switch** is checked, corresponding to the value of `state` for that occurrence of `close`.

6 A Core Distributed Language

We now define the core of the distributed language illustrated in Section 5. For the top-level language, the only additions are the access points and their types $\langle T \rangle$, channel session types and their translation to class session types, and the **spawn** primitive. However, there are significant changes to the internal language, in order to introduce a layer of concurrently executing components that communicate on channels.

6.1 Syntax

Figure 23 defines the new syntax. The types of access points are top-level declarations. Of the new values, access points n can appear in top-level programs, but channel endpoints c^\pm are part of the internal language. The **spawn** primitive was not used in the example in Section 5, but its behaviour is to start a new thread executing the specified method on a new instance of the specified class. Although a parameter is required as in any method call, for simplicity the type system restricts the parameter's type to be `Null` in this case, so that there is only one form of inter-thread communication. The syntax of channel session types Σ is included so that the types

Declarations	$D ::= \dots \mid \text{access } \langle \Sigma \rangle n$
Values	$v ::= \dots \mid c^+ \mid c^- \mid n$
Expressions	$e ::= \dots \mid \text{spawn } C.m(e)$
Contexts	$\mathcal{E} ::= \dots \mid \text{spawn } C.m(\mathcal{E})$
Channel session types	$\Sigma ::= \text{end} \mid X \mid \mu X. \Sigma \mid ?[T]. \Sigma \mid ![T]. \Sigma$ $\mid \& \{l : \Sigma_l\}_{l \in E} \mid \oplus \{l : \Sigma_l\}_{l \in E}$
States	$s ::= \dots \mid s \parallel s \mid (\nu c) s$

Figure 23: Additional syntax for channels and states

Structural congruence:

$$s_1 \parallel s_2 \equiv s_2 \parallel s_1 \quad s_1 \parallel (s_2 \parallel s_3) \equiv (s_1 \parallel s_2) \parallel s_3 \quad (\text{E-COMM}, \text{E-ASSOC})$$

$$s_1 \parallel (\nu c) s_2 \equiv (\nu c) (s_1 \parallel s_2) \text{ if } c^+, c^- \text{ not free in } s_1 \quad (\text{E-SCOPE})$$

Reduction rules:

$$\begin{aligned}
(\text{R-INIT}) \quad & \frac{h(r).f = n \quad h'(r').f' = n \quad c \text{ fresh}}{(h * r; \mathcal{E}[f.\text{accept}()]) \parallel (h' * r'; \mathcal{E}'[f'.\text{request}()]) \longrightarrow (\nu c) ((h * r; \mathcal{E}[c^+]) \parallel (h' * r'; \mathcal{E}'[c^-]))} \\
(\text{R-COMBASE}) \quad & \frac{h(r).f = c^p \quad h'(r').f' = c^{\bar{p}} \quad v \notin \mathcal{O}}{(h * r; \mathcal{E}[f.\text{send}(v)]) \parallel (h' * r'; \mathcal{E}'[f'.\text{receive}()]) \longrightarrow (h * r; \mathcal{E}[\text{null}]) \parallel (h' * r'; \mathcal{E}'[v])} \\
(\text{R-COMOBJ}) \quad & \frac{h(r).f = c^p \quad h'(r').f' = c^{\bar{p}} \quad \varphi \in \text{Inj}(\text{dom}(h \downarrow o), \mathcal{O} \setminus \text{dom}(h'))}{(h * r; \mathcal{E}[f.\text{send}(o)]) \parallel (h' * r'; \mathcal{E}'[f'.\text{receive}()]) \longrightarrow} \\
& \quad (h \uparrow o * r; \mathcal{E}[\text{null}]) \parallel (h' + \varphi(h \downarrow o) * r'; \mathcal{E}'[\varphi(o)]) \\
(\text{R-SPAWN}) \quad & \frac{o \text{ fresh} \quad C.\text{fields} = \vec{f} \quad m(x) \{e\} \in C}{(h * r; \mathcal{E}[\text{spawn } C.m(v)]) \longrightarrow (h * r; \mathcal{E}[\text{null}]) \parallel (o = C[\vec{f} = \vec{\text{null}}] * o; e\{\text{null}/x\})} \\
(\text{R-PAR}) \quad & \frac{s \longrightarrow s'}{s \parallel s'' \longrightarrow s' \parallel s''} \quad (\text{R-STR}) \quad \frac{s \equiv s' \quad s' \longrightarrow s'' \quad s'' \equiv s'''}{s \longrightarrow s'''} \quad (\text{R-NEWCHAN}) \quad \frac{s \longrightarrow s'}{(\nu c) s \longrightarrow (\nu c) s'}
\end{aligned}$$

Top-level typing rules:

$$\begin{aligned}
(\text{T-SPAWN}) \quad & \frac{\Gamma * r \triangleright e : \text{Null} \triangleleft \Gamma' * r' \quad C.\text{session} = \{ _ m(\text{Null}) : _ ; \dots \}}{\Gamma * r \triangleright \text{spawn } C.m(e) : \text{Null} \triangleleft \Gamma' * r'} \\
(\text{T-NAME}) \quad & \frac{\text{access } \langle \Sigma \rangle n}{\Gamma * r \triangleright n : \llbracket \langle \Sigma \rangle \rrbracket \triangleleft \Gamma * r}
\end{aligned}$$

Figure 24: Reduction and top-level typing rules for concurrency and channels

of access points can be declared. The syntax of states is extended to include parallel composition and a channel binder νc , which binds both c^+ and c^- in the style of [33]. In a parallel composition, the states are exactly states from the semantics of the sequential language; in particular, each one has its own heap. This means that **spawn** generates a new heap as well as a new executing method body. Communication between parallel expressions is only via channels.

The syntax extensions do not include **request**, **accept**, **send** and **receive**, as they are treated as method names.

6.2 Semantics

Figure 24 defines the reduction rules for the distributed language, as well as the top-level typing rules. The reduction rules make use of a pi-calculus style structural congruence relation, again following [33]. It is the smallest congruence (with respect to parallel and binding) that is also closed under the given rules.

Rule R-INIT defines interaction between **accept** and **request**, which creates a fresh channel c and substitutes one endpoint into each expression.

There are two rules for communication, involving interaction between `send` and `receive`. Rule R-COMBASE is for communication of non-objects and rule R-COMOBJ is for communication of objects. R-COMBASE expresses a straightforward transfer of a value, while R-COMOBJ also transfers part of the heap corresponding to the contents of a transferred object. In R-COMOBJ, φ is an arbitrary renaming function which associates to every identifier in $\text{dom}(h)$ an identifier not in $\text{dom}(h')$. This rule can easily be made deterministic in practice by using a total ordering on identifiers and a mechanism to generate fresh ones.

R-SPAWN creates a new parallel state whose heap contains a single instance of the specified class. As discussed above, communication between threads is only through channels in order to keep the formal system a reasonable size; therefore, no data is transmitted to the new thread and the body of the method being spawned always has its parameter replaced by the literal `null`. The type system will ensure that $v = \text{null}$, so that this semantics makes sense. The remaining rules are standard.

Returning to R-COMOBJ, there is some additional notation associated with identifying the part of the heap that must be transferred; we now define it. First, write \mathcal{O} for the set of all object identifiers.

Definition 6.1 *Let h be a heap. For any entry $o = C[\{f_i = v_i\}_{i \in I}]$ in h , we define the children of o in h to be the set of all v_i which are object identifiers: $\text{children}_h(o) = \{v_i \mid i \in I\} \cap \mathcal{O}$.*

We say that an object identifier o in $\text{dom}(h)$ is a root in h if there is no o' in $\text{dom}(h)$ such that $o \in \text{children}_h(o')$. We note $\text{roots}(h)$ the set of roots in h .

We say that h is complete if for any o in $\text{dom}(h)$ we have $\text{children}_h(o) \subseteq \text{dom}(h)$.

If h is complete, we define the descendants of o in h to be the smallest set containing o and the children of any object it contains. Formally, let $\text{children}_h^0(o) = \{o\}$ and for $i \geq 1$, $\text{children}_h^i(o) = \bigcup_{\omega \in \text{children}_h^{i-1}(o)} \text{children}_h(\omega)$. Then $\text{desc}_h(o) = \bigcup_{i \in \mathbb{N}} \text{children}_h^i(o)$.

Definition 6.2 (Heap separation) *Let h be a complete heap and o a root of h . We define $h \downarrow o$ to be the sub-heap obtained by restricting h to the descendants of o , and $h \uparrow o$ to be the sub-heap obtained by removing from h the descendants of o . Note that $h \downarrow o$ is complete and has the property that o is its only root.*

Definition 6.3 (Additional notation) • *Let h be a heap and let φ be a function from \mathcal{O} to \mathcal{O} . We denote by $\varphi(h)$ the result of applying φ to all object identifiers in h , including inside object records.*

- *We denote by $\text{Inj}(A, B)$ the set of injective functions from A to B .*
- *We denote by $+$ the disjoint union of heaps or environments, i.e. the operation $h + h'$ is defined by merging h and h' if their domains are disjoint and undefined otherwise.*

6.3 Type System

The type system treats `send`, `receive`, `request` and `accept` as method calls on objects whose session types are defined by the translations in Figure 25. A channel endpoint with (channel) session type Σ is treated as an object with (class) session type $\llbracket \Sigma \rrbracket$. The type constructor $\&$ (offer) is translated into a `receive` method with return type `linkthis` in order to capture the relationship between the received label and the subsequent type. The type constructor \oplus (select) is translated into a collection of `send` methods with different parameter types, each being a singleton type for the corresponding label.

In a similar but much simpler way, an access type $\langle \Sigma \rangle$ is translated into a (class) session type that allows both `request` and `accept` to be called repeatedly and at any time. These two methods need to return dual channel endpoints, which requires the following definition.

Given a channel session type Σ , define a class session type $\llbracket \Sigma \rrbracket$ as follows.

$$\begin{aligned}\llbracket \text{end} \rrbracket &= \{\} \\ \llbracket X \rrbracket &= X \\ \llbracket \mu X. \Sigma \rrbracket &= \mu X. \llbracket \Sigma \rrbracket \\ \llbracket ?[T]. \Sigma \rrbracket &= \{T \text{ receive}(\text{Null}) : \llbracket \Sigma \rrbracket\} \\ \llbracket ![T]. \Sigma \rrbracket &= \{\text{Null send}(T) : \llbracket \Sigma \rrbracket\} \\ \llbracket \&\{l : \Sigma_l\}_{l \in E} \rrbracket &= \{\text{linkthis receive}(\text{Null}) : \langle l : \llbracket \Sigma_l \rrbracket \rangle_{l \in E}\} \\ \llbracket \oplus\{l : \Sigma_l\}_{l \in E} \rrbracket &= \{\text{Null send}(\langle l \rangle) : \llbracket \Sigma_l \rrbracket\}_{l \in E}\end{aligned}$$

In the type system, a channel endpoint with session type Σ is treated as an object with type $\llbracket \Sigma \rrbracket$. Calls of **send** and **receive** are typed as standard method calls.

Given an access type $\langle \Sigma \rangle$, define a class session type $\llbracket \langle \Sigma \rangle \rrbracket$ by

$$\llbracket \langle \Sigma \rangle \rrbracket = \mu X. \{\llbracket \Sigma \rrbracket \text{ request}(\text{Null}) : X, \llbracket \Sigma \rrbracket \text{ accept}(\text{Null}) : X\}.$$

In the type system, an access point with type $\langle \Sigma \rangle$ is treated as an object with type $\llbracket \langle \Sigma \rangle \rrbracket$. Calls of **request** and **accept** are typed as standard method calls.

Figure 25: Object types for channels and access points

These rules add to or replace the rules in Figure 11.

$$\begin{aligned}(\text{T-CHAN}) \quad & \Gamma, c^p : T * r \triangleright c^p : T \triangleleft \Gamma * r & (\text{T-EMPTY}) \quad & \Theta \vdash \varepsilon : \llbracket \Theta \rrbracket \\ (\text{T-HADD}) \quad & \frac{\Theta \vdash h : \Gamma \quad \Gamma, o : C[\{\text{Null } f_i\}_{1 \leq i \leq n}] * o \triangleright f_1 \leftrightarrow v_1; \dots; f_n \leftrightarrow v_n : \text{Null} \triangleleft \Gamma' * o}{\Theta \vdash h, \{o = C[\{f_i = v_i\}_{1 \leq i \leq n}]\} : \Gamma'} \\ (\text{T-HIDE}) \quad & \frac{\Theta \vdash h : \Gamma, o : C[F] \quad F \vdash C : S}{\Theta \vdash h : \Gamma, o : C[S]} & (\text{T-STATE}) \quad & \frac{\Theta \vdash h : \Gamma \quad \Gamma * r \triangleright e : T \triangleleft \Gamma' * r'}{\Theta; \Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r'} \\ (\text{T-THREAD}) \quad & \frac{\Theta; \Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r'}{\Theta \vdash (h * r; e)} & (\text{T-PAR}) \quad & \frac{\Theta \vdash s \quad \Theta' \vdash s'}{\Theta + \Theta' \vdash s \parallel s'} \\ (\text{T-NEWCHAN}) \quad & \frac{\Theta, c^+ : \Sigma, c^- : \bar{\Sigma} \vdash s}{\Theta \vdash (\nu c) s}\end{aligned}$$

Figure 26: Internal typing rules for the distributed language

Definition 6.4 (Dual channel type) *The dual type $\bar{\Sigma}$ of a channel session type Σ is defined inductively as follows:*

$$\begin{aligned}\overline{\text{end}} &= \text{end} \\ \overline{X} &= X \\ \overline{\mu X. \Sigma} &= \mu X. \bar{\Sigma} \\ \overline{![T]. \Sigma} &= ?[T]. \bar{\Sigma} \\ \overline{\oplus\{l : \Sigma_l\}_{l \in E}} &= \&\{l : \bar{\Sigma}_l\}_{l \in E}\end{aligned}$$

together with symmetric cases so that $\bar{\bar{\Sigma}} = \Sigma$. It is sufficient to use this inductive definition, rather than a coinductive definition [31], because we have adopted the equi-recursive convention (Definition 3.9).

By convention, **request** returns a channel endpoint of type $\llbracket \bar{\Sigma} \rrbracket$ and **accept** returns an endpoint of type $\llbracket \Sigma \rrbracket$.

Because access points n are global constants, they can be used repeatedly even though their session types are linear; there is no restriction to a single occurrence of a given name.

The only new typing rules for the top-level language are in Figure 24. T-SPAWN allows a method to be used in a **spawn** expression if it is available in the initial session type of the specified class. T-NAME obtains the type of an access point from its declaration, and assigns an object type according to the translation described above.

Figure 26 contains typing rules for the internal language with the concurrency extensions. Rules with the same names as rules in Figure 11 are replacements.

Rule T-CHAN takes the type of a channel endpoint from the typing environment. The remaining rules involve a new typing environment Θ , which maps channel endpoints to channel session types Σ ; these are indeed *channel* session types, not their translations into class session types. T-HADD, T-HIDE and T-STATE are just the corresponding rules from Figure 11 with Θ added. In T-EMPTY the notation $\llbracket \Theta \rrbracket$ means that the translation from channel session types to class session types is applied to the type of each channel endpoint. In combination with T-STATE, this means that the typing of expressions uses class session types for channel endpoints; the T in T-CHAN is a class session type.

T-THREAD lifts a typed state to a typed concurrent component, preserving only the channel typing Θ , which is used in T-PAR and T-NEWCHAN. In T-PAR, $\Theta + \Theta'$ means union, with the assumption that Θ and Θ' have disjoint domains. T-NEWCHAN requires the complementary endpoints of each channel to have dual session types.

6.4 Subtyping

We have two subtyping relations between channel session types: $\Sigma <: \Sigma'$ as defined in [31], and $\llbracket \Sigma \rrbracket <: \llbracket \Sigma' \rrbracket$ as defined in this paper. To avoid a detour into the definition of $\Sigma <: \Sigma'$, we state the following result without proof.

Proposition 6.5 $\Sigma <: \Sigma' \Rightarrow \llbracket \Sigma \rrbracket <: \llbracket \Sigma' \rrbracket$.

Interestingly, the converse is not true, as subtyping between translations of channel session types is a larger relation. For example:

- for all Σ , $\llbracket \Sigma \rrbracket <: \llbracket \text{end} \rrbracket$
- if E is an enumeration then $\llbracket ?[E] . \Sigma \rrbracket <: \llbracket \& \{l : \Sigma\}_{l \in E} \rrbracket$
- $\llbracket \oplus \{l : \Sigma\} \rrbracket = \llbracket !\{l\} . \Sigma \rrbracket$ and therefore by transitivity any translated \oplus type is a subtype of all the corresponding individual translated send types.

This suggests the possibility, in the context of [31], of generalizing the subtyping relation between channel session types by considering branch/select labels as values in an enumerated type. We do not explore this idea further in the present paper.

7 results

The key results concerning the distributed language supporting self-calls are, again, Subject-Reduction, Type Safety, and Conformance. Notice that we can no longer guarantee the absence of stuck states for all well-typed programs, as one endpoint of a channel may try to send when the other endpoint is not available to receive.

7.1 Properties of typing derivations

This subsection is mostly a collection of lemmas which will be used to prove the main theorems in the following ones. They draw various useful consequences from the fact that a program state is well-typed. Their proofs can be found in Appendix 10.

We define $\text{chans}(h)$ as the set of channel endpoints appearing in object records in h . We define $\text{chans}(\Gamma)$ and $\text{objs}(\Gamma)$ as the sets of, respectively, channel endpoints and object identifiers in $\text{dom}(\Gamma)$. We have $\text{dom}(\Gamma) = \text{chans}(\Gamma) \cup \text{objs}(\Gamma)$.

Lemma 7.1 *Suppose $\Theta \vdash h : \Gamma$. Then (a) h is complete, (b) $\text{chans}(\Gamma) \subseteq \text{dom}(\Theta) \setminus \text{chans}(h)$ and (c) $\text{objs}(\Gamma) \subseteq \text{roots}(h)$.*

Lemma 7.2 (Rearrangement of typing derivations for expressions) *Suppose we have $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$. Then there exists a typing derivation for this judgement in which:*

1. T-SUB only occurs at the very end, just before T-SWITCH or T-SWITCHLINK as the last rule in the derivation for each of the branches, or just before T-CALL as the last rule in the derivation for the parameter;

2. T-SUBENV only occurs immediately before T-SUB in the first three cases and does not occur at all in the fourth, i.e. T-CALL.

Lemma 7.3 (Rearrangement of typing derivations for heaps) Suppose $\Theta \vdash h : \Gamma$ holds. Let o be an arbitrary root of h . Then there exists a typing derivation for it such that:

1. T-SUB is never used;
2. T-SUBENV is used at most once, as the last rule leading to the right premise of the last occurrence of T-HADD;
3. every occurrence of T-HIDE follows immediately the occurrence of T-HADD concerning the same object identifier;
4. the occurrence of T-HADD concerning an identifier o' is always immediately preceded (on the left premise) by the occurrences of T-HADD/T-HIDE concerning the descendants of o' ;
5. the first root added is o .

Lemma 7.4 (Splitting of the heap) Suppose $\Theta \vdash h : \Gamma, o : T$. Let $\Theta_1 = \Theta \setminus \text{chans}(h \downarrow o)$ and let Θ_2 be Θ restricted to $\text{chans}(h \downarrow o)$. Then we have: $\Theta_1 \vdash (h \uparrow o) : \Gamma$ and $\Theta_2 \vdash (h \downarrow o) : o : T$.

Lemma 7.5 (Merging of heaps) Suppose $\Theta \vdash h : \Gamma$ and $\Theta' \vdash h' : \Gamma'$ with $\text{dom}(h) \cap \text{dom}(h') = \emptyset$ and $\text{dom}(\Theta) \cap \text{dom}(\Theta') = \emptyset$. Then we have $\Theta + \Theta' \vdash h + h' : \Gamma + \Gamma'$.

These two lemmas show, if we apply them repeatedly, that a typing derivation for a heap can be considered as a set of separate typing derivations leading to each root of the heap. This will allow us in particular to show results for particular cases where a heap has only one root and generalize them.

Lemma 7.6 Suppose $\Theta \vdash h : o : S$. Let φ be an injective function from $\text{dom}(h)$ to \mathcal{O} . Then we have $\Theta \vdash \varphi(h) : \varphi(o) : S$.

Lemma 7.7 (Opening) If $\Theta \vdash h : \Gamma$, if $\Gamma(r)$ is a branch session type S and if $h(r)$ is an object identifier o , then we know from Lemma 7.1 that h contains an entry for o . Let C be the class of this entry, then there exists a field typing F for C such that $\Theta \vdash h : \Gamma\{r \mapsto C[F]\}$ and $F \vdash C : S$.

Lemma 7.8 (Closing) If $\Theta \vdash h : \Gamma$ and $\Gamma(r) = C[F]$ and $F \vdash C : S$, then $\Theta \vdash h : \Gamma\{r \mapsto S\}$.

Lemma 7.9 (modification of the heap) Suppose that we have $\Theta \vdash h : \Gamma$ and $\Gamma * r \triangleright v' : T' \triangleleft \Gamma' * r$, and that $\Gamma'(r.f) = T$ where T is not a variant. Let $v = h(r).f$. The modified heap $h\{r.f \mapsto v'\}$ can be typed as follows:

1. if v is an object identifier or a channel endpoint, then:

$$\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}, v : T$$

2. if v is not an object or channel and T is not a link type, then:

$$\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}$$

3. if $v = l_0$ and $T = \text{link } f'$, then:

- $\Gamma'(r.f') = \langle l : S_l \rangle_{l \in E}$ for some E such that $l_0 \in E$ and some set of branch session types S_l . Note that this implies $f \neq f'$.
- $\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}\{r.f' \mapsto S_{l_0}\}$

Lemma 7.10 (Substitution) If $\text{this} : C[F], x : T' * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'] * \text{this}$, and if $\Gamma(r) = C[F]$, then:

1. if T' is a base type (i.e. neither an object type nor a link) and v is a literal value of that type, or if v is an access point name declared with type $\langle \Sigma \rangle$ and $\llbracket \langle \Sigma \rangle \rrbracket <: T'$, we have:

$$\Gamma * r \triangleright e\{v/x\} : T \triangleleft \Gamma\{r \mapsto C[F']\} * r.$$

2. if T' is an object type and v is an object identifier or a channel endpoint, we have:

$$\Gamma, v : T' * r \triangleright e\{v/x\} : T \triangleleft \Gamma\{r \mapsto C[F']\} * r.$$

Lemma 7.11 (Typability of Subterms) *If \mathcal{D} is a derivation of $\Gamma * r \triangleright \mathcal{E}(e) : T \triangleleft \Gamma' * r'$ then there exist Γ_1, r_1 and U such that \mathcal{D} has a subderivation \mathcal{D}' concluding $\Gamma * r \triangleright e : U \triangleleft \Gamma_1 * r_1$ and the position of \mathcal{D}' in \mathcal{D} corresponds to the position of the hole in \mathcal{E} .*

Lemma 7.12 (Replacement) *If*

1. \mathcal{D} is a derivation of $\Gamma * r \triangleright \mathcal{E}(e) : T \triangleleft \Gamma' * r'$
2. \mathcal{D}' is a subderivation of \mathcal{D} concluding $\Gamma * r \triangleright e : U \triangleleft \Gamma_1 * r_1$
3. the position of \mathcal{D}' in \mathcal{D} corresponds to the position of the hole in \mathcal{E}
4. $\Gamma'' * r'' \triangleright e' : U \triangleleft \Gamma_1 * r_1$

then $\Gamma'' * r'' \triangleright \mathcal{E}(e') : T \triangleleft \Gamma' * r'$.

7.2 Type preservation

We use $\vdash s$ as an abbreviation for $\emptyset \vdash s$; this represents well-typedness of a closed configuration. We have the following result:

Theorem 7.13 (Subject Reduction) *If, in a context parameterised by a set of well-typed declarations, we have $\vdash s$ and $s \longrightarrow s'$, then $\vdash s'$.*

This global result is a consequence of a subject reduction theorem for a single thread, which is similar but not identical to what we stated as Theorem 3.18 (which will be a particular case). The reason it is not identical is that we need to prove that the type of an expression is preserved not only when this expression reduces on its own but also when it communicates with another thread. In order to state precisely this thread-wise type preservation theorem, we introduce a labelled transition system for threads. Transition labels can be: τ indicating internal reduction, $c^p ! [v]$ or $c^p ? [v]$ indicating that the non-object value v is sent or received on channel c^p , $c^p ! [h]$ or $c^p ? [h]$, where h is a heap with a single root o , indicating that the object o (together with its content) is sent or received on channel c^p , $n[c^p]$ indicating that the channel endpoint c^p is received from access point n , or, finally, $C.m()$ indicating that the thread spawns another one using method m of class C .

Definition 7.14 (Labelled transition system) *We define a labelled transition system for threads by the following rules:*

$$\begin{aligned}
(\text{TR-RED}) \quad & \frac{(h * r; e) \longrightarrow (h' * r'; e')}{(h * r; e) \xrightarrow{\tau} (h' * r'; e')} \quad (\text{TR-SEND}) \quad \frac{h(r).f = c^p \quad v \notin \mathcal{O}}{(h * r; \mathcal{E}[f.\text{send}(v)]) \xrightarrow{c^p ! [v]} (h * r; \mathcal{E}[\text{null}])} \\
(\text{TR-SEND OBJ}) \quad & \frac{h(r).f = c^p}{(h * r; \mathcal{E}[f.\text{send}(o)]) \xrightarrow{c^p ! [h \downarrow o]} (h \uparrow o * r; \mathcal{E}[\text{null}])} \\
(\text{TR-RECEIVE}) \quad & \frac{h(r).f = c^p \quad v \notin \mathcal{O}}{(h * r; \mathcal{E}[f.\text{receive}()]) \xrightarrow{c^p ? [v]} (h * r; \mathcal{E}[v])} \\
(\text{TR-RCV OBJ}) \quad & \frac{h(r).f = c^p \quad \text{roots}(h') = \{o\} \quad \text{dom}(h) \cap \text{dom}(h') = \emptyset}{(h * r; \mathcal{E}[f.\text{receive}()]) \xrightarrow{c^p ? [h']} (h + h' * r; \mathcal{E}[o])}
\end{aligned}$$

$$\begin{array}{c}
(\text{TR-ACCEPT}) \frac{h(r).f = n}{(h * r; \mathcal{E}[f.\text{accept}()]) \xrightarrow{n[c^+]} (h * r; \mathcal{E}[c^+])} \\
(\text{TR-REQUEST}) \frac{h(r).f = n}{(h * r; \mathcal{E}[f.\text{request}()]) \xrightarrow{n[c^-]} (h * r; \mathcal{E}[c^-])} \\
(\text{TR-SPAWN}) (h * r; \mathcal{E}[\text{spawn } C.m(v)]) \xrightarrow{C.m()} (h * r; \mathcal{E}[\text{null}])
\end{array}$$

Note that both τ and $C.m()$ correspond to the thread being able to reduce on its own. An important feature of this transition relation is that the only case where several different transitions are possible from a given state is **receive**. In all cases including **receive**, the right-hand state is fully determined by the left-hand one and the transition label.

Definition 7.15 A similar transition relation, with the same set of labels, is defined on channel environments Θ as follows:

$$\begin{array}{c}
\Theta \xrightarrow{\tau} \Theta \qquad \Theta \xrightarrow{C.m()} \Theta \qquad \frac{n.\text{protocol} = \langle \Sigma \rangle \quad \forall p, c^p \notin \text{dom}(\Theta)}{\Theta \xrightarrow{n[c^+]} \Theta, c^+ : \Sigma} \\
\frac{n.\text{protocol} = \langle \Sigma \rangle \quad \forall p, c^p \notin \text{dom}(\Theta)}{\Theta \xrightarrow{n[c^-]} \Theta, c^- : \bar{\Sigma}} \qquad \frac{\llbracket \Sigma' \rrbracket <: T}{\Theta, c^p : ! [T].\Sigma, c'^{p'} : \Sigma' \xrightarrow{c^p ! [c'^{p'}]} \Theta, c^p : \Sigma} \\
\frac{\llbracket \Sigma' \rrbracket <: T}{\Theta, c^p : ? [T].\Sigma \xrightarrow{c^p ? [c'^{p'}]} \Theta, c^p : \Sigma, c'^{p'} : \Sigma'} \\
\frac{\emptyset \triangleright v : T \triangleleft \emptyset}{\Theta, c^p : ! [T].\Sigma \xrightarrow{c^p ! [v]} \Theta, c^p : \Sigma} \qquad \frac{\emptyset \triangleright v : T \triangleleft \emptyset}{\Theta, c^p : ? [T].\Sigma \xrightarrow{c^p ? [v]} \Theta, c^p : \Sigma} \\
\frac{l_0 \in E}{\Theta, c^p : \oplus \{l : \Sigma_l\}_{l \in E} \xrightarrow{c^p ! [l_0]} \Theta, c^p : \Sigma_{l_0}} \qquad \frac{l_0 \in E}{\Theta, c^p : \& \{l : \Sigma_l\}_{l \in E} \xrightarrow{c^p ? [l_0]} \Theta, c^p : \Sigma_{l_0}} \\
\frac{\Theta_1 \vdash h : o : S \quad \text{dom}(\Theta_1) \subseteq \text{chans}(h)}{\Theta_1 + \Theta_2, c^p : ! [S].\Sigma \xrightarrow{c^p ! [h]} \Theta_2, c^p : \Sigma} \\
\frac{\Theta' \vdash h : o : S \quad \text{dom}(\Theta') \subseteq \text{chans}(h) \quad \text{dom}(\Theta) \cap \text{dom}(\Theta') = \emptyset}{\Theta, c^p : ? [S].\Sigma \xrightarrow{c^p ? [h]} \Theta + \Theta', c^p : \Sigma}
\end{array}$$

Where we use $\emptyset \triangleright v : T \triangleleft \emptyset$ as an abbreviation for $\text{dummy} : C[] * \text{dummy} \triangleright v : T \triangleleft \text{dummy} : C[] * \text{dummy}$ — meaning that v is a literal value (or access point name) of type T .

We can now state our thread-wise type preservation theorem.

Theorem 7.16 (Thread-wise progress and type preservation) Let \mathcal{D} be a set of well-typed declarations, that is, such that for every class declaration D in \mathcal{D} we have $\vdash D$. In a context parameterised by \mathcal{D} , suppose we have $\Theta; \Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r'$.

Then either e is a value or there exists a transition label λ such that we have $(h * r; e) \xrightarrow{\lambda} (h' * r''; e')$ for some h', r'' and e' .

Furthermore, if λ is such that $\Theta \xrightarrow{\lambda} \Theta'$ for some Θ' then there exists Γ'' such that $\Theta'; \Gamma'' \triangleright (h' * r''; e') : T \triangleleft \Gamma' * r'$ holds.

Theorem 3.18 is the particular case where $\lambda = \tau$.

Corollary 7.17 (Theorem 3.19) If \mathcal{D} contains no name declaration and Θ is empty, then there exists s' such that $(h * r; e) \longrightarrow s'$.

Proof.[(Corollary)] In that particular case, $\Theta \vdash h : \Gamma$ implies that the heap cannot contain any n or c^p , hence λ can only be τ or of the form $C.m()$.

Proof.[(Theorem)] We always use typing derivations where subsumption steps only occur at the positions described in Lemma 7.2. Furthermore, it is sufficient to consider only cases where subsumption does not occur at the end: indeed, if it does occur, then we can add a similar subsumption step to the new judgement. The hypothesis in the theorem that $\Theta; \Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r'$ holds is necessarily a result of T-STATE and therefore is equivalent to the two hypotheses $\Theta \vdash h : \Gamma$ and $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$, which we will sometimes refer to directly.

We prove the theorem by induction on the structure of e with respect to contexts, and present the inductive case first:

If e is of the form $\mathcal{E}[e_1]$ where e_1 is not a value and \mathcal{E} is not just $[_]$ then Lemma 7.11 tells us that $\Gamma * r \triangleright e_1 : U \triangleleft \Gamma_1 * r_1$ appears in the typing derivation of $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$ for some U, r_1 and Γ_1 . From there we can apply T-STATE and derive $\Theta; \Gamma \triangleright (h * r; e_1) : U \triangleleft \Gamma_1 * r_1$. This allows us to use the induction hypothesis and get λ, e_2, r'' and h' such that $(h * r; e_1) \xrightarrow{\lambda} (h' * r''; e_2)$. Then we straightforwardly have $e \xrightarrow{\lambda} \mathcal{E}[e_2]$, either by applying R-CONTEXT if λ is τ or by replacing the context in the transition rule if it is something else. Now if λ is such that $\Theta \xrightarrow{\lambda} \Theta'$ then the induction hypothesis² also gives us Γ'' such that $\Theta'; \Gamma'' \triangleright (h' * r''; e_2) : U \triangleleft \Gamma_1 * r_1$ holds. From this we get, by reading T-STATE upwards, $\Theta' \vdash h' : \Gamma''$ and $\Gamma'' * r'' \triangleright e_2 : U \triangleleft \Gamma_1 * r_1$. We use Lemma 7.12 with the latter in order to obtain $\Gamma'' * r'' \triangleright \mathcal{E}[e_2] : T \triangleleft \Gamma' * r'$ and conclude with T-STATE.

The base cases are if e is of the form $\mathcal{E}[v]$ with \mathcal{E} elementary (i.e. not of the form $\mathcal{E}[\mathcal{E}']$ with $\mathcal{E}' \neq [_]$) and if it is not of the form $\mathcal{E}[e_1]$ at all. We list them below.

- If e is a value, there is nothing to prove.
- e cannot be a variable. Indeed, $\Theta \vdash h : \Gamma$ implies that $\text{dom}(\Gamma)$ contains only object identifiers and channel endpoints. Therefore, $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$ cannot be a conclusion of T-VAR or T-LINVAR, thus e is not a variable.
- $e = v; e'$. Then the expression reduces by R-SEQ and the initial derivation is as follows:

$$\frac{\Theta \vdash h : \Gamma \text{ (a)} \quad \frac{(1) \quad \frac{\Gamma * r \triangleright v : T' \triangleleft \Gamma_1 * r \quad \Gamma_1 * r \triangleright e' : T \triangleleft \Gamma' * r' \text{ (b)}}{\Gamma * r \triangleright v; e' : T \triangleleft \Gamma' * r'} \text{ (T-SEQ)}}{\Theta; \Gamma \triangleright (h * r; v; e') : T \triangleleft \Gamma' * r'} \text{ (T-STATE)}$$

Furthermore, T' is not a link type. Therefore, (1) cannot be T-VARF or T-VARS and it is either T-REF, T-CHAN, T-NAME, T-LABEL or T-NULL, since these are the only rules for typing values. If it is T-NULL, T-LABEL or T-NAME, then $\Gamma = \Gamma_1$; if it is T-REF or T-CHAN, then $\Gamma <: \Gamma_1$ and we can use Lemma 3.14 to get $\Gamma * r \triangleright e' : T \triangleleft \Gamma' * r'$ from (b) in both cases. We conclude from this using (a) and T-STATE.

- $e = \text{new } C()$. Then the expression reduces by R-NEW and the initial reduction is as follows:

$$\text{(T-STATE)} \frac{\Theta \vdash h : \Gamma \text{ (a)} \quad \frac{}{\Gamma * r \triangleright \text{new } C() : C.\text{session} \triangleleft \Gamma * r} \text{ (T-NEW)}}{\Theta; \Gamma \triangleright (h * r; \text{new } C()) : C.\text{session} \triangleleft \Gamma * r}$$

Let $S = C.\text{session}$. From the hypothesis that \mathcal{D} is well-typed, we have $\vdash \text{class } C \{S; \vec{f}; \vec{M}\}$. This must come from T-CLASS, therefore we have $\vec{\text{Null}} \vec{f} \vdash C : S \text{ (b)}$.

We build the following derivation:

$$\begin{array}{c} \text{(T-HADD)} \quad \frac{\text{(a)} \quad \frac{\text{T-NULL, T-SWAP, T-SEQ}}{\Gamma, o : C[\vec{\text{Null}} \vec{f}] * o \triangleright \vec{f} \leftrightarrow \vec{\text{Null}} : \text{Null} \triangleleft \Gamma, o : C[\vec{\text{Null}} \vec{f}] * o}}{\Theta \vdash h, \{o = C[\vec{f} = \vec{\text{null}}]\} : \Gamma, o : C[\vec{\text{Null}} \vec{f}]} \quad \text{(b)} \\ \text{(T-HIDE)} \quad \frac{}{\Theta \vdash h, \{o = C[\vec{f} = \vec{\text{null}}]\} : \Gamma, o : S} \end{array}$$

²clearly there is no λ such that we would have $\mathcal{E}[e_1] \xrightarrow{\lambda}$ but not $e_1 \xrightarrow{\lambda}$, hence it is legitimate to use the induction hypothesis here.

then conclude $\Theta; \Gamma, o : S \triangleright (h, \{o = C[\vec{f} = \overrightarrow{\text{null}}]\} * r; o) : S \triangleleft \Gamma * r$ using T-REF (it is not possible that r starts with o since o is fresh) and T-STATE.

- $e = \text{switch } (v) \{l : e_l\}_{l \in E}$. Then we have two cases. The slightly more complex one is if the initial derivation is as follows:

$$\frac{\frac{\frac{v \text{ is a label}}{\Gamma * r \triangleright v : \{v\} \triangleleft \Gamma * r} \quad \Gamma(r.f) = S}{\Gamma * r \triangleright v : \text{link } f \triangleleft \Gamma\{r.f \mapsto \langle v : S \rangle\} * r} \quad v \in E \text{ (b)} \quad \Gamma * r \triangleright e_v : T \triangleleft \Gamma' * r \text{ (c)}}{\Gamma * r \triangleright \text{switch } (v) \{l : e_l\}_{l \in E} : T \triangleleft \Gamma' * r}$$

(using T-LABEL, T-VARS, T-SWITCHLINK top to bottom). As usual we also have $\Theta \vdash h : \Gamma$ (a) as the other premise of T-STATE (omitted for lack of space). The reason why the initial environment of judgement (c) is Γ is because it is obtained from the version of Γ with the type of $r.f$ modified by modifying this type again, putting back S instead of the variant. (b) implies that the expression reduces by R-SWITCH. As regards type preservation, we can conclude $\Theta; \Gamma \triangleright (h * r; e_v) : T \triangleleft \Gamma' * r$ directly from (a), (c), and T-STATE. The other case is when the T-VARS step is absent and the following rule is T-SWITCH instead of T-SWITCHLINK; the argument is the same.

- $e = f \leftrightarrow v$. Then the initial derivation is as follows:

$$\frac{\frac{\dots}{\Gamma * r \triangleright v' : T' \triangleleft \Gamma_1 * r} \quad \Gamma_1(r.f) = T \text{ (c)} \quad T \text{ is not a variant (d)}}{\Gamma * r \triangleright f \leftrightarrow v' : T \triangleleft \Gamma_1\{r.f \mapsto T'\} * r} \text{ (T-SWAP)}$$

and we also have, as usual, $\Theta \vdash h : \Gamma$ (a). The fact that $\Gamma_1(r.f)$ is defined implies that $\Gamma(r.f)$ is also defined, indeed the effect of typing v can only remove from the environment or create a variant type, so it can only decrease the set of valid field references. Thus $h(r).f$ is defined as well, and the expression reduces by R-SWAP. Let $v = h(r).f$. From (a), (b), (c) and (d), we use Lemma 7.9 to get Γ'' such that $\Theta \vdash h\{r.f \mapsto v'\} : \Gamma''$. We then notice that in each of the three cases of the lemma we have $\Gamma'' * r \triangleright v : T \triangleleft \Gamma_1\{r.f \mapsto T'\} * r$:

1. If v is an object identifier or channel endpoint then $\Gamma'' = \Gamma_1\{r.f \mapsto T'\}, v : T$. We use T-REF or T-CHAN.
2. If v is not an object or channel and T is not a link type, then v is either null, an access point name or a label. We use T-NUL, T-NAME or T-LABEL.
3. If $T = \text{link } f'$ then $\Gamma_1(r.f') = \langle l : S_l \rangle_{l \in E}$ with $v \in E$ and we have $\Gamma'' = \Gamma_1\{r.f \mapsto T'\}\{r.f' \mapsto S_v\}$. We use T-LABEL, T-VARS and T-SUBENV.

Finally we conclude with T-STATE.

- $e = \text{return } v$. Then the expression reduces by R-RETURN. The initial derivation is as follows:

$$(1) \frac{\frac{\dots}{\Gamma * r.f \triangleright v : T_1 \triangleleft \Gamma_1 * r.f} \quad \Gamma_1(r.f) = C[F] \quad F \vdash C : S \text{ (b)}}{\Gamma * r.f \triangleright \text{return } v : T \triangleleft \Gamma_1\{r.f \mapsto S\} * r} \text{ (T-RETURN)}$$

with also $\Theta \vdash h : \Gamma$ (a). We distinguish cases depending on what rule (1) is:

- If (1) is T-NUL, T-NAME or T-LABEL then $\Gamma = \Gamma_1$, and if it is T-REF or T-CHAN then $\Gamma = \Gamma_1, v : T_1$. In both cases we have $\Gamma(r.f) = \Gamma_1(r.f)$ and $T_1 = T$. From (a) and (b) we deduce $\Theta \vdash h : \Gamma\{r.f \mapsto S\}$ using the closing lemma (Lemma 7.8). We then use T-NUL, T-NAME, T-LABEL, T-CHAN or T-REF, as appropriate, to get $\Gamma\{r.f \mapsto S\} * r \triangleright v : T_1 \triangleleft \Gamma_1\{r.f \mapsto S\} * r$, and we conclude with T-STATE.
- (1) cannot be T-VARS because T-RETURN forbids that T_1 be of the form $\text{link } f'$.
- If (1) is T-VARF, then $T_1 = \text{linkthis}$ and $T = \text{link } f$. Furthermore, v is a label, $F = \langle v : F' \rangle$ with F' not a variant, and $\Gamma = \Gamma_1\{r.f \mapsto C[F']\}$. (b) then implies that S is of the form $\langle l : S_l \rangle_{l \in E}$ with $v \in E$ and $F' \vdash C : S_v$. Note that because F' is not a variant, S_v must be a branch. Now, from that judgement and (a), we use the closing lemma to get $\Theta \vdash h : \Gamma\{r.f \mapsto S_v\}$. Let $\Gamma'' = \Gamma\{r.f \mapsto S_v\}$. Since Γ only differs from Γ_1 by the type of $r.f$, it is also the case of Γ'' , and as $\langle v : S_v \rangle$ is a subtype of S , we have $\Gamma''\{r.f \mapsto \langle v : S_v \rangle\} <: \Gamma_1\{r.f \mapsto S\}$. From all this, we build the following derivation:

$$\begin{array}{c}
\text{(T-LABEL)} \frac{v \text{ is a label}}{\Gamma'' * r \triangleright v : \{v\} \triangleleft \Gamma'' * r} \quad S_v \text{ branch} \\
\text{(T-VARS)} \frac{}{\Gamma'' * r \triangleright v : T \triangleleft \Gamma'' \{r.f \mapsto \langle v : S_v \rangle\} * r} \\
\text{(T-SUBENV)} \frac{}{\Gamma'' * r \triangleright v : T \triangleleft \Gamma' * r} \\
\text{(T-STATE)} \frac{\Theta \vdash h : \Gamma \{r.f \mapsto S_v\}}{\Theta; \Gamma'' \triangleright (h * r; v) : T \triangleleft \Gamma' * r}
\end{array}$$

- $e = \text{spawn } C.m(v)$. The initial derivation involves T-SPAWN, and v is null. The premise that the method exists implies that the state can reduce by R-SPAWN, which corresponds to a $C.m()$ transition. The new derivation is obtained replacing T-SPAWN with T-NULL.
- $e = f.m(v)$. The initial derivation is as follows, with $m = m_j$ and $j \in I$:

$$\begin{array}{c}
(1) \frac{\dots}{\Gamma * r \triangleright v : T' \triangleleft \Gamma_1 * r} \\
\text{(T-SUB)} \frac{}{\Gamma * r \triangleright v : T'_j \triangleleft \Gamma_1 * r} \quad \Gamma_1(r.f) = \{T_i \ m_i(T'_i) : S_i\}_{i \in I} \text{ (b)} \\
\text{(T-CALL)} \frac{}{\Gamma * r \triangleright f.m_j(v) : T \triangleleft \Gamma_1 \{r.f \mapsto S_j\} * r}
\end{array}$$

and we also have $\Theta \vdash h : \Gamma$ (a). T is obtained from T_j as specified in T-CALL, i.e. replacing `linkthis` with `link f` if necessary. Let $S = \{T_i \ m_i(T'_i) : S_i\}_{i \in I}$. First note that T'_j is a part of a method signature and that only a restricted set of types is allowed there: it cannot be of the form `link f'`. Furthermore, (1) cannot be T-VARF because of (b), thus T' is not `linkthis` either. Indeed, if $\Gamma_1(r)$ were a variant, $\Gamma_1(r.f)$ would not be defined. Therefore (1) is either T-NULL, T-LABEL, T-CHAN, T-NAME or T-REF and in all cases we have $\Gamma(r.f) = \Gamma_1(r.f)$. As it is a session type, it implies because of (a) that $h(r).f$ exists and is either an object identifier, an access point name or a channel endpoint. We distinguish these three cases:

- $h(r).f$ is an object identifier o . We use (a) and the opening lemma (Lemma 7.7) to get a field typing $C[F]$ such that $\Theta \vdash h : \Gamma \{r.f \mapsto C[F]\}$ and $F \vdash C : S$. This last judgement implies, by definition, that F is not a variant; that, among others, method m_j appears in the declaration of class C ; and that, if e_j is its body and x its parameter, we have $x : T'_j, \text{this} : C[F] * \text{this} \triangleright e_j : T_j \triangleleft \text{this} : C[F_j] * \text{this}$ and $F_j \vdash C : S_j$. The fact that the method is declared implies $(h * r; e) \longrightarrow (h * r.f; \text{return } e_j \{v/x\})$; we now have to type this resulting state. For this, we apply the substitution lemma (Lemma 7.10) to the typing judgement for e_j , using $\Gamma_1 \{r.f \mapsto C[F]\}$ as the Γ of the lemma and $r.f$ as the r of the lemma. The first case of the lemma corresponds to (1) being T-NULL, T-LABEL or T-NAME; the second one corresponds to (1) being T-REF or T-CHAN. In both cases, the resulting judgement is:

$$\Gamma \{r.f \mapsto C[F]\} * r.f \triangleright e_j \{v/x\} : T_j \triangleleft \Gamma_1 \{r.f \mapsto C[F_j]\} * r.f$$

Indeed, the difference between Γ and Γ_1 depends on (1) in the same way as the lemma's result. From this and $F_j \vdash C : S_j$ we can now apply T-RETURN and get:

$$\Gamma \{r.f \mapsto C[F]\} * r.f \triangleright \text{return } e_j \{v/x\} : T \triangleleft \Gamma_1 \{r.f \mapsto S_j\} * r$$

where T is the same as in the initial derivation. We then conclude, using the heap typing that was provided by the opening lemma, with T-STATE.

- $h(r).f$ is an access point name n . Then $\Gamma(r.f)$ must come, in the derivation of $\Theta \vdash h : \Gamma$, from T-NAME, which implies that n is declared, that m_j is either `accept` or `request`, and that $T_j \triangleright \llbracket \Sigma \rrbracket$ where Σ is either the declared type or its dual depending on which one m_j is. All this implies that the state does a $n[c^p]$ transition where c is fresh and p depends, again, on m_j , and that $\Theta \xrightarrow{n[c^p]} \Theta, c^p : \Sigma$. The resulting state is typed using $\Gamma'' = \Gamma, c^p : \llbracket \Sigma \rrbracket$ and T-CHAN.
- $h(r).f$ is a channel endpoint c^p . Then $\Theta \vdash h : \Gamma$ implies that $c^p \in \text{dom}(\Theta)$ and $S \triangleright \llbracket \Theta(c^p) \rrbracket$. Hence m_j is either `send` or `receive`. We distinguish the two cases. In the first case, the fact that S contains `send` implies that $\Theta(c^p)$ is either of the form $! [T'_j].\Sigma$ with $T'_j \triangleleft T_j$ or $\oplus \{l : \Sigma_l\}_{l \in E}$ and then $T'_j = \{v\}$ and $v \in E$. If v is not an object identifier then the state does a $c^p ! [v]$ transition. We can see that in both cases (send

and select), Θ is able to follow that transition and evolves in such a way that $\Theta' \vdash h : \Gamma'$ holds: the session type of c^p is advanced and if v was a channel it is removed from the environment, which corresponds to the difference between Γ and Γ' , thus it suffices to change the instance of T-EMPTY at the root of the derivation leading to (a) to get this new typing. Then the new state is typed using T-NUL and T-STATE. If v is an object identifier, then (1) is T-REF and thus $v \in \text{dom}(\Gamma)$, which implies (using (a)) that v is a root of h , so the state does a $c^p ! [h \downarrow v]$ transition. We use the splitting lemma (Lemma 7.4) to see that Θ is able to follow this transition and yields a Θ' such that we have $\Theta' \vdash h \uparrow v : \Gamma'$. We can then again conclude using T-NUL and T-STATE.

In the case where m_j is receive, the state can straightforwardly do a transition, which will be a receive on channel c^p , however the transition label is not completely determined by the original state as we do not know what will be received. So we have to prove type preservation in all cases where the transition label λ is such that $\Theta \xrightarrow{\lambda} \Theta'$ for some Θ' . If λ is of the form $c^p ? [v']$, then this hypothesis tells us that $\Theta(c^p)$ is either of the form $? [T_0] . \Sigma$, and then v' must be a literal value of type T_0 or a channel endpoint which gets added to the environment with a type smaller than T_0 , or of the form $\& \{l : \Sigma_l\}_{l \in E}$, and then $v' \in E$. In the first case we must have $T_0 <: T_j$, thus the resulting expression, which is v' , can be typed using the appropriate literal value rule, or T-CHAN, and subsumption. In the second one, $T_j = \text{linkthis}$ so that $T = \text{link } f$; the resulting expression can be typed using T-LABEL and T-VARS. As for the new initial environment, it is obtained, as in the case of send, by replacing the instance of T-EMPTY at the top of the derivation for (a) with one using Θ' instead of Θ , so that v' gets added to the initial environment if it is a channel and that the session type of $r.f$ is correctly advanced, meaning, in the case of a branch, that it is advanced to the particular session corresponding to v' , the variant type being reconstituted in the final environment by T-VARS. Finally, if λ is of the form $c^p ? [h']$, then we have $\Theta' = \Theta + \Theta''$ with $\Theta'' \vdash h' : o : T_j$, where o is the only root of h' . The merging lemma (Lemma 7.5) gives us a typing for the new heap and, as in the other cases, advancing the session type of c^p yields a session type change in $r.f$, corresponding to the difference between Γ and Γ' . We conclude using T-REF and T-STATE. \square

The following two lemmas will allow us to deduce from this theorem the proof of subject reduction for configurations.

Lemma 7.18 *If $\Theta \vdash s$ and $s \equiv s'$ then $\Theta \vdash s'$.*

Proof. By induction on the derivation of $s \equiv s'$.

Lemma 7.19 *If $s \longrightarrow s'$, then either:*

1. $s \equiv (\nu \vec{c}) ((h * r; e) \parallel s'')$,
 $s' \equiv (\nu \vec{c}) ((h' * r'; e') \parallel s'')$
and $(h * r; e) \xrightarrow{\tau} (h' * r'; e')$, or
2. $s \equiv (\nu \vec{c}) ((h_1 * r_1; e_1) \parallel (h_2 * r_2; e_2) \parallel s'')$,
 $s' \equiv (\nu \vec{c}) (\nu d) ((h_1 * r_1; e'_1) \parallel (h_2 * r_2; e'_2) \parallel s'')$,
 $(h_1 * r_1; e_1) \xrightarrow{n[d^+]} (h_1 * r_1; e'_1)$ and $(h_2 * r_2; e_2) \xrightarrow{n[d^-]} (h_2 * r_2; e'_2)$, or
3. $s \equiv (\nu \vec{c}) ((h_1 * r_1; e_1) \parallel (h_2 * r_2; e_2) \parallel s'')$,
 $s' \equiv (\nu \vec{c}) ((h_1 * r_1; e'_1) \parallel (h_2 * r_2; e'_2) \parallel s'')$,
 $(h_1 * r_1; e_1) \xrightarrow{c^p ! [v]} (h_1 * r_1; e'_1)$ and $(h_2 * r_2; e_2) \xrightarrow{c^p ? [v]} (h_2 * r_2; e'_2)$, or
4. $s \equiv (\nu \vec{c}) ((h_1 * r_1; e_1) \parallel (h_2 * r_2; e_2) \parallel s'')$,
 $s' \equiv (\nu \vec{c}) ((h'_1 * r_1; e'_1) \parallel (h'_2 * r_2; e'_2) \parallel s'')$,
 $(h_1 * r_1; e_1) \xrightarrow{c^p ! [h']} (h'_1 * r_1; e'_1)$ and $(h_2 * r_2; e_2) \xrightarrow{c^p ? [\varphi(h')]} (h'_2 * r_2; e'_2)$
with $h' = h_1 \downarrow o$, $h'_1 = h_1 \uparrow o$, and $h'_2 = h_2 + \varphi(h')$, or

5. $s \equiv (\nu \vec{c}) ((h * r; e) \parallel s'')$,
 $s' \equiv (\nu \vec{c}) ((h * r; e') \parallel (o = C[\vec{f} = \overrightarrow{\text{null}}] * o; e'' \{\text{null}/x\}) \parallel s'')$
and $(h * r; e) \xrightarrow{C.m()}(h * r; e')$, where $C.\text{fields} = \vec{f}$, o is fresh and $m(x) \{e''\} \in C$.

Proof. This is nothing more than a reformulation of the reduction rules in terms of labelled transitions: the derivation for $s \longrightarrow s'$ can contain any number of instances of R-PAR, R-STR or R-NEWCHAN but must have one of the other rules at the top. It is straightforward to see that depending on that top rule we are in one of the five cases listed: (1) for any of the single-thread rules in Figure 7, (2) for R-INIT, (3) for R-COMBASE, (4) for R-COMOBJ, and (5) for R-SPAWN.

We can now prove Theorem 7.13. Proof. [(Theorem 7.13)] Because of Lemma 7.18 we only need to look at the different cases described in Lemma 7.19.

In cases (1) and (5), the initial derivation is as follows:

$$\begin{array}{c} \text{(T-THREAD)} \frac{\Theta_1; \Gamma \triangleright (h * r; e) : T \triangleleft \Gamma' * r''}{\text{(T-PAR)} \frac{\Theta_1 \vdash (h * r; e) \quad \Theta_2 \vdash s''}{\text{(T-NEWCHAN)} \frac{\Theta_1 + \Theta_2 \vdash (h * r; e) \parallel s''}{\vdash s}}} \end{array}$$

In case (1), Theorem 7.13 gives us $\Theta_1; \Gamma'' \triangleright (h' * r'; e') : T \triangleleft \Gamma' * r''$; from there the final derivation is the same.

In case (5), the theorem gives us the same result, but the final derivation is more complicated as there is one more parallel component. The $C.m()$ transition tells us that e must be of the form $\mathcal{E}[\text{spawn } C.m(v)]$. From Lemma 7.11, this implies that the subexpression $\text{spawn } C.m(v)$ is typable, which must be a consequence of T-SPAWN, implying that m appears in the initial session type S of C with a Null argument type. As, by hypothesis, the declaration of class C is well-typed, this implies (from T-CLASS) $x : \text{Null}, \text{this} : C[\text{Null } \vec{f}] * \text{this} \triangleright e'' : T \triangleleft \text{this} : C[F] * \text{this}$. We apply the substitution lemma (7.10) to this judgement to replace this with o and x with null , and we build the heap typing $\emptyset \vdash o = C[\vec{f} = \overrightarrow{\text{null}}] : o : C[\text{Null } \vec{f}]$ from T-EMPTY and T-HADD. This gives a typing for the new thread, with an empty Θ , using T-STATE and T-THREAD and we can conclude with T-PAR.

In cases (2), (3), and (4), the initial derivation is:

$$\begin{array}{c} \frac{\Theta_1; \Gamma_1 \triangleright (h_1 * r_1; e_1) : T_1 \triangleleft \Gamma'_1 * r'_1 \quad \Theta_2; \Gamma_2 \triangleright (h_2 * r_2; e_2) : T_2 \triangleleft \Gamma'_2 * r'_2}{\text{(T-PAR)} \frac{\Theta_1 \vdash (h_1 * r_1; e_1) \quad \Theta_2 \vdash (h_2 * r_2; e_2)}{\text{(T-PAR)} \frac{\Theta_1 + \Theta_2 \vdash (h_1 * r_1; e_1) \parallel (h_2 * r_2; e_2)}{\text{(T-NEWCHAN)} \frac{\Theta_1 + \Theta_2 + \Theta \vdash (h_1 * r_1; e_1) \parallel (h_2 * r_2; e_2) \parallel s''}{\vdash s}}} \quad \Theta \vdash s'' \end{array}$$

Furthermore, we can deduce from the transition labels that the expressions in the two topmost premises are of the form $\mathcal{E}_1[f_1.m_1(v_1)]$ and $\mathcal{E}_2[f_2.m_2(v_2)]$ with $h_1(r_1).f_1$ and $h_2(r_2).f_2$ being, in case (2), n , and in cases (3) and (4), respectively c^p and $c^{\bar{p}}$. These two topmost premises must come from T-STATE, which implies $\Theta_1 \vdash h_1 : \Gamma_1$ and $\Theta_2 \vdash h_2 : \Gamma_2$, from which we deduce, in case (2), that n is a declared access point name and in cases (3) and (4) that $\llbracket \Theta_1(c^p) \rrbracket <: \Gamma_1(r_1.f_1)$ and $\llbracket \Theta_2(c^{\bar{p}}) \rrbracket <: \Gamma_2(r_2.f_2)$. We use Theorem 7.13 on these two topmost premises and distinguish cases.

In case (2), Θ_1 and Θ_2 make transitions which introduce two dual types for d^+ and d^- , which are fresh so that the disjoint unions are still possible, and we just need to add an additional step of T-NEWCHAN before the last one.

In cases (3) and (4), we first remark that because T-NEWCHAN in the derivation leads to an empty environment, c must be one of the channels in $(\nu \vec{c})$ and we must have $\Theta_1(c^p) = \Sigma$ and $\Theta_2(c^{\bar{p}}) = \bar{\Sigma}$ for some Σ . Then we use Lemma 7.11 to get a typing judgement for the method call subexpression on the sending side (thread 1). This judgement has Γ_1 as an initial typing environment and comes from T-CALL; as we have $\Sigma <: \Gamma_1(r_1.f_1)$, this implies that Σ is either of the form $! [T]. \Sigma'$ with v (in case (3)) or o (in case (4)) of type T , or (only in case (3)) of the form $\oplus \{l : \Sigma_l\}_{l \in E}$ with $v \in E$. The simplest case is (3): then this typing information, together with the duality of the two endpoint types, shows that Θ_2 follows the transition with the new type of $c^{\bar{p}}$ still dual to the new type of c^p . In the case where v is a channel endpoint, its typing goes from Θ_1 to Θ_2 but stays the same, so that it is unchanged in the sum environment yielded by T-PAR. Thus we can still apply T-NEWCHAN.

Case (4) is similar but, additionally, a renaming function is applied to the transmitted heap. We use Lemma 7.6 to see that the type of its only root, which is all we need, stays the same, so that again Θ_2 can follow the transition. We also have that a whole part of the channel environment can go from Θ_1 to Θ_2 but the effect is the same as with just one channel: it does not affect the sum environment resulting from T-PAR. So again we can still apply T-NEWCHAN. \square

7.3 Type safety

We now have the following safety result, ensuring not only race-freedom (no two sends or receives in parallel on the same endpoint of a channel) but also that the communication is successful.

Theorem 7.20 (No Communication Errors) *Let*

$$s \equiv (\nu \vec{c})(s' \parallel (h * r; \mathcal{E}[r.f.m(v)]) \parallel (h' * r'; \mathcal{E}[r'.f'.m'(v')]))$$

and suppose that $\vdash s$ holds. If $h(r).f = c^p$ and $h'(r').f' = c^q$ then:

1. $q = \bar{p}$,
2. *channel c does not occur in s' , and*
3. *there exists s'' such that $s \longrightarrow s''$.*

As the statement is true in particular when s' is empty, it implies that communication between the two threads is possible. Proof. This is an essentially straightforward consequence of $\vdash s$. The typing derivation is similar to the one shown for cases 2/3/4 in Theorem 7.13 above; the two top premises must be consequences of T-STATE and the heap typing necessary to apply this rule implies, respectively, $\Gamma_1(r.f) :> \llbracket \Theta_1(c^p) \rrbracket$ and $\Gamma_2(r'.f') :> \llbracket \Theta_2(c^q) \rrbracket$. Because of the disjoint unions in T-PAR, $c^p \in \text{dom}(\Theta_1)$ and $c^q \in \text{dom}(\Theta_2)$ immediately imply (1) and (2); (3) is then a consequence of the duality constraint imposed by T-NEWCHAN: looking at the translations of dual channel types, and because the method call subexpressions must be typed by T-CALL, if m is *send* then m' must be *receive* and vice-versa.

This theorem, together with the progress aspect of Theorem 7.16, restricts the set of blocked configurations to the following: if $\vdash s$ and $s \not\rightarrow$, then all parallel components in s are either terminated (reduced to values), unmatched *accepts* or *requests*, or method calls on *pairwise distinct* channels — this last case corresponding to a deadlock.

7.4 Conformance

We now have the technical material necessary to prove Theorem 3.31 (conformance). Note that we do not formally extend this result to the distributed setting, as stating a similar property in that case would require more complex definitions describing, among other things, how call traces are moved around between threads; however we can see informally that, because objects keep their content and session type when transmitted, all necessary information is kept such that we still have a conformance property.

Proof. We first prove, by strong induction on n , a slightly different result, namely the following: for each i there is Γ_i such that $\Gamma_i \triangleright (h_i * r_i; e_i) : T \triangleleft \Gamma' * r'$ and tr_i is consistent with Γ_i .

We suppose that this property is true for any reduction sequence of length n or less whose initial state satisfies the hypotheses and prove that it is true also for length $n + 1$. The base case $n = 1$ is trivial.

If the n th reduction step $(h_n * r_n; e_n) \longrightarrow (h_{n+1} * r_{n+1}; e_{n+1})$ does not originate from R-RETURN, we use the induction hypothesis on the beginning of the sequence; we refer to the cases in the proof of Theorem 7.16 to show that the Γ_{n+1} it allows to construct from Γ_n indeed is consistent with tr_{n+1} . Because we are only interested in Γ_{n+1} and not Γ' , in most cases we can use Lemmas 7.11 and 7.12 to ignore any context \mathcal{E} and proceed as if the reduction is exactly an instance of its original rule.

If the rule is R-SEQ, R-SWITCH or R-SWAP then $tr_{n+1} = tr_n$.

If the rule is R-SEQ or R-SWITCH then the proof of Theorem 7.16 shows that we can choose $\Gamma_{n+1} = \Gamma_n$, so there is nothing more to prove.

If the rule is R-SWAP then the proof of Theorem 7.16 indicates that Γ_{n+1} (called Γ'' in subject reduction) can be defined using Lemma 7.9 from the Γ''' (called Γ_1 in subject reduction) obtained after typing v' , the value that gets swapped into the field. First of all note that most objects, notably all those which are not v' and not in a field of r , have the same type and position in the heap in Γ_{n+1} as they have in Γ . For all them the result is straightforward: we only concentrate on those objects that move or change type. Depending on the nature of T and T' (object, link, or base type), there may be one or two of them. Recall that neither type can be `linkthis` as else the expression would not be typable. We distinguish cases separately for T and T' , knowing that any combination is possible (except both linking to the same field). Cases for T' :

- If T' is an object type (thus v' is an object name o'), then $\Gamma_{n+1}(r.f) = \Gamma_n(o')$ (the rule used for v' is T-REF). We also have $tr_{n+1}(h_{n+1}(r.f)) = tr_{n+1}(o') = tr_n(o')$, so tr_{n+1} is indeed consistent with Γ_{n+1} with respect to reference $r.f$.
- If T' is `link f'`, the rule used for v' is T-VARS, and $\Gamma_{n+1}(r.f') = \langle v' : S_{v'} \rangle$. We have $\Gamma_{n+1}(r.f) = \text{link } f'$ and $h_{n+1}(r.f) = v'$, hence the actual session type of $r.f'$ in h_{n+1} according to Γ_{n+1} is $S_{v'}$. Thus consistency is preserved for $r.f'$.

Cases for T (corresponding respectively to cases 1 and 3 of Lemma 7.9):

- If T is an object type (thus $h_n(r.f)$ is an object name o), then Γ_{n+1} contains a new entry for o , with type $\Gamma_n(r.f)$. Consistency for this new entry comes from consistency for $r.f$ at the previous step.
- If T is `link f''`, then $\Gamma_n(r.f') = \langle l : S_l \rangle_{l \in E}$ and $h_n(r.f) = l_0$ is in E . Thus the actual session type of $r.f''$ in h_n according to Γ_n is S_{l_0} . Lemma 7.9 also gives us $\Gamma_{n+1}(r.f') = S_{l_0}$, hence the actual session type of $r.f''$ has not changed, and consistency is preserved.

If the rule is R-NEW then the proof of Theorem 7.16 shows that a suitable Γ_{n+1} is of the form $\Gamma_n, o : C.\text{session}$ where o is the fresh object name introduced by the reduction. Definition 3.26 states that tr_{n+1} extends tr_n by assigning an empty call trace to o ; clearly tr_{n+1} is consistent with Γ_{n+1} .

If the rule is R-CALL then the proof of Theorem 7.16 shows that a suitable Γ_{n+1} is Γ_n with the type of $r.f$ replaced by a type which is not a session. So there is no consistency requirement in Γ_{n+1} for $r.f$, and every other reference is given the same call trace by tr_{n+1} as by tr_n . Therefore tr_{n+1} is consistent with Γ_{n+1} .

Now if the n th step originates from R-RETURN, we reason slightly differently. We know by hypothesis that r_1 is a prefix of r_{n+1} . Furthermore, since the n th step is R-RETURN, r_n is of the form $r_{n+1}.f$. Reduction rules can only alter the current object by removing or adding one single field reference at once, therefore there must be a previous reduction step in the sequence, say the i th, that last went from r_{n+1} to $r_{n+1}.f$. That is, we chose i such that $r_{n+1}.f$ is a prefix of all r_j for j between $i+1$ and n and that $r_i = r_{n+1}$. That step must originate from R-CALL as it is the only rule which adds a field specification to the current object. Thus, it is of the form $(h_i * r_{n+1}; \mathcal{E}(f.m(v')))) \longrightarrow (h_{i+1} * r_{n+1}.f; \mathcal{E}(\text{return } e))$, where e is the method body of m with the parameter substituted. Then it is straightforward to see that the whole reduction sequence from $i+1$ to n consists of reductions of e inside the context $\mathcal{E}(\text{return } [_])$.

We first use the induction hypothesis on the first part of the reduction (1 to i) so as to get judgments up to $\Gamma_i \triangleright (h_i * r_{n+1}; \mathcal{E}(f.m(v')))) : T \triangleleft \Gamma' * r'$. We then use Lemma 7.11 to get $\Gamma_i \triangleright (h_i * r_{n+1}; f.m(v')) : T' \triangleleft \Gamma'' * r''$ and note that this judgment must come from T-CALL, which implies that $r'' = r_{n+1}$, that $\Gamma_i(r_{n+1}.f)$ is of the form $\{T' m(\dots) : S, \dots\}$ and that $\Gamma''(r_{n+1}.f) = S$. Furthermore, T' is either a base type if S is a branch or `link f` if it is a variant. We know that tr_i is consistent with Γ_i , therefore we have $\text{class}(o).\text{session} \xrightarrow{tr_i(o)}^* \{T' m(\dots) : S, \dots\} \xrightarrow{m} S$.

We now use the induction hypothesis again on the reduction sequence from i to n for this particular call subexpression, recalling that i has been defined such that the hypothesis on the current object is indeed satisfied by this sequence. We can also use Lemma 7.12 at each step in order to lift the judgements thus obtained to the whole expression. To summarise, this means that for any j between $i+1$ and n we have: $e_j = \mathcal{E}(\text{return } e'_j)$ for some e'_j , $\Gamma_j \triangleright (h_j * r_j; \text{return } e'_j) : T' \triangleleft \Gamma'' * r_{n+1}$ and $\Gamma_j \triangleright (h_j * r_j; e_j) : T \triangleleft \Gamma' * r'$, and that tr_j is consistent with Γ_j .

$$\begin{aligned}
\mathcal{W}(C) &= \mathcal{A}_C(C.\text{session}, C.\text{fields}, \emptyset) \\
&\quad \text{if for every req } F \text{ ens } F' \text{ for } T' \text{ m}(T \ x) \ \{e\} \in C \\
&\quad \quad F' \neq \langle _ \rangle \text{ and } \mathcal{B}_C(e, F, x : T) = (T', F', _) \\
\\
\mathcal{A}_C(S, F, \Delta) &= \Delta \text{ if } (F, S) \in \Delta \\
\mathcal{A}_C(\mu X.S, F, \Delta) &= \mathcal{A}_C(S\{\mu X.S/X\}, F, \Delta \cup \{(F, \mu X.S)\}) \\
\mathcal{A}_C(\{T_i \ m_i(U_i) : S_i\}_{1 \leq i \leq n}, F, \Delta_0) &= \Delta_n \\
&\quad \text{where for } i = 1 \text{ to } n \\
&\quad \quad \text{let } (T'_i, F'_i, _) = \mathcal{B}_C(e_i, F, x_i : U_i) \text{ where } m_i(x_i) \ \{e_i\} \in C \\
&\quad \quad \text{if } T'_i <: T_i \text{ then let } \Delta_i = \mathcal{A}_C(S_i, F'_i, \Delta_{i-1}) \\
&\quad \quad \text{else if } T'_i \text{ is an enumeration } E \text{ and } T_i = \text{linkthis} \\
&\quad \quad \quad \text{then let } \Delta_i = \mathcal{A}_C(S_i, \langle l : F'_i \rangle_{l \in E}, \Delta_{i-1}) \\
&\quad \quad \text{else if } T'_i = \text{linkthis} \text{ and } T_i \text{ is an enumeration } E \text{ and } F'_i = \langle l : F_l \rangle_{l \in E'} \text{ and } E' \subseteq E \\
&\quad \quad \quad \text{then let } \Delta_i = \mathcal{A}_C(S_i, \bigvee_{l \in E'} F_l, \Delta_{i-1}) \\
\mathcal{A}_C(\langle l : S_l \rangle_{l \in E}, \langle l : F_l \rangle_{l \in E'}, \Delta_0) &= \Delta_n \\
&\quad \text{where } E' = \{l_1 \dots l_n\} \subseteq E \text{ and for } i = 1 \text{ to } n, \Delta_i = \mathcal{A}_C(S_{l_i}, F_{l_i}, \Delta_{i-1})
\end{aligned}$$

Combining variants

$$\begin{aligned}
\{T_i f_i\}_{i \in I} \vee \{T'_i f_i\}_{i \in I} &= \{(T_i \vee T'_i) f_i\}_{i \in I} \\
\langle l : F_l \rangle_{l \in I} \vee \langle l : F'_l \rangle_{l \in J} &= \langle l : F''_l \rangle_{l \in I \cup J} \\
&\quad \text{where } F''_l = F_l \vee F'_l \text{ if } l \in I \cap J, F_l \text{ if } l \notin J, F'_l \text{ if } l \notin I
\end{aligned}$$

Figure 27: Typechecking: algorithms \mathcal{W} and \mathcal{A} .

For the last reduction step, R-RETURN, the proof of Theorem 7.16 tells us that we can choose a Γ_{n+1} which is identical to Γ_n except for the type of $r_{n+1}.f$, and as the call trace for other references is not modified, consistency is preserved for them. For $r_{n+1}.f$ we have to look back at the initial subexpression on step i . First note that R-SWAP can only act on a field of the current object, therefore since $r_{n+1}.f$ is a prefix of the current object during the whole subsequence, its content cannot change and is the same object o throughout. Similarly, there is no other R-CALL or R-RETURN acting on that particular object, hence $tr_n(o) = tr_{i+1}(o) = tr_i(o)m$. We saw above that this call trace leads the initial session of o to S . Then the judgement for the final subexpression, at step $n+1$, is of the form $\Gamma_{n+1} \triangleright (h_{n+1} * r_{n+1}; v) : T' \triangleleft \Gamma'' * r_{n+1}$. There are two cases, as in the proof of Theorem 7.16. If T' is a base type then S is a branch and it is possible to decide that $\Gamma_{n+1}(r_{n+1}.f)$ is equal to S . In that case the call trace either does not change or has a label appended, but as S is a branch it can do a transition to itself with any label, therefore $tr_{n+1}(o)$ is consistent with $\Gamma_{n+1}(r_{n+1}.f)$ in both cases. If T' is link f , then v is a label, S is a variant $\langle l : S_l \rangle_{l \in E}$ and $\Gamma_{n+1}(r_{n+1}.f)$ can be chosen equal to S_v . We have $tr_{n+1}(o) = tr_n(o)v$ and $S \xrightarrow{v} S_v$, so consistency is preserved.

This completes the inductive proof that for every step i in the reduction sequence there is Γ_i such that $\Gamma_i \triangleright (h_i * r_i; e_i) : T \triangleleft \Gamma' * r'$ and tr_i is consistent with Γ_i . This fact obviously implies that tr_i is valid for all the objects which have a session type in Γ_i ; we now argue that it is also the case for the other objects, namely those which either are not at all in Γ_i or do not have a session type. We know by hypothesis that it is the case for tr_1 and show by a very simple induction that it cannot change from i to $i+1$. The i th step can only change the call trace for an object o if it originates from R-CALL or R-RETURN concerning that object. R-CALL can only occur if the reducible part of the expression is indeed a method call on a field which contains o , and that is only typable if Γ_i contains a session type for that field which is a branch containing the method, and thus allows the appropriate transition: therefore validity of the call trace for o is preserved in that case. R-RETURN on the other hand can only occur if the reducible part of the expression is a return and if the current object is (the address of) o , and we saw that in that case the Γ_{i+1} constructed in our proof contains a session type for o , so this case is covered by the consistency result.

$\mathcal{B}_C(\text{null}, F, V) = (\text{Null}, F, V)$
 $\mathcal{B}_C(n, F, V) = (\llbracket n.\text{protocol} \rrbracket, F, V)$
 $\mathcal{B}_C(x, F, y : T) = (T, F, V)$ if $x = y$, where $V = \emptyset$ if T is linear or $y : T$ otherwise
 $\mathcal{B}_C(f \leftrightarrow e, F, V) = (U, F'', V')$
 where $(T, F', V') = \mathcal{B}_C(e, F, V)$ and $F'(f)$ is not a variant and
 if $T = \text{linkthis}$ then $F' = \langle l : F_l \rangle_{l \in E}$ and $U = (\bigvee_{l \in E} F_l)(f)$ and $F'' = (\bigvee_{l \in E} F_l)\{f \mapsto E\}$
 else $U = F'(f)$ and $F'' = F'\{f \mapsto T\}$
 $\mathcal{B}_C(l, F, V) = (\text{linkthis}, \langle l : F \rangle, V)$
 $\mathcal{B}_C(\text{new } C'(), F, V) = (C'.\text{session}, F, V)$
 $\mathcal{B}_C(f.m_j(e), F, V) = (T, F'', V')$
 where $(T', F', V') = \mathcal{B}_C(e, F, V)$ and
 if $T' = \text{linkthis}$ then $F' = \langle l : F_l \rangle_{l \in E}$ and $(\bigvee_{l \in E} F_l)(f) = \{T_i \ m_i(T'_i) : S_i\}_{i \in I}$ and $j \in I$
 and T'_j is an enumeration E' and $E \subseteq E'$ and $F'' = (\bigvee_{l \in E} F_l)\{f \mapsto S'_j\}$ and
 $T = \text{link } f$ if $T_j = \text{linkthis}$, $T = T_j$ otherwise
 else $F'(f) = \{T_i \ m_i(T'_i) : S_i\}_{i \in I}$ and $j \in I$ and $T' <: T'_j$ and
 $F'' = F'\{f \mapsto S'_j\}$ and $T = \text{link } f$ if $T_j = \text{linkthis}$, $T = T_j$ otherwise
 $\mathcal{B}_C(m(e), F, V) = (T', F''', V')$
 where $(T, F', V') = \mathcal{B}_C(e, F, V)$ and $\text{req } F'' \text{ ens } F''$ for $T' \ m(T'' \ x) \ \{e\} \in C$ and
 if $T = \text{linkthis}$ then $F' = \langle l : F_l \rangle_{l \in E}$ and T'' is an enumeration E' and
 $E \subseteq E'$ and $\bigvee_{l \in E} F_l <: F''$
 else $T <: T''$ and $F' <: F''$
 $\mathcal{B}_C(\text{switch } (e) \ \{l : e_l\}_{l \in E}, F, V) = (T, \bigvee_{l \in E} F'_l, V'')$
 where $(U, F', V') = \mathcal{B}_C(e, F, V)$ and
 if $U = E'$ then $E' \subseteq E$ and $\forall l \in E'. (T, F'_l, V'') = \mathcal{B}_C(e_l, F', V')$
 else if $U = \text{linkthis}$ then $F' = \langle m : G_m \rangle_{m \in E'}$ and $E' \subseteq E$ and
 $\forall l \in E'. (T, F'_l, V'') = \mathcal{B}_C(e_l, \bigvee_{m \in E'} G_m, V')$
 else if $U = \text{link } f$ then
 $F'(f) = \langle l : S_l \rangle_{l \in E'}$ and $E' \subseteq E$ and $\forall l \in E'. (T, F'_l, V'') = \mathcal{B}_C(e_l, F'\{f \mapsto S_l\}, V')$
 $\mathcal{B}_C(\text{while } (e) \ \{e'\}, F, V) = (\text{Null}, F'', V')$
 where $(U, F', V') = \mathcal{B}_C(e, F, V)$ and
 if $U = E'$ then $E' \subseteq \{\text{True}, \text{False}\}$ and $\mathcal{B}_C(e', F', V') = (\text{Null}, F, V)$ and $F'' = F'$
 else if $U = \text{linkthis}$ then $F' = \langle l : F_l \rangle_{l \in E}$ and $E \subseteq \{\text{True}, \text{False}\}$ and
 $\mathcal{B}_C(e', \bigvee_{l \in E} F_l, V') = (\text{Null}, F, V)$ and $F'' = \bigvee_{l \in E} F_l$
 else if $U = \text{link } f$ then $F'(f) = \langle \text{True} : S_{\text{True}}, \text{False} : S_{\text{False}} \rangle$ and
 $\mathcal{B}_C(e', F'\{f \mapsto S_{\text{True}}\}, V') = (\text{Null}, F, V)$ and $F'' = F'\{f \mapsto S_{\text{False}}\}$
 $\mathcal{B}_C(e; e', F, V) = \mathcal{B}_C(e', F'', V')$
 where $(T, F', V') = \mathcal{B}_C(e, F, V)$ and $T \neq \text{link } _$ and
 if $T = \text{linkthis}$ then $F' = \langle l : F_l \rangle_{l \in E}$ and $F'' = \bigvee_{l \in E} F_l$
 else $F'' = F'$
 $\mathcal{B}_C(\text{spawn } C'.m(e), F, V) = (\text{Null}, F', V')$
 where $(\text{Null}, F', V') = \mathcal{B}_C(e, F, V)$ and $\text{Null } m(\text{Null}) \in C'.\text{session}$

Figure 28: Typechecking: algorithm \mathcal{B} .

8 Type Checking Algorithm

This section introduces a type checking algorithm, sound and complete with respect to the type system in Section 6, and describes a prototype implementation of a programming language based on the ideas of the paper.

8.1 The Algorithm

Figures 27 and 28 define a type checking algorithm for the distributed language, including the sequential extensions from Section 4. The algorithm is applied to each component of a distributed system, and in order to ensure type safety of the complete system there must be some separate mechanism to check that each access point n is given the same type everywhere. A program is type checked by calling algorithm \mathcal{W} on each class definition and checking that no call generates an error. The definition of algorithm \mathcal{W} follows the typing rule T-CLASS in Figure 14. It calls algorithm \mathcal{A} to check the relation $F \vdash C : S$ and algorithm \mathcal{B} to type check the bodies of the methods that have req/ens annotations. Algorithm \mathcal{A} also calls algorithm \mathcal{B} to typecheck the bodies of the methods that appear in the session type.

```

class C {
  session { linkthis m(int): ( FALSE: SCf, TRUE: SCt ) }
  where SCf = ... , SCt = ...
  ...
}

class D {
  session { linkthis a(int): ( FALSE: SDf, TRUE: SDt ) ,
    linkthis b(int): ( FALSE: SDf, TRUE: SDt ) ,
    { FALSE, TRUE } c(int): SD1,
    { FALSE, TRUE, UNKNOWN } d(int): SD2 }
  where SDf = ... , SDt = ... , SD1 = ... , SD2 = ...

  f;

  a(x) { // Not allowed, because return type is link f
    f ↔ new C();
    f.m(x); }

  aa(x) { // Allowed, because body type is linkthis
    f ↔ new C();
    switch (f.m(x)) {
      case FALSE: FALSE;
      case TRUE: TRUE; } }

  b(x) { // Allowed, by creating a uniform variant
    even(x); }

  bb(x) { // Allowed, because body type is linkthis
    switch (even(x)) {
      case FALSE: FALSE;
      case TRUE: TRUE; } }

  c(x) { // Allowed, by taking a join of field typings
    f ↔ new C();
    switch (f.m(x)) {
      case FALSE: FALSE;
      case TRUE: TRUE; } }

  cc(x) { // Allowed, by taking a join of equal field typings
    switch (even(x)) {
      case FALSE: FALSE;
      case TRUE: TRUE; } }

  d(x) { // Allowed, because of subtyping between enumerations
    even(x); }
}

```

Figure 29: Example for type checking.

In both \mathcal{A} and \mathcal{B} there are several “if” and “where” clauses; they should be interpreted as conditions which, if not satisfied, cause termination with a typing error.

Because of the coinductive definition of $F \vdash C : S$, algorithm \mathcal{A} uses a set Δ of assumed relationships between field typings F and session types S . If there is no error then the algorithm returns Δ , but at the top level we are only interested in success or failure, not in the returned value.

Algorithm \mathcal{B} checks the typing judgement for expressions, defined in Figure 9, specialized to the top-level form $\text{this} : C[F], V * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], V' * \text{this}$ as explained in Section 3.4.1. The definition of \mathcal{B} follows the typing rules (Figure 9) except for one point: T-VARF means that the rules are not syntax-directed, as any expression with type E can also be given type *linkthis*. For this reason, clause l of \mathcal{B} produces type *linkthis* and a variant field typing with the single label l . More general variant field typings are produced when typing *switch* expressions, as the \vee operator is used to combine the field typings arising from the branches. This is the typical situation when typing the body of a method whose return type is *linkthis*: the body contains a *switch* whose branches return different labels with different associated field typings.

It is possible, however, that giving type `linkthis` to l is incorrect. It might turn out that the expression needs to have an enumerated type E , for example in order to be passed as a method parameter or returned as a method result of type E . An expression that has been inappropriately typed with `linkthis` can, in general, be associated with any variant field typing, for example if it contains a `switch` whose branches yield different field typings. In this case, the algorithm uses \vee to combine the branches of the variant field typing into a single field typing; the join is always over all of the labels in the variant. This happens in several places in algorithm \mathcal{B} , indicated by conditions of the form “if $T = \text{linkthis}$ ”, and in the final “else” branch of the third clause of algorithm \mathcal{A} .

The algorithm for checking subtyping is not described here but is similar to the one defined for channel session types in [31]. We write $S \vee S'$ for the least upper bound of S and S' with respect to subtyping. It is defined by taking the intersection of sets of methods and the least upper bound of their continuations. Details of a similar definition (greatest lower bound of channel session types) can be found in [44].

The type checking algorithm is modular in the sense that to check class C we only need to know the session types of other classes, not their method definitions.

We have not yet investigated type inference, but there are two ways in which it might be beneficial. One would be to infer the `req/ens` annotations. The other would be to support some form of polymorphism over field typings, along the lines that if method m does not use field f then it should be callable independently of the type of f . This might reduce the need to type check the definition of m every time it occurs in the session type.

8.2 Examples of Type Checking

Figure 29 defines classes C and D . In class C , only the outer layer of the session type is of interest; the example uses an object of class C but does not need the definition of method `m`. Class D , as well as the outer layer of the session type, contains a field `f` and one or two candidate definitions for each of the methods `a`, `b`, `c` and `d`. The definitions of `a` and `aa` are alternatives for the method `a` specified in the session type, and so on.

The definition of `a` is not typable because the type of the returned expression is `link f`. Allowing this would let the caller of `a` have access to field `f`. Instead, the result of `f.m(x)` must be analyzed with a `switch`, as in the definition of `aa`, which is typable. The `linkthis` type required by the signature of `a` is introduced by the enumeration labels `FALSE` and `TRUE` in the branches of the `switch`. A compiler could insert `switches` of this kind automatically, allowing the definition of `a` as syntactic sugar.

The remaining method definitions are all typable and illustrate different features of the type system and the algorithm. In the definition of `b`, the method `even` is supposed to be the obvious function for testing parity of an integer, returning `TRUE` or `FALSE`. This definition is typable even though the body of `b` does not introduce a `linkthis` type, because algorithm \mathcal{A} constructs a variant field typing over $\{\text{TRUE}, \text{FALSE}\}$ in which both options are the same. This is seen in the first `else` clause of \mathcal{A} . The definition of `bb` achieves the same effect by using the labels `FALSE` and `TRUE` to introduce the type `linkthis`. Each label corresponds to a partial variant field typing, and checking the `switch` combines them by means of the \vee operator. Because the field `f` is not involved in the method body, the field typing is the same in both options of the variant.

Method `c` has the same definition as `a`, but this time the signature in the session type specifies a simple enumeration as the return type. This is allowed, by using the \vee operator to construct the join of the field typings, in the second `else` clause of \mathcal{A} . This means that when the algorithm proceeds to type check method definitions in the session type `SD1`, the type of `f` is taken to be the join of `SCf` and `SCt`. Whether or not this loss of information causes a problem will depend on the particular definitions of those types, which we have not shown. Method `cc` is handled in the same way, but this time there is no loss of information because the types being joined are identical; this in turn is because `f` is not involved in the method body.

Finally, method `d` illustrates straightforward subtyping between enumerations, defined as set inclusion.

8.3 Correctness of the Algorithm

The following sequence of results outlines the proof of soundness and completeness of the algorithm. The detailed proofs are routine and are omitted.

Theorem 8.1 *Algorithm \mathcal{A} always terminates, either with an error (and then the function \mathcal{A} is undefined) or with a result.*

Proof. Similar to proofs about algorithms for coinductively-defined subtyping relations [53, Chapter 16].

Lemma 8.2 *If $\text{this} : C[F], V * \text{this} \triangleright e : \text{linkthis} \triangleleft \text{this} : C[F'], V' * \text{this}$ then for some E and $\{F_l\}_{l \in E}$, $F' = \langle l : F_l \rangle_{l \in E}$ and $\text{this} : C[F], V * \text{this} \triangleright e : E \triangleleft \text{this} : C[\bigvee_{l \in E} F_l], V' * \text{this}$.*

Proof. By induction on the typing derivation.

Lemma 8.3 *If $\mathcal{B}_C(e, F, V) = (T, F', V')$ then $\text{this} : C[F], V * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], V' * \text{this}$.*

Proof. By induction on the structure of e .

Lemma 8.4 *If $\text{this} : C[F], V * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], V' * \text{this}$ and $\mathcal{B}_C(e, F, V) = (T', F'', V'')$ then $V'' < V'$ and either*

1. $T' < T$ and $F'' < F'$, or
2. $T = \text{linkthis}$, T' is an enumeration E , $F' = \langle l : F_l \rangle_{l \in E'}$, $E \subseteq E'$ and $\forall l \in E. F'' < F_l$, or
3. T is an enumeration E , $T' = \text{linkthis}$, $F'' = \langle l : F_l \rangle_{l \in E'}$, $E' \subseteq E$ and $\forall l \in E'. F_l < F'$.

Proof. By induction on the typing derivation.

Theorem 8.5 *If $F \vdash C : S$ then $\mathcal{A}_C(S, F, \emptyset)$ is defined.*

Proof. Consider the execution of $\mathcal{A}_C(S, F, \emptyset)$. It terminates and has various calls of the form $\mathcal{A}_C(S', F', \Delta)$, including the top-level call. We prove the following statement, by induction on the number of recursive calls in the execution of $\mathcal{A}_C(S', F', \Delta)$: if $\Delta \subseteq \bullet \vdash C : \bullet$ and $F' \vdash C : S'$ then $\mathcal{A}_C(S', F', \Delta)$ is defined and $\mathcal{A}_C(S', F', \Delta) \subseteq \bullet \vdash C : \bullet$.

Lemma 8.6 *If $\mathcal{A}_C(S, F, \Delta)$ is defined then for any Δ' , $\mathcal{A}_C(S, F, \Delta \cup \Delta') = \mathcal{A}_C(S, F, \Delta) \cup \Delta'$.*

Proof. Similar to the proof of Theorem 8.5, by induction on the recursive calls within a given top-level call.

Lemma 8.7 *Suppose $\mathcal{A}_C(\mu X.S_0, F_0, \emptyset)$ is defined and $(F_0, \mu X.S_0) \notin \Delta$. Then for all S and F , if $\mathcal{A}_C(S, F, \Delta \cup \{(F_0, \mu X.S_0)\})$ is defined then $\mathcal{A}_C(S, F, \Delta)$ is defined.*

Proof. Similar to the proof of Theorem 8.5, by induction on the recursive calls within a given top-level call.

Lemma 8.8 *If $\mathcal{A}_C(\mu X.S, F, \emptyset)$ is defined then $\mathcal{A}_C(S\{\mu X.S/X\}, F, \emptyset)$ is defined.*

Proof. By the definition of \mathcal{A} , $\mathcal{A}_C(\mu X.S, F, \emptyset) = \mathcal{A}_C(S\{\mu X.S/X\}, F, \{(F, \mu X.S)\})$, which is therefore defined. By Lemma 8.7, $\mathcal{A}_C(S\{\mu X.S/X\}, F, \emptyset)$ is defined.

Corollary 8.9 *If $\mathcal{A}_C(S, F, \emptyset)$ is defined then $\mathcal{A}_C(\text{unfold}(S), F, \emptyset)$ is defined.*

Theorem 8.10 *If $\mathcal{A}_C(S, F, \emptyset)$ is defined then $F \vdash C : S$.*

Proof. By Corollary 8.9 and the fact that $F \vdash C : S$ is defined in terms of the unfolded structure of session types, it is sufficient to consider the case in which S is guarded.

Similarly to the proof of Theorem 8.5, consider the recursive calls in the execution of $\mathcal{A}_C(S_0, F_0, \emptyset)$. We show that the following relation is a C -consistency relation:

$$\mathcal{R} = \{(F, S) \mid \mathcal{A}_C(S, F', \Delta) \text{ is called for some } \Delta \text{ and } F' \text{ with } F < F'\}.$$

This is easily checked, using the three cases of Lemma 8.4 to correspond to the three cases in the third clause of the definition of \mathcal{A} .

8.4 Implementation

We have used the Polyglot [51] system to implement the ideas of this paper as a prototype extension of Java 1.4 (extended with **enum** declarations), which we call Bica. The compiler accepts conventional Java code, possibly including **@session** annotations in classes and in method parameters, as well as **@req** and **@ens** annotations for recursive methods (cf. Section 4.2). All we do is extended type checking; there is no need to touch the back-end of the compiler.

To keep in line with the expectations of Java programmers, annotations follow the first style in Figure 1, page 3. Also, the type system is nominal (cf. Section 4.4); label sets (cf. Figure 5) are explicitly introduced via Java 1.5 **enum** declarations. The ideas presented in this paper, addressing a subset of the Java language, are extended towards the whole language. In particular:

- The **while** loop technique described in Section 4.1 is extended to handle **for** and **do-while** loops.
- The same idea is used to type the various goto instructions present in Java: exceptions, **break**, **continue** and **return**, labelled versions included.
- All control flow instructions (including **if-then**, not discussed in the paper) can be used with conventional or with session-related **boolean/enum** values.
- Classes not featuring a **@session** annotation are considered shared rather than linear. Their objects are treated very much like the **null** value (cf. Section 4.3). We do not allow a shared class to contain a linear field, even though it is perfectly acceptable for a method of a shared class to have a linear parameter.
- The same technique used for “top-level” classes is used for inner, nested, local (defined within methods) and anonymous classes.
- In order to mention overloaded methods in **@session** annotations, alias names for these methods are introduced via extra annotations.
- Static fields are always shared.
- Class inheritance (cf. Section 4.4) is supported; interface or multiple inheritance is not. **enum** inheritance (contravariant subtyping) is supported via annotations.
- The distributed part of the language is not implemented at the time of this writing.

A prototype implementation is available from <http://gloss.di.fc.ul.pt/bica/>.

9 Related Work

Previous work on session types for object-oriented languages. Two lines of work, by Dezani-Ciancaglini, Yoshida et al. [[13, 25]; [22, 23]] and by Hu [39], have already been described in Section 1. We have explained that the distinctive feature of our work is that we can store a channel in a field of an object and allow several methods to use it. We are also able to interleave sessions on different channels.

[38] have also extended SJ to support event-driven programming, with a session type discipline to ensure safe event handling and progress. We have not considered event-driven programming in our setting.

Campos and Vasconcelos [11, 12] developed MOOL, a simple class-based object-oriented language, to study object usage and access. The novelties are that class usage types are attached to class definitions, and the communication mechanism is based on method call instead of being channel-based. The latter feature is the main difference with respect to our work.

Non-uniform concurrent objects / active objects. Another related line of research, started by [50], aimed at describing the behaviour of non-uniform *active* objects in concurrent systems, whose behaviour (including the set of available methods) may change dynamically. He defined subtyping for active objects, but did not formally define a language semantics or a type system. The topic has been continued, in the context of process calculi, by several authors [[18]; [17]; [47];

[48]; [57, 56, 55]; [9, 10]]. [9] is the most relevant work; it uses an approach based on spatial types to give very fine-grained control of resources, and [45] has implemented a Java prototype based on this idea. [19] define a concurrent Java-like language incorporating inheritance and subtyping and equipped with a type-and-effect system, in which method availability is made dependent on the state of objects.

The distinctive feature of our approach to non-uniform objects, in comparison with all of the above work, is that we allow an object's abstract state to depend on the result of a method call. This gives a very nice integration with the branching structure of channel session types, and with subtyping.

Specifically related to the notion of subtyping between session types, the work of [58] is worth mentioning. He proposes a type-based approach to ensure that both component objects and their clients have compatible protocols. The typing discipline specifies not only how to use the component's methods, but also the notifications it sends to its clients. Rossie calls this enhanced specification a Logical Observable Entity (LOE), which is a finite-state machine equipped with a subtyping notion. An LOE is a high-level description of an object, specifying which transitions (method executions) change its state, providing for each state both the available methods and notifications to be sent to the clients. LOEs support behavioural subtyping, in its afferent aspects (how clients may affect the LOE) — a subtype must allow at least the traces of its supertype, and in its efferent aspects (how a LOE processing a method request has effects on clients) — the subtype must not send more notifications than the supertype. This behavioural subtyping notion on finite-state machines, which is in its spirit very similar to the one of session types — "more offers, less requests", is defined as a simulation relation. Rossie shows that this relation ensures safe substitutability.

Typestates. Based on the fact that method availability depends on an object's internal state (the situation identified by Nierstrasz, as mentioned above), Strom and Yemini [59] proposed *typestates*. The concept consists of identifying the possible states of an object and defining pre- and post-conditions that specify in which state an object should be so that a given method would be available, and in which state the method execution would leave the object.

Vault [20, 27] follows the typestates approach. It uses linear types to control aliasing, and uses the *adoption and focus* mechanism [27] to re-introduce aliasing in limited situations. *Fugue* [21, 28] extends similar ideas to an object-oriented language, and uses explicit pre- and post-conditions.

[4] also work on a typestates approach in an object-oriented language, defining a sound modular automated static protocol-checking setting. They define a state and method refinement relation achieving a behavioural subtyping relation. The work is extended with access permissions, that combine typestate with aliasing information about objects [5], and with concurrency, via the atomic block synchronization primitive used in transactional memory systems [3]. Like us, they allow the typestate to depend on the result of a method call. *Plural* is a prototype tool that embodies their approach, providing automated static analysis in a concurrent object-oriented language [6]. To evaluate their approach they annotated and verified several standard Java APIs [7].

[46] develop a new aliasing control mechanism, finer and more expressive than previous proposals, based on defining object views according to specific access constraints. The discipline is implemented in a type system combining views and a typestate approach, checking user defined aliasing patterns.

Finally, *Sing#* [26] is an extension of C# which has been used to implement Singularity, an operating system based on message-passing. It incorporates session types to specify protocols for communication channels, and introduces typestate-like *contracts*. The published paper [26] does not discuss the relationship between channel contracts and non-uniform objects or typestates, and does not define a formal language. A technical point is that *Sing#* uses a single construct `switch receive` to combine receiving an enumeration value and doing a case-analysis, whereas our system allows a `switch` on an enumeration value to be separated from the method call that produces it.

Session types and typestates are related approaches, but there are stylistic and technical differences. With respect to the former, session types are like labelled transition systems or finite-state automata, capturing the behaviour of an object. When developing an application, one may start from session types and then implement the classes. Typestates take each transition of a session type and attach it to a method as pre- and post-conditions. With respect to technical differences, the main ones are: (a) session types unify types and typestates in a single class type as a global

behavioural specification; (b) our subtyping relation is structural, while the typestates refinement relation is nominal; (c) *Plural* uses a software transactional model as concurrency control mechanism (thus, shared memory), which is lighter and easier than locks, but one has to mark atomic blocks in the code, whereas our communication-centric model (using channels) is simpler and allows us to use the same type abstraction (session types) instead of a new programming construct; moreover, channel-based communication also allows us to specify the client-server communication protocol as the channel session type, and to implement it modularly, in several methods which may even be in different classes; (d) typestate approaches allow flexible aliasing control, whereas our approach uses only linear objects (to add better alias/access control is simple and an orthogonal issue).

Static verification of protocols. *Cyclone* [34] and *CQual* [29] are systems based on the C programming language that allow protocols to be statically enforced by a compiler. *Cyclone* adds many benefits to C, but its support for protocols is limited to enforcing locking of resources. Between acquiring and releasing a lock, there are no restrictions on how a thread may use a resource. In contrast, our system uses types both to enforce locking of objects (via linearity) and to enforce the correct sequence of method calls. *CQual* expects users to annotate programs with type qualifiers; its type system, simpler and less expressive than the above, provides for type inference.

Unique ownership of objects. In order to demonstrate the key idea of modularizing session implementations by integrating session-typed channels and non-uniform objects, we have taken the simplest possible approach to ownership control: strict linearity of non-uniform objects. This idea goes back at least to the work of [2] and has been applied many times. However, linearity causes problems of its own: linear objects cannot be stored in shared data structures, and this tends to restrict expressivity. There is a large literature on less extreme techniques for static control of aliasing: Hogg’s *Islands* [35], Almeida’s *balloon types* [1], Clarke et al.’s *ownership types* [16], Fähndrich and DeLine’s *adoption and focus* [27], Östlund et al.’s *Joe₃* [52] among others. In future work we intend to use an off-the-shelf technique for more sophisticated alias analysis. The property we need is that when changing the type of an object (by calling a method on it or by performing a `switch` or a `while` on an enumeration constant returned from a method call) there must be a unique reference to it.

Resource usage analysis. [41] define a general resource usage analysis problem for an extended λ -calculus, including a type inference system, that statically checks the order of resource usage. Although quite expressive, their system only analyzes the sequence of method *calls* and does not consider branching on method *results* as we do.

Analysis of concurrent systems using pi-calculus. Some work on static analysis of concurrent systems expressed in pi-calculus is also relevant, in the sense that it addresses the question (among others) of whether attempted uses of a resource are consistent with its state. Kobayashi et al. have developed a generic framework [40] including a verification tool [42] in which to define type systems for analyzing various behavioural properties including sequences of resource uses [43]. In some of this work, types are themselves abstract processes, and therefore in some situations resemble our session types. [15] use CCS to describe properties of pi-calculus programs, and verify the validity of temporal formulae via a combination of type-checking and model-checking techniques, thereby going beyond static analysis.

All of this pi-calculus-based work follows the approach of modelling systems in a relatively low-level language which is then analyzed. In contrast, we work directly with the high-level abstractions of session types and objects.

10 Conclusion

We have extended existing work on session types for object-oriented languages by allowing the implementation of a session to be divided between several methods which can be called independently. This supports a modular approach which is absent from previous work. Technically, it is achieved by integrating session types for communication channels and a static type system for non-uniform objects. A session-typed channel is one kind of non-uniform object, but objects whose fields are non-uniform are also, in general, non-uniform. Typing guarantees that the sequence of

messages on every channel, and the sequence of method calls on every non-uniform object, satisfy specifications expressed as session types.

We have formalized the syntax, operational semantics and static type system of a core distributed class-based object-oriented language incorporating these ideas. Soundness of the type system is expressed by type preservation, conformance and correct communication theorems. The type system includes a form of tpestate and uses simple linear type theory to guarantee unique ownership of non-uniform objects. It allows the tpestate of an object after a method call to depend on the result of the call, if this is of an enumerated type, and in this situation, the necessary case-analysis of the method result does not need to be done immediately after the call.

We have illustrated our ideas with an example based on a remote file server, and described a prototype implementation. By incorporating further standard ideas from the related literature, it should be straightforward to extend the implementation to a larger and more practical language.

In the future we intend to work on the following topics. (1) More flexible control of aliasing. The mechanism for controlling aliasing should be orthogonal to the theory of how operations affect uniquely-referenced objects. We intend to adapt existing work to relax our strictly linear control and obtain a more flexible language. (2) In Section 4.4 we outlined an adaptation of our structural type system to a nominal type system as found in languages such as Java. We would also like to account for Java’s distinction and relationship between classes and interfaces. (3) Specifications involving several objects. Multi-party session types [8, 36] and conversation types [10] specify protocols with more than two participants. It would be interesting to adapt those theories into type systems for more complex patterns of object usage.

Acknowledgements We thank Jonathan Aldrich and Luís Caires for helpful discussions. Bica (Section 8.4) was implemented by Alexandre Z. Caldeira. Gay was partially supported by the UK EPSRC (EP/E065708/1 “Engineering Foundations of Web Services” and EP/F037368/1). He thanks the University of Glasgow for the sabbatical leave during which part of this research was done. Gay and Ravara were partially supported by the Security and Quantum Information Group at Instituto de Telecomunicações, Portugal. Vasconcelos was partially supported by the Large-Scale Informatics Systems Laboratory, Portugal. Ravara was partially supported by the Portuguese Fundação para a Ciência e a Tecnologia FCT (SFRH/BSAB/757/2007), and by the UK EPSRC (EP/F037368/1 “Behavioural Types for Object-Oriented Languages”). Gesbert was supported by the UK EPSRC (EP/E065708/1) and by the French ANR (project ANR-08-EMER-004 “CODEX”).

References

- [1] Paulo Sérgio Almeida. Balloon types: Controlling sharing of state in data types. In *Proceedings of the 11th European Conference on Object-Oriented Programming (ECOOP)*, volume 1241 of *Lecture Notes in Computer Science*, pages 32–59. Springer, 1997.
- [2] Henry G. Baker. ‘Use-once’ variables and linear objects — storage management, reflection and multi-threading. *ACM SIGPLAN Notices*, 30(1):45–52, 1995.
- [3] Nels E. Beckman, Kevin Bierhoff, and Jonathan Aldrich. Verifying correct usage of atomic blocks and tpestate. In *Proceedings of the 23rd ACM SIGPLAN Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA)*, pages 227–244. ACM, 2008.
- [4] Kevin Bierhoff and Jonathan Aldrich. Lightweight object specification with tpestates. In *Proceedings of the 13th ACM SIGSOFT Symposium on Foundations of Software Engineering (FSE)*, pages 217–226. ACM, 2005.
- [5] Kevin Bierhoff and Jonathan Aldrich. Modular tpestate checking of aliased objects. In *Proceedings of the 22nd ACM SIGPLAN Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA)*, pages 301–320. ACM, 2007.

- [6] Kevin Bierhoff and Jonathan Aldrich. PLURAL: checking protocol compliance under aliasing. In *Companion of the 30th International Conference on Software Engineering (ICSE)*, pages 971–972. ACM, 2008.
- [7] Kevin Bierhoff, Nels E. Beckman, and Jonathan Aldrich. Practical API protocol checking with access permissions. In *Proceedings of the 23rd European Conference on Object-Oriented Programming (ECOOP)*, volume 5653 of *Lecture Notes in Computer Science*, pages 195–219. Springer, 2009.
- [8] E. Bonelli and A. Compagnoni. Multipoint Session Types for a Distributed Calculus. In *Proceedings of the 3rd International Symposium on Trustworthy Global Computing (TGC)*, volume 4912 of *Lecture Notes in Computer Science*, pages 240–256. Springer, 2007.
- [9] Luis Caires. Spatial-behavioral types for concurrency and resource control in distributed systems. *Theoretical Computer Science*, 402(2–3):120–141, 2008.
- [10] Luís Caires and Hugo Torres Vieira. Conversation types. *Theoretical Computer Science*, 411(51–52):4399–4440, 2010.
- [11] Joana Campos. Linear and shared objects in concurrent programming. Master’s thesis, University of Lisbon, 2010.
- [12] Joana Campos and Vasco T. Vasconcelos. Channels as objects in concurrent object-oriented programming. In *Proceedings of the 3rd International Workshop on Programming Language Approaches to Concurrency and Communication-cEntric Software (PLACES)*, Electronic Proceedings in Theoretical Computer Science (EPTCS), 2010. To appear.
- [13] Sara Capecchi, Mario Coppo, Mariangiola Dezani-Ciancaglini, Sophia Drossopoulou, and Elena Giachino. Amalgamating sessions and methods in object-oriented languages with generics. *Theoretical Computer Science*, 410(2–3):142–167, 2009.
- [14] Marco Carbone, Kohei Honda, and Nobuko Yoshida. Structured global programming for communication behaviour. In *Proceedings of the 16th European Symposium on Programming Languages and Systems (ESOP)*, volume 4421 of *Lecture Notes in Computer Science*, pages 2–17. Springer, 2007.
- [15] Sagar Chaki, Sriram K. Rajamani, and Jakob Rehof. Types as models: model checking message-passing programs. In *Proceedings of the 29th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 45–57. ACM, 2002.
- [16] D. G. Clarke, J. M. Potter, and J. Noble. Ownership types for flexible alias protection. In *Proceedings of the 13th ACM SIGPLAN Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA)*, pages 48–64. ACM, 1998.
- [17] Jean-Louis Colaço, Mark Pantel, Fabien Dagnat, and Patrick Sallé. Safety analysis for non-uniform service availability in Actors. In *Proceedings of the IFIP TC6/WG6.1 3rd International Conference on Formal Methods for Open Object-Based Distributed Systems (FMOODS)*, volume 139 of *IFIP Conference Proceedings*. Kluwer, 1999.
- [18] Jean-Louis Colaço, Mark Pantel, and Patrick Sallé. A set-constraint-based analysis of Actors. In *Proceedings of the IFIP TC6/WG6.1 International Workshop on Formal Methods for Open Object-Based Distributed Systems (FMOODS)*, pages 107–122. Chapman & Hall, 1997.
- [19] Ferruccio Damiani, Elena Giachino, Paola Giannini, and Sophia Drossopoulou. A type safe state abstraction for coordination in Java-like languages. *Acta Informatica*, 45(7–8):479–536, 2008.
- [20] Robert DeLine and Manuel Fähndrich. Enforcing high-level protocols in low-level software. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, pages 59–69. ACM, 2001.

- [21] Robert DeLine and Manuel Fähndrich. The Fugue protocol checker: is your software Baroque? Technical Report MSR-TR-2004-07, Microsoft Research, 2004.
- [22] Mariangiola Dezani-Ciancaglini, Sophia Drossopoulou, Elena Giachino, and Nobuko Yoshida. Bounded session types for object-oriented languages. In *Proceedings of the 5th International Symposium on Formal Methods for Components and Objects (FMCO 2006)*, volume 4709 of *Lecture Notes in Computer Science*, pages 207–245. Springer, 2007.
- [23] Mariangiola Dezani-Ciancaglini, Sophia Drossopoulou, Dimitris Mostrous, and Nobuko Yoshida. Objects and session types. *Information and Computation*, 207(5):595–641, 2009.
- [24] Mariangiola Dezani-Ciancaglini, Dimitris Mostrous, Nobuko Yoshida, and Sophia Drossopoulou. Session types for object-oriented languages. In *Proceedings of the 20th European Conference on Object-Oriented Programming (ECOOP)*, volume 4067 of *LNCS*, pages 328–352. Springer, 2006.
- [25] Mariangiola Dezani-Ciancaglini, Nobuko Yoshida, Alexander Ahern, and Sophia Drossopoulou. A distributed object-oriented language with session types. In *Proceedings of the International Symposium on Trustworthy Global Computing (TGC)*, volume 3705 of *Lecture Notes in Computer Science*, pages 299–318. Springer, 2005.
- [26] Manuel Fähndrich, Mark Aiken, Chris Hawblitzel, Orion Hodson, Galen Hunt, James R. Larus, and Steven Levi. Language support for fast and reliable message-based communication in Singularity OS. In *EuroSys*, pages 177–190. ACM, 2006.
- [27] Manuel Fähndrich and Robert DeLine. Adoption and focus: practical linear types for imperative programming. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, pages 13–24. ACM, 2002.
- [28] Manuel Fähndrich and Robert DeLine. Typestates for objects. In *Proceedings of the 13th European Symposium on Programming Languages and Systems (ESOP)*, volume 3086 of *Lecture Notes in Computer Science*, pages 465–490. Springer, 2004.
- [29] Jeffrey S. Foster, Tachio Terauchi, and Alex Aiken. Flow-sensitive type qualifiers. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, pages 1–12. ACM, 2002.
- [30] Simon Gay, Vasco T. Vasconcelos, António Ravara, Nils Gesbert, and Alexandre Z. Caldeira. Modular session types for distributed object-oriented programming. In *Proceedings of the 37th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 299–312. ACM, 2010.
- [31] Simon J. Gay and Malcolm J. Hole. Subtyping for session types in the pi calculus. *Acta Informatica*, 42(2/3):191–225, 2005.
- [32] Simon J. Gay, António Ravara, and Vasco T. Vasconcelos. Session types for inter-process communication. Technical Report TR-2003-133, Department of Computing Science, University of Glasgow, 2003.
- [33] Simon J. Gay and Vasco T. Vasconcelos. Linear type theory for asynchronous session types. *Journal of Functional Programming*, 20(1):19–50, 2010.
- [34] Dan Grossman, Greg Morrisett, Trevor Jim, Michael Hicks, Yanling Wang, and James Cheney. Region-based memory management in Cyclone. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, pages 282–293. ACM, 2002.
- [35] John Hogg. Islands: aliasing protection in object-oriented languages. In *Proceedings of the 6th ACM SIGPLAN Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA)*, pages 271–285. ACM, 1991.

- [36] K. Honda, N. Yoshida, and M. Carbone. Multipart asynchronous session types. In *Proceedings of the 35th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 273–284. ACM, 2008.
- [37] Kohei Honda, Vasco Vasconcelos, and Makoto Kubo. Language primitives and type discipline for structured communication-based programming. In *Proceedings of the 7th European Symposium on Programming Languages and Systems (ESOP)*, volume 1381 of *Lecture Notes in Computer Science*, pages 122–138. Springer, 1998.
- [38] Raymond Hu, Dimitrios Kouzapas, Olivier Pernet, Nobuko Yoshida, and Kohei Honda. Type-safe eventful sessions in Java. In *Proceedings of the 24th European Conference on Object-Oriented Programming (ECOOP)*, volume 6183 of *Lecture Notes in Computer Science*, pages 329–353. Springer, 2010.
- [39] Raymond Hu, Nobuko Yoshida, and Kohei Honda. Session-based distributed programming in Java. In *Proceedings of the 22nd European Conference on Object-Oriented Programming (ECOOP)*, volume 5142 of *Lecture Notes in Computer Science*, pages 516–541. Springer, 2008.
- [40] Atsushi Igarashi and Naoki Kobayashi. A generic type system for the pi-calculus. *Theoretical Computer Science*, 311(1–3):121–163, 2004.
- [41] Atsushi Igarashi and Naoki Kobayashi. Resource usage analysis. *ACM Transactions on Programming Languages and Systems*, 27(2):264–313, 2005.
- [42] Naoki Kobayashi. Type-based information flow analysis for the pi-calculus. *Acta Informatica*, 42(4–5):291–347, 2005.
- [43] Naoki Kobayashi, Kohei Suenaga, and Lucian Wischik. Resource usage analysis for the π -calculus. *Logical Methods in Computer Science*, 2(3:4):1–42, 2006.
- [44] Leonardo G. Mezzina. *Typing Services*. PhD thesis, IMT Institute for Advanced Studies, Lucca, Italy, 2009.
- [45] Filipe Militão. Design and implementation of a behaviorally typed programming system for web services. Master’s thesis, New University of Lisbon, 2008.
- [46] Filipe Militão, Jonathan Aldrich, and Luís Caires. Aliasing control with view-based typestate. In *Proceedings of the 12th Workshop on Formal Techniques for Java-Like Programs (FTfJP)*. ACM, 2010.
- [47] Elie Najm, Abdelkrim Nimour, and Jean-Bernard Stefani. Guaranteeing liveness in an object calculus through behavioral typing. In *Proceedings of the IFIP TC6 WG6.1 Joint International Conference on Formal Description Techniques for Distributed Systems and Communication Protocols (FORTE XII) and Protocol Specification, Testing and Verification (PSTV XIX)*, pages 203–221. Kluwer, 1999.
- [48] Elie Najm, Abdelkrim Nimour, and Jean-Bernard Stefani. Infinite types for distributed object interfaces. In *Proceedings of the IFIP TC6 WG6.1 3rd International Conference on Formal Methods for Open Object-Based Distributed Systems (FMOODS)*, volume 139 of *IFIP Conference Proceedings*. Kluwer, 1999.
- [49] Matthias Neubauer and Peter Thiemann. An implementation of session types. In *Proceedings of the 6th International Symposium on Practical Aspects of Declarative Languages (PADL)*, volume 3057 of *Lecture Notes in Computer Science*, pages 56–70. Springer, 2004.
- [50] Oscar Nierstrasz. Regular types for active objects. In *Object-Oriented Software Composition*, pages 99–121. Prentice Hall, 1995.
- [51] Nathaniel Nystrom, Michael R. Clarkson, and Andrew C. Myers. Polyglot: an extensible compiler framework for Java. In *Proceedings of the 12th International Conference on Compiler Construction (CC)*, volume 2622 of *Lecture Notes in Computer Science*, pages 138–152. Springer, 2003.

- [52] Johan Östlund, Tobias Wrigstad, Dave Clarke, and Beatrice Åkerblom. Ownership, uniqueness and immutability. In *Objects, Components, Models and Patterns: 46th International Conference, TOOLS EUROPE*, volume 11 of *Lecture Notes in Business Information Processing*, pages 178–197. Springer, 2008.
- [53] Benjamin C. Pierce. *Types and Programming Languages*. MIT Press, 2002.
- [54] Riccardo Pucella and Jesse A. Tov. Haskell session types with (almost) no class. In *Proceedings of the 1st ACM SIGPLAN Symposium on Haskell*, pages 25–36. ACM, 2008.
- [55] Franz Puntigam. State inference for dynamically changing interfaces. *Computer Languages*, 27:163–202, 2002.
- [56] Franz Puntigam and Christof Peter. Types for active objects with static deadlock prevention. *Fundamenta Informaticæ*, 49:1–27, 2001.
- [57] António Ravara and Vasco T. Vasconcelos. Typing non-uniform concurrent objects. In *Proceedings of the 11th International Conference on Concurrency Theory (CONCUR)*, volume 1877 of *Lecture Notes in Computer Science*, pages 474–488. Springer, 2000.
- [58] Jonathan G. Rossie, Jr. Logical observable entities. In *Proceedings of the 25th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 154–165. ACM, 1998.
- [59] Robert E. Strom and Shaula Yemini. Typestate: A programming language concept for enhancing software reliability. *IEEE Transactions on Software Engineering*, 12(1):157–171, 1986.
- [60] Kaku Takeuchi, Kohei Honda, and Makoto Kubo. An interaction-based language and its typing system. In *Proceedings of the 6th International Conference on Parallel Architectures and Languages Europe (PARLE)*, volume 817 of *Lecture Notes in Computer Science*, pages 398–413. Springer, 1994.
- [61] Antonio Vallecillo, Vasco T. Vasconcelos, and António Ravara. Typing the behavior of software components using session types. *Fundamenta Informaticæ*, 73(4):583–598, 2006.
- [62] Vasco T. Vasconcelos, Simon J. Gay, and António Ravara. Type checking a multithreaded functional language with session types. *Theoretical Computer Science*, 368(1–2):64–87, 2006.
- [63] Vasco T. Vasconcelos, Simon J. Gay, António Ravara, Nils Gesbert, and Alexandre Z. Caldeira. Dynamic interfaces. Presented at the International Workshop on Foundations of Object-Oriented Languages (FOOL), 2009.
- [64] Andrew K. Wright and Matthias Felleisen. A syntactic approach to type soundness. *Information and Computation*, 115(1):38–94, 1994.

Appendix: Proofs of lemmas from Section 7.1

Lemma 7.1 *Suppose $\Theta \vdash h : \Gamma$. Then (a) h is complete, (b) $\text{chans}(\Gamma) \subseteq \text{dom}(\Theta) \setminus \text{chans}(h)$ and (c) $\text{objs}(\Gamma) \subseteq \text{roots}(h)$.*

Proof. By induction on the derivation of $\Theta \vdash h : \Gamma$. The only axiom is T-EMPTY for which the properties are true. Then T-HIDE does not change either h or $\text{dom}(\Gamma)$ so it preserves all three properties. The other case is T-HADD. Let h' be the heap in the conclusion. Then $\text{children}_{h'}(o)$ is the set of v_i which are object identifiers. Let K be the set of v_i which are channel endpoints. The typing derivation for the sequence of swaps in the right premise must include an occurrence of T-REF for each object identifier, and of T-CHAN for each channel endpoint, each followed by T-SWAP and a number of occurrences of T-SEQ. Looking at these rules, we can see that this implies:

1. $\text{children}_{h'}(o) \cup K \subseteq \text{dom}(\Gamma)$ and

2. $\text{dom}(\Gamma') \subseteq (\text{dom}(\Gamma) \setminus (\text{children}_{h'}(o) \cup K)) \cup \{o\}$. (Note that o cannot be one of the v_i because it is the current object in the judgement: the premise of T-REF forbids it.)

From (1) and induction hypothesis (c) we get $\text{children}_{h'}(o) \subseteq \text{roots}(h)$. We have $\text{roots}(h) \subseteq \text{dom}(h) \subseteq \text{dom}(h')$ and o is the only new object in h' , so h' is complete.

If we project (2) onto just channel endpoints, we get $\text{chans}(\Gamma') \subseteq \text{chans}(\Gamma) \setminus K$. From the definition of h' , $\text{chans}(h')$ is equal to $\text{chans}(h) \cup K$. Hence induction hypothesis (b) yields (b) again for h' .

If we project (2) onto just object identifiers, we get $\text{objs}(\Gamma') \subseteq (\text{objs}(\Gamma) \setminus \text{children}_{h'}(o)) \cup \{o\}$. From induction hypothesis (a) and the fact that $o \notin \text{dom}(h)$ we get that o is a root in h' . Furthermore, all roots of h which are not children of o are also roots of h' . Thus induction hypothesis (c) allows us to conclude $\text{objs}(\Gamma') \subseteq \text{roots}(h')$.

Lemma 7.2 (Rearrangement of typing derivations for expressions) *Suppose we have $\Gamma * r \triangleright e : T \triangleleft \Gamma' * r'$. Then there exists a typing derivation for this judgement in which:*

1. T-SUB only occurs at the very end, just before T-SWITCH or T-SWITCHLINK as the last rule in the derivation for each of the branches, or just before T-CALL as the last rule in the derivation for the parameter;
2. T-SUBENV only occurs immediately before T-SUB in the first three cases and does not occur at all in the fourth, i.e. T-CALL.

Proof. First note that T-SUB and T-SUBENV commute and that any consecutive sequence of occurrences of one of these rules can collapse into a single occurrence using transitivity. What remains to be shown is that these rules can be pushed down in all cases but those mentioned in the statement. We enumerate the cases below.

- T-SWAP. T-SUB on the premise can be replaced with T-SUBENV on the conclusion as T has been transferred to the environment. T-SUBENV on the premise can be replaced by a combination of T-SUB (for the type of $r'.f$) and T-SUBENV (for the rest) on the conclusion.
- T-CALL. If T-SUBENV is used on the premise to increase the type of something else than $r'.f$ it can be moved to the conclusion. If the type of $r'.f$ is changed, first note that the only relevant part is the signature of m_j . Suppose the subsumption step changes it from $U_j m_j(U'_j) : S'_j$ to $T_j m_j(T'_j) : S_j$. For the parameter type we have $T'_j <: U'_j$ so we can use T-SUB on the premise to increase the type of e from T'_j to U'_j instead. For the session and result types, we have two cases:

- if $U_j <: T_j$ and $S'_j <: S_j$ it can just be moved to a T-SUBENV step on the conclusion.
- if $U_j = E$, $T_j = \text{linkthis}$ and $\langle l : S'_j \rangle_{l \in E} <: S_j$, then the original conclusion of the rule (with T-SUBENV on the premise) was:

$$\Gamma * r \triangleright f.m_j(e) : \text{link } f \triangleleft \Gamma' \{r'.f \mapsto S_j\} * r'$$

and the new one with the subsumption step removed is:

$$\Gamma * r \triangleright f.m_j(e) : E \triangleleft \Gamma' \{r'.f \mapsto S'_j\} * r'.$$

So in that case the original judgement can be obtained back from this new conclusion using T-VARS followed by T-SUBENV.

- T-SEQ. T-SUB on the first premise is irrelevant and T-SUBENV on the same premise can be removed using Lemma 3.14. Subsumption on the second premise straightforwardly commutes to the conclusion.
- T-SWITCH. Lemma 3.14 allows us to remove T-SUBENV on the first premise. Straightforwardly T-SUB can be removed as well as it just makes E' smaller.
- T-SWITCHLINK. T-SUB is irrelevant; removing T-SUBENV can only make E' and the initial typing environments for the branches smaller and we can use Lemma 3.14.

- T-VARF and T-VARS. T-SUB can increase E which becomes the indexing set of the variant in the conclusion. By definition of subtyping for variants it is possible to increase it afterwards using T-SUBENV. T-SUBENV straightforwardly commutes.
- T-RETURN. T-SUB straightforwardly commutes, as well as the part of T-SUBENV not concerning $r'.f$. Subsumption on $\Gamma'(r'.f)$ can be removed using Proposition 3.15. \square

Lemma 7.3 (Rearrangement of typing derivations for heaps) *Suppose $\Theta \vdash h : \Gamma$ holds. Let o be an arbitrary root of h . Then there exists a typing derivation for it such that:*

1. T-SUB is never used;
2. T-SUBENV is used at most once, as the last rule leading to the right premise of the last occurrence of T-HADD;
3. every occurrence of T-HIDE follows immediately the occurrence of T-HADD concerning the same object identifier;
4. the occurrence of T-HADD concerning an identifier o' is always immediately preceded (on the left premise) by the occurrences of T-HADD/T-HIDE concerning the descendants of o' ;
5. the first root added is o .

Proof. The first two points are a consequence of Lemma 7.2: the only expressions which appear in the typing derivation are sequences of swaps, not containing any switch or method call; furthermore their type is always Null, making T-SUB at the end irrelevant. What remains to be checked is then just that T-SUBENV at the end of the derivation for one sequence of swaps can be pushed down to the next occurrence of T-HADD whenever there is one. This is just a matter of using Proposition 3.15 in the case of T-HIDE and Lemma 3.14 in the case of T-HADD.

Note that these points imply in particular that in all applications of T-HADD but the last one, any element in $\text{dom}(\Gamma)$ which is not one of the v_i also occurs in Γ' with exactly the same type.

For the third point, first notice that the premise of T-HIDE implies o is a root of h because of Lemma 7.1. This implies that the rule immediately above T-HIDE either is a T-HADD introducing o or does not concern o at all (in particular, o cannot be a v_i , otherwise it would not be a root in the conclusion). In the second case, T-HIDE can be pushed upwards.

The fourth and fifth points are a consequence of the remark we made about the first two: if o' is not a descendant of o nor vice-versa, then the occurrences of T-HADD and T-HIDE concerning o and its descendants commute with those concerning o' and its descendants as they affect completely disjoint parts of the environment. In the case of the last occurrence of T-HADD there may be a subsumption step but it is still possible to commute with it by pushing this subsumption step down again.

Lemma 7.4 (Splitting of the heap) *Suppose $\Theta \vdash h : \Gamma, o : T$. Let $\Theta_1 = \Theta \setminus \text{chans}(h \downarrow o)$ and let Θ_2 be Θ restricted to $\text{chans}(h \downarrow o)$. Then we have: $\Theta_1 \vdash (h \uparrow o) : \Gamma$ and $\Theta_2 \vdash (h \downarrow o) : o : T$.*

Proof. We know from Lemma 7.1 that o is a root in h . We consider the particular derivation given by Lemma 7.3 where o is the first root added to the heap. Now if we look at the conclusion of the last rule concerning o (T-HADD or T-HIDE depending whether T is a field or session type), we know that at this point the heap is $h \downarrow o$, and therefore the only object identifier in the environment is its only root: o . Furthermore, this part of the derivation is still true if we replace the initial Θ with Θ_2 , with the only difference that then the final Γ contains no channels, and thus is of the form $o : T'$. We also know that the type of o is not changed in the rest of the derivation except possibly by the subsumption step at the end; therefore T' is a subtype of T . If they are session types, using Proposition 3.17 we can change the last occurrence of T-HIDE to use T instead of T' and get $\Theta_2 \vdash (h \downarrow o) : o : T$. Otherwise, we can add a subsumption step to the derivation for the sequence of swaps on the right of T-HADD to get the same result.

For the rest of the derivation, we know that o is not used, therefore it can be removed from the initial environment without affecting the derivation except by the fact that it will not be in the final environment either. Furthermore, we know from Lemma 7.1 that the initial environment minus its only object identifier o is included in $\Theta \setminus \text{chans}(h \downarrow o) = \Theta_1$. More precisely, the lemma gives

us inclusion of domains, but because subsumption is not used in the first part of the derivation we also know that the types are the same. Thus we can replace the first part of the derivation by an instance of T-EMPTY using Θ_1 and the second part is still valid (with all the descendants of o removed from the heap), yielding $\Theta_1 \vdash (h \uparrow o) : \Gamma$ at the bottom.

Lemma 7.5 (Merging of heaps) *Suppose $\Theta \vdash h : \Gamma$ and $\Theta' \vdash h' : \Gamma'$ with $\text{dom}(h) \cap \text{dom}(h') = \emptyset$ and $\text{dom}(\Theta) \cap \text{dom}(\Theta') = \emptyset$. Then we have $\Theta + \Theta' \vdash h + h' : \Gamma + \Gamma'$.*

Proof. Since Θ and Θ' are disjoint, the channels in Θ' cannot appear anywhere in the typing derivation for h . Thus, it is possible to add Θ' to every typing environment occurring in the derivation for h without altering its validity, yielding $\Theta + \Theta' \vdash h : \Gamma + \Theta'$. Looking now at the derivation for h' , since the domains of the heaps are disjoint and $\text{objs}(\Gamma) \subseteq \text{roots}(h)$, none of the identifiers in Γ can appear anywhere in it. Thus we can add Γ to every typing environment and h to every heap occurring in the derivation for h' , replacing the T-EMPTY at the top with the conclusion of the other derivation, which yields the result we want.

Lemma 7.6 *Suppose $\Theta \vdash h : o : S$. Let φ be an injective function from $\text{dom}(h)$ to \mathcal{O} . Then we have $\Theta \vdash \varphi(h) : \varphi(o) : S$.*

Proof. Straightforward. Changing the names does not affect the typing derivation in any way.

Lemma 7.7 (Opening) *If $\Theta \vdash h : \Gamma$, if $\Gamma(r)$ is a branch session type S and if $h(r)$ is an object identifier o , then we know from Lemma 7.1 that h contains an entry for o . Let C be the class of this entry, then there exists a field typing F for C such that $\Theta \vdash h : \Gamma\{r \mapsto C[F]\}$ and $F \vdash C : S$.*

Proof. We prove this by induction on the depth of r . The base case is $r = o$. Using Lemmas 7.4 and 7.5, we can restrict ourselves to the case where o is the only root of h . In that case we know that the last rule used in the typing derivation for $\Theta \vdash h : o : S$ must be T-HIDE. The result we want is constituted precisely by the premises of that rule.

For the inductive case, r is of the form $o'.f.\vec{f}$. We consider the case where o' is the only root. The typing derivation then ends with T-HADD and f gets populated in the sequence of swaps by some object identifier³ o'' . Let $r' = o''.\vec{f}$, and consider what $\Gamma(r')$ can be, knowing that in the conclusion r has a branch session type: the only way the type can be modified in the sequence of swaps is by subsumption. Indeed, T-VARS, the other possibility, introduces a variant type. Therefore $\Gamma(r') = S'$ with $S' <: S$. We can thus use the induction hypothesis to replace Γ with $\Gamma\{r \mapsto C[F]\}$ on the left premise, with $F \vdash C : S'$. Then just use Proposition 3.17 to see that we also have $F \vdash C : S$ and see that the type yielded in the conclusion by this new premise is what we want.

Lemma 7.8 (Closing) *If $\Theta \vdash h : \Gamma$ and $\Gamma(r) = C[F]$ and $F \vdash C : S$, then $\Theta \vdash h : \Gamma\{r \mapsto S\}$.*

Proof. Again we prove this by induction on the depth of r and the base case is $r = o$. In that case the lemma is nothing more than T-HIDE. The inductive case is very similar to the above: we look at the type of r' (defined as above) in the Γ on the left premise of the last T-HADD, noticing that the type of r in the conclusion can only differ from it by subsumption, this time because we know from Lemma 3.27 that T-VARF is never used. Hence the original type is $C[F']$ with $F' <: F$. Proposition 3.15 gives us $F' \vdash C : S$ and thus we can use the induction hypothesis to change the type of r' in this premise, which propagates to the type of r in the conclusion.

Lemma 7.9 (modification of the heap) *Suppose that we have $\Theta \vdash h : \Gamma$ and $\Gamma * r \triangleright v' : T' \triangleleft \Gamma' * r$, and that $\Gamma'(r.f) = T$ where T is not a variant. Let $v = h(r).f$. The modified heap $h\{r.f \mapsto v'\}$ can be typed as follows:*

1. if v is an object identifier or a channel endpoint, then:

$$\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}, v : T$$

³We know o'' is an object identifier and not a channel endpoint because, according to the hypotheses, either it is o itself or \vec{f} is nonempty, implying o'' has fields.

2. if v is not an object or channel and T is not a link type, then:

$$\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}$$

3. if $v = l_0$ and $T = \text{link } f'$, then:

- $\Gamma'(r.f') = \langle l : S_l \rangle_{l \in E}$ for some E such that $l_0 \in E$ and some set of branch session types S_l . Note that this implies $f \neq f'$.
- $\Theta \vdash h\{r.f \mapsto v'\} : \Gamma'\{r.f \mapsto T'\}\{r.f' \mapsto S_{l_0}\}$

Proof. First of all, note that the hypothesis that $\Gamma'(r.f)$ is defined implies that $\Gamma'(r)$ is not a variant, hence T' is not `linkthis`. In other words, the judgement cannot be derived from T-VARF. Furthermore, the fact that T is not a variant either means that the judgement is not derived from an instance of T-VARS referring to field f . As this rule is the only possibility (beside subsumption) for a judgement typing a value to depend on, and modify, the type of a field, this implies that $\Gamma(r.f)$ is a subtype of T and also that the judgement would still hold with another type for f . In particular we have $\Gamma\{r.f \mapsto \text{Null}\} * r \triangleright v' : T' \triangleleft \Gamma'\{r.f \mapsto \text{Null}\} * r$ (a). We will in the following use this judgement (a) rather than the one in the hypothesis.

We prove the lemma by induction on the depth of r , but the inductive case is straightforward (just apply the induction hypothesis to the left premise of T-HADD). In the base case, r is an object identifier o . We use Lemma 7.4 to consider a typing derivation for the sub-heap $h \downarrow o$. Let $\Gamma_o = o : T_o$ and Θ_o be the environments corresponding to that part of the heap. We look at the application of T-HADD which ends the derivation for $\Theta_o \vdash h_o : \Gamma_o$. As T is not a variant, it is possible to consider that f is the last field to get populated in the swap sequence. We thus have something of the form:

$$\frac{\Theta_o \vdash (h \downarrow o) \setminus o : \Gamma_1 \quad \frac{\frac{\text{(T-SEQ)} \quad \dots \quad \frac{\text{(T-SWAP)} \quad \frac{\text{(1)} \quad \dots}{\Gamma_2 * o \triangleright v : T_v \triangleleft \Gamma_3 * o}}{\Gamma_2 * o \triangleright f \leftrightarrow v : \text{Null} \triangleleft \Gamma_3\{o.f \mapsto T_v\} * o}}}{\Gamma_1 * o \triangleright \dots; f \leftrightarrow v : \text{Null} \triangleleft \Gamma_3\{o.f \mapsto T_v\} * o}}{\Gamma_1 * o \triangleright \dots; f \leftrightarrow v : \text{Null} \triangleleft \Gamma_o * o} \text{(T-SUBENV)}} \text{(T-HADD)}} \Theta_o \vdash h \downarrow o : \Gamma_o$$

with $T_v <: T$ and $\Gamma_3\{o.f \mapsto T_v\} <: \Gamma_o$. If we change the type of $o.f$, this last relation becomes $\Gamma_3 <: \Gamma_o\{o.f \mapsto \text{Null}\}$ (b).

What we want to do is to replace the judgement on the top right, which is an application of some rule (1), by a judgement typing v' . For this, we need the rest of the environment. We consider the judgement for the rest of the heap, $\Theta \setminus \Theta_o \vdash h \uparrow o : \Gamma \setminus o$. Since the domains are disjoint, we can apply Lemma 7.5 to this and the leftmost premise of T-HADD, yielding $\Theta \vdash h \setminus o : \Gamma \setminus o + \Gamma_1$. If we replace our left premise with this, the initial environment we get on the top right is now $\Gamma_4 = \Gamma \setminus o + \Gamma_2$, as the additional part is unaffected by the sequence of swaps. This environment is almost $\Gamma\{o.f \mapsto \text{Null}\}$, but not quite. We now have three cases depending on what rule (1) is, which correspond to the three cases of the lemma.

1. If (1) is T-REF or T-CHAN, meaning v is an object identifier or a channel endpoint, then $\Gamma_2 = \Gamma_3, v : T_v$. Using (b), this yields $\Gamma_2 <: \Gamma_o\{o.f \mapsto \text{Null}\}, v : T_v$. Adding $\Gamma \setminus o$ to both sides, we get $\Gamma_4 <: \Gamma\{o.f \mapsto \text{Null}\}, v : T_v$. If we replace the initial environment in (a) with this one, we get the $v : T_v$ back in the final environment. We then use Lemma 3.14 to replace this initial environment with Γ_4 , and T-SUBENV to change T_v into T in the final one: $\Gamma_4 * o \triangleright v' : T' \triangleleft \Gamma'\{o.f \mapsto \text{Null}\}, v : T * o$. Just see that it yields what we want at the bottom of the derivation.
2. If (1) is T-LABEL or T-NUL or T-NAME, i.e. if v is a literal value of non-link, non-linear type, then Γ_2 is identical to Γ_3 and we have, using (b) and adding $\Gamma \setminus o$ to both sides, $\Gamma_4 <: \Gamma\{o.f \mapsto \text{Null}\}$, so we can directly (with Lemma 3.14) use judgement (a).
3. If (1) is T-VARS, the last possibility, then v is a label l_0 and T_v is `link f'` for some f' . As it has no strict supertype, we have $T = \text{link } f'$ as well. We also have $\Gamma_3(o.f') = \langle l_0 : S \rangle$. From (b) we have that $\Gamma_o(o.f') = \Gamma(o.f')$ is a supertype of this variant type, thus also a variant. This implies that (a) cannot come from a T-VARS concerning f' ; therefore, $\Gamma'(o.f')$

is a supertype of $\Gamma(o.f')$ and hence, by transitivity, of $\langle l_0 : S \rangle$, which gives us the first item of the conclusion, with $S <: S_{l_0}$. We now just have to notice that $\Gamma_2 = \Gamma_3\{o.f' \mapsto S\}$ and that (a) is independent of the type of f' just like it is of the type of f , and we can conclude similarly to the two previous cases. \square

Lemma 7.10 (Substitution) *If $\text{this} : C[F], x : T' * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'] * \text{this}$, and if $\Gamma(r) = C[F]$, then:*

1. *if T' is a base type (i.e. neither an object type nor a link) and v is a literal value of that type, or if v is an access point name declared with type $\langle \Sigma \rangle$ and $\llbracket \langle \Sigma \rangle \rrbracket <: T'$, we have:*

$$\Gamma * r \triangleright e\{v/x\} : T \triangleleft \Gamma\{r \mapsto C[F']\} * r.$$

2. *if T' is an object type and v is an object identifier or a channel endpoint, we have:*

$$\Gamma, v : T' * r \triangleright e\{v/x\} : T \triangleleft \Gamma\{r \mapsto C[F']\} * r.$$

Proof. In order to do an induction, we add the following case where x is still present in the final environment : if we have $\text{this} : C[F], x : T' * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], x : T'' * \text{this}$, and if T' is an object type and v is an object identifier, then we have $\Gamma, v : T' * r \triangleright e\{v/x\} : T \triangleleft \Gamma\{r \mapsto C[F']\}, v : T'' * r$.

We prove this by induction on the derivation of $\text{this} : C[F], x : T' * \text{this} \triangleright e : T \triangleleft \text{this} : C[F'], V * \text{this}$ (where V is either empty or $v : T''$ depending on the case). For most toplevel rules, the result is immediate. The only ones for which it is not are T-VAR and T-LINVAR. For T-VAR the result is obtained using either T-NUL if T' is Null or T-LABEL and T-SUB if it is an enumerated type. In the case of an extension adding new base types, we assume there is a similar rule to type the corresponding literal values. For T-LINVAR, if v is an access point name the result is obtained using T-NAME and T-SUB. Otherwise, v is an object identifier and the result is obtained using T-REF, noticing that because $\Gamma(r)$ is defined and v is not in Γ , the path r does not start with v and the premise is satisfied.

Lemma 7.11 (Typability of Subterms) *If \mathcal{D} is a derivation of $\Gamma * r \triangleright \mathcal{E}(e) : T \triangleleft \Gamma' * r'$ then there exist Γ_1, r_1 and U such that \mathcal{D} has a subderivation \mathcal{D}' concluding $\Gamma * r \triangleright e : U \triangleleft \Gamma_1 * r_1$ and the position of \mathcal{D}' in \mathcal{D} corresponds to the position of the hole in \mathcal{E} .*

Proof. A straightforward induction on the structure of \mathcal{E} ; the expression e is always at the extreme left of the typing derivation for $\mathcal{E}(e)$.

Lemma 7.12 (Replacement) *If*

1. *\mathcal{D} is a derivation of $\Gamma * r \triangleright \mathcal{E}(e) : T \triangleleft \Gamma' * r'$*
2. *\mathcal{D}' is a subderivation of \mathcal{D} concluding $\Gamma * r \triangleright e : U \triangleleft \Gamma_1 * r_1$*
3. *the position of \mathcal{D}' in \mathcal{D} corresponds to the position of the hole in \mathcal{E}*
4. *$\Gamma'' * r'' \triangleright e' : U \triangleleft \Gamma_1 * r_1$*

*then $\Gamma'' * r'' \triangleright \mathcal{E}(e') : T \triangleleft \Gamma' * r'$.*

Proof. Replace \mathcal{D}' in \mathcal{D} by the derivation of $\Gamma'' * r'' \triangleright e' : U \triangleleft \Gamma_1 * r_1$.